



**ADOBE PHOTOSHOP CC 2014**

**JAVASCRIPT SCRIPTING REFERENCE**



© 2014 Adobe Systems Incorporated. All rights reserved.

Adobe® Photoshop® CC 2014 JavaScript Scripting Reference for Windows® and Macintosh®.

NOTICE: All information contained herein is the property of Adobe Systems Incorporated. No part of this publication (whether in hardcopy or electronic form) may be reproduced or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written consent of Adobe Systems Incorporated. The software described in this document is furnished under license and may only be used or copied in accordance with the terms of such license.

This publication and the information herein is furnished AS IS, is subject to change without notice, and should not be construed as a commitment by Adobe Systems Incorporated. Adobe Systems Incorporated assumes no responsibility or liability for any errors or inaccuracies, makes no warranty of any kind (express, implied, or statutory) with respect to this publication, and expressly disclaims any and all warranties of merchantability, fitness for particular purposes, and noninfringement of third party rights.

Any references to company names in sample templates are for demonstration purposes only and are not intended to refer to any actual organization.

Adobe®, the Adobe logo, Acrobat®, GoLive®, InDesign®, Illustrator®, Photoshop® are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.

Apple®, Mac OS®, and Macintosh® are trademarks of Apple Computer, Inc., registered in the United States and other countries. Microsoft®, and Windows® are either registered trademarks or trademarks of Microsoft Corporation in the United States and other countries. JavaScript™ and all Java-related marks are trademarks or registered trademarks of Sun Microsystems, Inc. in the United States and other countries. UNIX® is a registered trademark of The Open Group.

All other trademarks are the property of their respective owners.

If this guide is distributed with software that includes an end user agreement, this guide, as well as the software described in it, is furnished under license and may be used or copied only in accordance with the terms of such license. Except as permitted by any such license, no part of this guide may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, recording, or otherwise, without the prior written permission of Adobe Systems Incorporated. Please note that the content in this guide is protected under copyright law even if it is not distributed with software that includes an end user license agreement.

The content of this guide is furnished for informational use only, is subject to change without notice, and should not be construed as a commitment by Adobe Systems Incorporated. Adobe Systems Incorporated assumes no responsibility or liability for any errors or inaccuracies that may appear in the informational content contained in this guide.

Adobe Systems Incorporated, 345 Park Avenue, San Jose, California 95110, USA.

# Contents

<b>1</b>	<b>Introduction .....</b>	<b>32</b>
	JavaScript support in Adobe Photoshop CC 2014 .....	32
	Executing scripts .....	33
	Installing scripts .....	33
	Executing other scripts .....	33
	Startup scripts .....	33
	Object model usage and naming .....	34
<b>2</b>	<b>JavaScript Object Reference .....</b>	<b>35</b>
	Object descriptions.....	35
	Properties notation .....	35
	displayDialogs.....	35
	Methods notation .....	35
	crop.....	36
	ActionDescriptor .....	37
	Properties.....	37
	count .....	37
	typename .....	37
	Methods .....	37
	clear .....	37
	erase .....	37
	fromStream .....	37
	getBoolean.....	37
	getClass.....	37
	getData.....	37
	getDouble .....	37
	getEnumerationType .....	37
	getEnumerationValue.....	37
	getInteger.....	37
	getKey.....	37
	getLargeInteger .....	38
	getList .....	38
	getObjectType.....	38
	getObjectValue.....	38
	getPath .....	38
	getReference .....	38
	getString .....	38
	getType .....	38
	getUnitDoubleType .....	38
	getUnitDoubleValue.....	38
	hasKey.....	38
	isEqual.....	38
	putBoolean .....	38
	putClass.....	38
	putData .....	38
	putDouble .....	38

putEnumerated .....	38
putInteger .....	39
putLargeInteger .....	39
putList .....	39
putObject .....	39
putPath .....	39
putReference .....	39
putString .....	39
putUnitDouble .....	39
toStream .....	39
ActionList .....	40
Properties .....	40
count .....	40
typename .....	40
Methods .....	40
clear .....	40
getBoolean .....	40
getClass .....	40
getData .....	40
getDouble .....	40
getEnumerationType .....	40
getEnumerationValue .....	40
getInteger .....	40
getLargeInteger .....	41
getList .....	41
getObjectType .....	41
getObjectValue .....	41
getPath .....	41
getReference .....	41
getString .....	41
getType .....	41
getUnitDoubleType .....	41
getUnitDoubleValue .....	41
putBoolean .....	41
putClass .....	41
putData .....	41
putDouble .....	41
putEnumerated .....	41
putInteger .....	41
putLargeInteger .....	41
putList .....	41
putObject .....	42
putPath .....	42
putReference .....	42
putString .....	42
putUnitDouble .....	42
ActionReference .....	43
Properties .....	43
typename .....	43
Methods .....	43
getContainer .....	43

getDesiredClass.....	43
getEnumeratedType.....	43
getEnumeratedValue.....	43
getForm.....	43
getIdentifier.....	43
getIndex.....	43
getName.....	43
getOffset.....	43
getProperty.....	43
putClass.....	44
putEnumerated.....	44
putIdentifier.....	44
putIndex.....	44
putName.....	44
putOffset.....	44
putProperty.....	44
Application.....	45
Properties.....	45
activeDocument.....	45
backgroundColor.....	45
build.....	45
colorSettings.....	45
displayDialogs.....	45
documents.....	45
fonts.....	45
foregroundColor.....	45
freeMemory.....	45
locale.....	46
macintoshFileTypes.....	46
measurementLog.....	46
name.....	46
notifiers.....	46
notifiersEnabled.....	46
path.....	46
playbackDisplayDialogs.....	46
playbackParameters.....	46
preferences.....	46
preferencesFolder.....	46
recentFiles.....	46
scriptingBuildDate.....	46
scriptingVersion.....	46
systemInformation.....	46
typename.....	46
version.....	47
windowsFileTypes.....	47
Methods.....	47
batch.....	47
beep.....	47
bringToFront.....	47
charIDToTypeID.....	47
doAction.....	47

eraseCustomOptions.....	47
executeAction.....	47
executeActionGet.....	47
featureEnabled.....	47
getCustomOptions.....	48
isQuicktimeAvailable.....	48
load.....	48
makeContactSheet.....	48
makePDFPresentation.....	48
makePhotoGallery.....	48
makePhotomerge.....	48
makePicturePackage.....	48
open.....	49
openDialog.....	49
purge.....	49
putCustomOptions.....	49
refresh.....	49
refreshFonts.....	49
runMenuItem.....	49
showColorPicker.....	50
stringIDToTypeID.....	50
togglePalettes.....	50
TypeIDToCharID.....	50
TypeIDToStringID.....	50
ArtLayer.....	53
Properties.....	53
allLocked.....	53
blendMode.....	53
bounds.....	53
boundsNoEffects.....	53
fillOpacity.....	53
filterMaskDensity.....	53
filterMaskFeather.....	53
grouped.....	53
isBackgroundLayer.....	53
kind.....	53
layerMaskDensity.....	54
layerMaskFeather.....	54
linkedLayers.....	54
name.....	54
opacity.....	54
parent.....	54
pixelsLocked.....	54
positionLocked.....	54
textItem.....	54
transparentPixelsLocked.....	54
typename.....	54
vectorMaskDensity.....	54
vectorMaskFeather.....	54
visible.....	54
xmpMetadata.....	54

Methods .....	55
adjustBrightnessContrast .....	55
adjustColorBalance .....	55
adjustCurves .....	55
adjustLevels .....	55
applyAddNoise .....	55
applyAverage .....	55
applyBlur .....	55
applyBlurMore .....	55
applyClouds .....	55
applyCustomFilter .....	55
applyDeInterlace .....	56
applyDespeckle .....	56
applyDifferenceClouds .....	56
applyDiffuseGlow .....	56
applyDisplace .....	56
applyDustAndScratches .....	56
applyGaussianBlur .....	56
applyGlassEffect .....	56
applyHighPass .....	56
applyLensBlur .....	57
applyLensFlare .....	57
applyMaximum .....	57
applyMedianNoise .....	57
applyMinimum .....	58
applyMotionBlur .....	58
applyNTSC .....	58
applyOceanRipple .....	58
applyOffset .....	58
applyPinch .....	58
applyPolarCoordinates .....	58
applyRadialBlur .....	58
applyRipple .....	58
applySharpen .....	58
applySharpenEdges .....	58
applySharpenMore .....	58
applyShear .....	58
applySmartBlur .....	59
applySpherize .....	59
applyStyle .....	59
applyTextureFill .....	59
applyTwirl .....	59
applyUnSharpMask .....	59
applyWave .....	59
applyZigZag .....	59
autoContrast .....	59
autoLevels .....	59
clear .....	59
copy .....	60
cut .....	60
desaturate .....	60

---

duplicate .....	60
equalize .....	60
invert .....	60
link.....	60
merge.....	60
mixChannels .....	61
move.....	61
photoFilter .....	61
posterize .....	61
rasterize.....	61
remove.....	61
resize .....	62
rotate.....	62
selectiveColor.....	62
shadowHighlight .....	62
threshold.....	62
translate .....	62
unlink .....	62
ArtLayers.....	65
Properties.....	65
length.....	65
parent.....	65
typename .....	65
Methods .....	65
add .....	65
getByName .....	65
removeAll .....	65
BatchOptions .....	66
Properties.....	66
destination .....	66
destinationFolder .....	66
errorFile .....	66
fileNaming.....	66
macintoshCompatible .....	66
overrideOpen.....	66
overrideSave.....	66
startingSerial .....	66
suppressOpen.....	66
suppressProfile .....	67
typename .....	67
unixCompatible.....	67
windowsCompatible .....	67
BitmapConversionOptions .....	68
Properties.....	68
angle.....	68
frequency.....	68
method.....	68
patternName .....	68
resolution.....	68
shape.....	68
typename .....	68



BMPSaveOptions .....	69
Properties.....	69
alphaChannels .....	69
depth.....	69
flipRowOrder .....	69
osType.....	69
rleCompression .....	69
typename .....	69
CameraRAWOpenOptions .....	70
Properties.....	70
bitsPerChannel .....	70
blueHue.....	70
blueSaturation .....	70
brightness.....	70
chromaticAberrationBY .....	70
chromaticAberrationRC.....	70
colorNoiseReduction .....	70
colorSpace.....	70
contrast .....	70
exposure .....	70
greenHue.....	70
greenSaturation .....	70
luminanceSmoothing .....	70
redHue .....	70
redSaturation .....	70
resolution.....	70
saturation .....	70
settings .....	70
shadows .....	70
shadowTint .....	70
sharpness.....	70
size .....	70
temperature.....	70
tint.....	71
typename .....	71
vignettingAmount .....	71
vignettingMidpoint .....	71
whiteBalance .....	71
Channel .....	72
Properties.....	72
color.....	72
histogram .....	72
kind .....	72
name.....	72
opacity .....	72
parent.....	72
typename .....	72
visible .....	72
Methods .....	72
duplicate .....	72
merge.....	73

---

remove.....	73
Channels.....	74
Properties.....	74
length.....	74
parent.....	74
typename .....	74
Methods .....	74
add .....	74
getByName .....	74
removeAll .....	74
CMYKColor.....	79
Properties.....	79
black .....	79
cyan.....	79
magenta.....	79
typename .....	79
yellow.....	79
ColorSampler .....	80
Properties.....	80
color.....	80
position .....	80
parent.....	80
typename .....	80
Methods .....	80
move.....	80
remove.....	80
ColorSamplers .....	81
Properties.....	81
length.....	81
parent.....	81
typename .....	81
Methods .....	81
add .....	81
removeAll .....	81
ContactSheetOptions .....	82
Properties.....	82
acrossFirst.....	82
bestFit .....	82
caption.....	82
columnCount .....	82
flatten.....	82
font.....	82
fontSize.....	82
height.....	82
horizontal .....	82
mode .....	82
resolution.....	82
rowCount.....	82
typename .....	82
useAutoSpacing.....	82
vertical .....	82

---

width .....	82
CountItem .....	83
Properties.....	83
position .....	83
parent.....	83
typename .....	83
Methods .....	83
remove.....	83
CountItems .....	84
Properties.....	84
length.....	84
parent.....	84
typename .....	84
Methods .....	84
add .....	84
getByName .....	84
removeAll .....	84
DCS1_SaveOptions .....	85
Properties.....	85
dCS .....	85
embedColorProfile.....	85
encoding.....	85
halftoneScreen .....	85
interpolation.....	85
preview .....	85
transferFunction.....	85
typename .....	85
vectorData.....	85
DCS2_SaveOptions .....	86
Properties.....	86
dCS .....	86
embedColorProfile.....	86
encoding.....	86
halftoneScreen .....	86
interpolation.....	86
multiFileDCS .....	86
preview .....	86
spotColors .....	86
transferFunction.....	86
typename .....	86
vectorData.....	86
DICOMOpenOptions .....	87
Properties.....	87
anonymize.....	87
columns.....	87
reverse .....	87
rows .....	87
showOverlays.....	87
typename .....	87
windowLevel .....	87
windowWidth .....	87

---

Document .....	88
Properties.....	88
activeChannels .....	88
activeHistoryBrushSource .....	88
activeHistoryState .....	88
activeLayer .....	88
artLayers.....	88
backgroundLayer.....	88
bitsPerChannel .....	88
channels.....	88
colorProfileName .....	88
colorProfileType .....	88
colorSamplers .....	88
componentChannels.....	88
countItems .....	89
fullName.....	89
guides .....	89
height.....	89
histogram .....	89
historyStates.....	89
info .....	89
layerComps .....	89
layers .....	89
layerSets.....	89
managed.....	89
measurementScale .....	89
mode.....	89
name.....	89
parent.....	89
path.....	89
pathItems .....	89
pixelAspectRatio .....	89
printSettings.....	89
quickMaskMode.....	90
resolution.....	90
saved .....	90
selection.....	90
typename .....	90
width .....	90
xmpMetadata.....	90
Methods .....	91
autoCount .....	91
changeMode .....	91
close.....	91
convertProfile.....	91
crop.....	91
duplicate .....	91
exportDocument .....	92
flatten.....	92
flipCanvas .....	92
importAnnotations .....	92

mergeVisibleLayers .....	92
paste .....	92
print .....	92
printOneCopy .....	92
rasterizeAllLayers .....	92
recordMeasurements .....	92
resizeCanvas .....	92
resizeImage .....	93
revealAll .....	93
rotateCanvas .....	93
save .....	93
saveAs .....	93
splitChannels .....	93
suspendHistory .....	93
trap .....	93
trim .....	94
DocumentPrintSettings .....	96
Properties .....	96
backgroundColor .....	96
bleedWidth .....	96
caption .....	96
centerCropMarks .....	96
colorBars .....	96
copies .....	96
cornerCropMarks .....	96
colorHandling .....	96
activePrinter .....	96
flip .....	96
hardProof .....	96
interpolate .....	96
labels .....	96
mapBlack .....	96
negative .....	96
renderIntent .....	96
posX .....	96
posY .....	96
printBorder .....	96
printerName .....	96
printSpace .....	96
registrationMarks .....	96
scale .....	97
vectorData .....	97
Methods .....	98
setPagePosition .....	98
DocumentInfo .....	99
Properties .....	99
author .....	99
authorPosition .....	99
caption .....	99
captionWriter .....	99
category .....	99

city.....	99
copyrighted.....	99
copyrightNotice.....	99
country.....	99
creationDate.....	99
credit.....	99
exif.....	99
headline.....	99
instructions.....	99
jobName.....	99
keywords.....	99
ownerUrl.....	99
parent.....	100
provinceState.....	100
source.....	100
supplementalCategories.....	100
title.....	100
transmissionReference.....	100
typename.....	100
urgency.....	100
Documents.....	102
Properties.....	102
length.....	102
parent.....	102
typename.....	102
Methods.....	102
add.....	102
getByName.....	102
EPSSaveOptions.....	103
Properties.....	103
antiAlias.....	103
constrainProportions.....	103
height.....	103
mode.....	103
resolution.....	103
typename.....	103
width.....	103
EPSSaveOptions.....	104
Properties.....	104
embedColorProfile.....	104
encoding.....	104
halftoneScreen.....	104
interpolation.....	104
preview.....	104
psColorManagement.....	104
transferFunction.....	104
transparentWhites.....	104
typename.....	104
vectorData.....	104
ExportOptionsIllustrator.....	105
Properties.....	105

path.....	105
pathName.....	105
typename .....	105
ExportOptionsSaveForWeb .....	106
Properties.....	106
blur.....	106
colorReduction .....	106
colors.....	106
dither.....	106
ditherAmount .....	106
format .....	106
includeProfile .....	106
interlaced.....	106
lossy.....	106
matteColor .....	106
optimized .....	106
PNG8.....	106
quality .....	107
transparency.....	107
transparencyAmount.....	107
transparencyDither .....	107
typename .....	107
webSnap .....	107
File.....	108
Folder.....	108
GalleryBannerOptions .....	109
Properties.....	109
contactInfo.....	109
date.....	109
font.....	109
fontSize.....	109
photographer.....	109
siteName .....	109
typename .....	109
GalleryCustomColorOptions .....	110
Properties.....	110
activeLinkColor.....	110
backgroundColor.....	110
bannerColor.....	110
linkColor.....	110
textColor .....	110
typename .....	110
visitedLinkColor.....	110
GalleryImagesOptions .....	111
Properties.....	111
border .....	111
caption.....	111
dimension.....	111
font.....	111
fontSize.....	111
imageQuality.....	111

includeCopyright.....	111
includeCredits.....	111
includeFilename.....	111
includeTitle .....	111
numericLinks.....	111
resizeConstraint .....	112
resizeImages.....	112
typename .....	112
GalleryOptions.....	113
Properties.....	113
addSizeAttributes.....	113
bannerOptions .....	113
customColorOptions .....	113
emailAddress.....	113
imagesOptions .....	113
includeSubFolders .....	113
layoutStyle .....	113
preserveAllMetadata .....	113
securityOptions .....	113
thumbnailOptions.....	113
typename .....	113
useShortExtension .....	113
useUTF8Encoding .....	113
GallerySecurityOptions .....	114
Properties.....	114
content.....	114
font.....	114
fontSize.....	114
opacity.....	114
text.....	114
textColor .....	114
textPosition.....	114
textRotate.....	114
typename .....	114
GalleryThumbnailOptions.....	115
Properties.....	115
border .....	115
caption.....	115
columnCount .....	115
dimension.....	115
font.....	115
fontSize.....	115
includeCopyright.....	115
includeCredits.....	115
includeFilename.....	115
includeTitle .....	115
rowCount.....	115
size .....	115
typename .....	115
GIFSaveOptions.....	116
Properties.....	116



colors.....	116
dither.....	116
ditherAmount .....	116
forced.....	116
interlaced.....	116
matte .....	116
palette.....	116
preserveExactColors .....	116
transparency.....	116
typename .....	116
GrayColor.....	117
Properties.....	117
gray .....	117
typename .....	117
Guide.....	118
Properties.....	118
direction.....	118
coordinate .....	118
Guides.....	119
Properties.....	119
length.....	119
parent.....	119
typename .....	119
Methods .....	119
add .....	119
getByName .....	119
HistoryState .....	120
Properties.....	120
name.....	120
parent.....	120
snapshot .....	120
typename .....	120
HistoryStates .....	121
Properties.....	121
length.....	121
parent.....	121
typename .....	121
Methods .....	121
getByName .....	121
HSBColor.....	122
Properties.....	122
brightness.....	122
hue .....	122
saturation .....	122
typename .....	122
IndexedConversionOptions .....	123
Properties.....	123
colors.....	123
dither.....	123
ditherAmount .....	123
forced.....	123

matte.....	123
palette.....	123
preserveExactColors.....	123
transparency.....	123
typename.....	123
JPEGSaveOptions.....	124
Properties.....	124
embedColorProfile.....	124
formatOptions.....	124
matte.....	124
quality.....	124
scans.....	124
typename.....	124
LabColor.....	125
Properties.....	125
a.....	125
b.....	125
l.....	125
typename.....	125
LayerComp.....	126
Properties.....	126
appearance.....	126
comment.....	126
name.....	126
parent.....	126
position.....	126
selected.....	126
typename.....	126
visibility.....	126
Methods.....	126
apply.....	126
recapture.....	126
remove.....	126
resetfromComp.....	126
LayerComps.....	127
Properties.....	127
length.....	127
parent.....	127
typename.....	127
Methods.....	127
add.....	127
getByName.....	127
removeAll.....	127
Layers.....	128
Properties.....	128
length.....	128
parent.....	128
typename.....	128
Methods.....	128
getByName.....	128
removeAll.....	128

LayerSet .....	129
Properties.....	129
allLocked.....	129
artLayers.....	129
blendMode.....	129
bounds.....	129
enabledChannels.....	129
layers .....	129
layerSets.....	129
linkedLayers.....	129
name.....	129
opacity .....	129
parent.....	129
typename .....	129
visible .....	129
Methods .....	130
duplicate .....	130
link.....	130
merge.....	130
move.....	130
remove.....	130
resize .....	130
rotate.....	130
translate .....	130
unlink .....	130
LayerSets .....	131
Properties.....	131
length.....	131
parent.....	131
typename .....	131
Methods .....	131
add .....	131
getByName .....	131
removeAll .....	131
MeasurementLog .....	133
Methods .....	133
exportMeasurements.....	133
deleteMeasurements .....	133
MeasurementScale .....	134
Properties.....	134
pixelLength .....	134
logicalLength .....	134
logicalUnits .....	134
NoColor .....	135
Properties.....	135
typename .....	135
Notifier.....	136
Properties.....	136
event.....	136
eventClass .....	136
eventFile .....	136

parent.....	136
typename .....	136
Methods .....	136
remove.....	136
Notifiers.....	137
Properties.....	137
length.....	137
parent.....	137
typename .....	137
Methods .....	137
add .....	137
removeAll .....	137
PathItem .....	138
Properties.....	138
kind .....	138
name.....	138
parent.....	138
subPathItems .....	138
typename .....	138
Methods .....	138
deselect .....	138
duplicate .....	138
fillPath.....	138
makeClippingPath.....	139
makeSelection .....	139
remove.....	139
select .....	139
strokePath .....	139
PathItems .....	142
Properties.....	142
length.....	142
parent.....	142
typename .....	142
Methods .....	142
add .....	142
getByName .....	142
removeAll .....	142
PathPoint.....	143
Properties.....	143
anchor.....	143
kind .....	143
leftDirection.....	143
parent.....	143
rightDirection.....	143
typename .....	143
PathPointInfo.....	144
Properties.....	144
anchor.....	144
kind .....	144
leftDirection.....	144
rightDirection.....	144

---

typename .....	144
PathPoints .....	146
Properties .....	146
length .....	146
parent .....	146
typename .....	146
PDFOpenOptions .....	147
Properties .....	147
antiAlias .....	147
bitsPerChannel .....	147
constrainProportions .....	147
cropPage .....	147
height .....	147
mode .....	147
name .....	147
page .....	147
resolution .....	147
suppressWarnings .....	147
typename .....	147
usePageNumber .....	147
width .....	147
PDFSaveOptions .....	148
Properties .....	148
alphaChannels .....	148
annotations .....	148
colorConversion .....	148
convertToEightBit .....	148
description .....	148
destinationProfile .....	148
downgradeColorProfile .....	148
downSample .....	148
downSampleSize .....	148
downSampleSizeLimit .....	148
embedColorProfile .....	148
embedFonts .....	148
embedThumbnail .....	148
encoding .....	148
interpolation .....	148
jpegQuality .....	149
layers .....	149
optimizeForWeb .....	149
outputCondition .....	149
outputConditionID .....	149
PDFCompatibility .....	149
PDFStandard .....	149
preserveEditing .....	149
presetFile .....	149
profileInclusionPolicy .....	149
registryName .....	149
spotColors .....	149
tileSize .....	149

transparency.....	149
typename .....	149
useOutlines .....	149
vectorData.....	150
view.....	150
PhotoCDOpenOptions .....	151
Properties.....	151
colorProfileName .....	151
colorSpace.....	151
orientation.....	151
pixelSize .....	151
resolution.....	151
typename .....	151
PhotoshopSaveOptions .....	152
Properties.....	152
alphaChannels .....	152
annotations.....	152
embedColorProfile.....	152
layers .....	152
spotColors .....	152
typename .....	152
PICTFileSaveOptions .....	153
Properties.....	153
alphaChannels .....	153
compression .....	153
embedColorProfile.....	153
resolution.....	153
typename .....	153
PICTResourceSaveOptions.....	154
Properties.....	154
alphaChannels .....	154
compression .....	154
embedColorProfile.....	154
name.....	154
resolution.....	154
resourceID .....	154
typename .....	154
PicturePackageOptions.....	155
Properties.....	155
content .....	155
flatten.....	155
font.....	155
fontSize.....	155
layout .....	155
mode .....	155
opacity .....	155
resolution.....	155
text .....	155
textColor .....	155
textPosition.....	155
textRotate.....	155

typename .....	155
PixarSaveOptions .....	156
Properties.....	156
alphaChannels .....	156
typename .....	156
PNGSaveOptions .....	157
Properties.....	157
compression .....	157
interlaced.....	157
typename .....	157
Preferences .....	158
Properties.....	158
additionalPluginFolder.....	158
appendExtension.....	158
askBeforeSavingLayeredTIFF.....	158
autoUpdateOpenDocuments .....	158
beepWhenDone.....	158
colorChannelsInColor .....	158
colorPicker.....	158
columnGutter.....	158
columnWidth .....	158
createFirstSnapshot.....	158
dynamicColorSliders.....	158
editLogItems .....	158
exportClipboard.....	159
fontPreviewSize.....	159
fullSizePreview.....	159
gamutWarningOpacity.....	159
gridSize .....	159
gridStyle .....	159
gridSubDivisions .....	159
guideStyle.....	159
iconPreview .....	159
imageCacheLevels .....	159
imagePreviews .....	159
interpolation.....	159
keyboardZoomResizesWindows.....	159
macOSThumbnail.....	159
maximizeCompatibility .....	159
maxRAMuse.....	159
nonLinearHistory .....	159
numberOfHistoryStates .....	160
otherCursors.....	160
paintingCursors.....	160
parent.....	160
pixelDoubling .....	160
pointSize .....	160
recentFileListLength.....	160
rulerUnits .....	160
saveLogItems .....	160
saveLogItemsFile .....	160

savePaletteLocations .....	160
showAsianTextOptions .....	160
showEnglishFontNames .....	160
showSliceNumber .....	160
showToolTips .....	160
smartQuotes .....	160
textFontSize .....	160
typename .....	160
typeUnits .....	161
useAdditionalPluginFolder .....	161
useHistoryLog .....	161
useLowerCaseExtension .....	161
useShiftKeyForToolSwitch .....	161
useVideoAlpha .....	161
windowsThumbnail .....	161
PresentationOptions .....	162
Properties .....	162
autoAdvance .....	162
includeFilename .....	162
interval .....	162
loop .....	162
magnification .....	162
PDFFileOptions .....	162
presentation .....	162
transition .....	162
typename .....	162
RawFormatOpenOptions .....	163
Properties .....	163
bitsPerChannel .....	163
byteOrder .....	163
channelNumber .....	163
headerSize .....	163
height .....	163
interleaveChannels .....	163
retainHeader .....	163
typename .....	163
width .....	163
RawSaveOptions .....	164
Properties .....	164
alphaChannels .....	164
spotColors .....	164
typename .....	164
RGBColor .....	165
Properties .....	165
blue .....	165
green .....	165
hexValue .....	165
red .....	165
typename .....	165
Selection .....	166
Properties .....	166



bounds.....	166
parent.....	166
solid .....	166
typename .....	166
Methods .....	166
clear .....	166
contract .....	166
copy .....	166
cut.....	166
deselect .....	166
expand.....	166
feather.....	166
fill .....	167
grow .....	167
invert.....	167
load.....	167
makeWorkPath .....	167
resize .....	167
resizeBoundary.....	167
rotate.....	167
rotateBoundary .....	167
select .....	167
selectAll.....	167
selectBorder.....	168
similar.....	168
smooth .....	168
store.....	168
stroke.....	168
translate .....	168
translateBoundary.....	168
SGIRGBSaveOptions .....	171
Properties.....	171
alphaChannels.....	171
spotColors .....	171
typename .....	171
SolidColor.....	172
Properties.....	172
cmyk .....	172
gray .....	172
hsb.....	172
lab.....	172
model.....	172
nearestWebColor .....	172
rgb.....	172
typename .....	172
Methods .....	172
isEqual.....	172
SubPathInfo.....	173
Properties.....	173
closed.....	173
entireSubPath .....	173

operation .....	173
typename .....	173
SubPathItem.....	174
Properties.....	174
closed.....	174
operation .....	174
parent.....	174
pathPoints .....	174
typename .....	174
SubPathItems.....	175
Properties.....	175
length.....	175
parent.....	175
typename .....	175
TargaSaveOptions.....	176
Properties.....	176
alphaChannels .....	176
resolution.....	176
rleCompression .....	176
typename .....	176
TextFont.....	177
Properties.....	177
family.....	177
name.....	177
parent.....	177
postScriptName .....	177
style.....	177
typename .....	177
TextFonts.....	178
Properties.....	178
length.....	178
parent.....	178
typename .....	178
Methods .....	178
getByName .....	178
TextItem.....	179
Properties.....	179
alternateLigatures .....	179
antiAliasMethod.....	179
autoKerning.....	179
autoLeadingAmount.....	179
baselineShift .....	179
capitalization .....	179
color.....	179
contents .....	179
desiredGlyphScaling.....	179
desiredLetterScaling.....	180
desiredWordScaling .....	180
direction .....	180
fauxBold .....	180
fauxItalic.....	180

firstLineIndent.....	180
font.....	180
hangingPunctuation .....	180
height.....	180
horizontalScale .....	180
hyphenateAfterFirst.....	181
hyphenateBeforeLast .....	181
hyphenateCapitalWords .....	181
hyphenateWordsLongerThan.....	181
hyphenation .....	181
hyphenationZone.....	181
hyphenLimit .....	181
justification .....	181
kind .....	181
language .....	181
leading .....	181
leftIndent .....	181
ligatures .....	181
maximumGlyphScaling .....	181
maximumLetterScaling .....	182
maximumWordScaling.....	182
minimumGlyphScaling.....	182
minimumLetterScaling.....	183
minimumWordScaling.....	183
noBreak .....	183
oldStyle.....	183
parent.....	183
position .....	183
rightIndent.....	183
size .....	183
spaceAfter .....	183
spaceBefore .....	184
strikeThru.....	184
textComposer .....	184
tracking.....	184
typename .....	184
underline.....	184
useAutoLeading.....	184
verticalScale.....	184
warpBend .....	184
warpDirection .....	184
warpHorizontalDistortion.....	184
warpStyle.....	184
warpVerticalDistortion.....	184
width .....	184
Methods .....	185
convertToShape.....	185
createPath .....	185
TiffSaveOptions.....	186
Properties.....	186
alphaChannels.....	186

annotations.....	186
byteOrder .....	186
embedColorProfile.....	186
imageCompression.....	186
interleaveChannels .....	186
jpegQuality .....	186
layerCompression.....	186
layers .....	186
saveImagePyramid.....	186
spotColors .....	186
transparency.....	186
typename .....	186
UnitValue .....	187
xmpMetadata .....	188
Properties.....	188
parent.....	188
rawData .....	188
typename .....	188
<b>3 JavaScript Resource.....</b>	<b>189</b>
JavaScript resource syntax.....	189
Basic JavaScript resource example .....	190
Enable-info grammar .....	190
Undefined values in enable-info evaluation .....	192
Using the "in" function .....	193
Action Manager automation.....	193
Terminology dictionary .....	193
Value type defintions .....	194
Uniqueness rules for terminology entries.....	195
Terminology definition example.....	195
<b>4 Scripting Constants .....</b>	<b>197</b>
AdjustmentReference .....	197
AnchorPosition .....	197
AntiAlias .....	197
AutoKernType .....	197
BatchDestinationType .....	197
BitmapConversionType.....	198
BitmapHalfToneType .....	198
BitsPerChannelType.....	198
BlendMode.....	198
BMPDepthType .....	198
ByteOrder .....	199
CameraRAWSettingsType.....	199
CameraRAWSize.....	199
ChangeMode.....	199
ChannelType .....	199
ColorBlendMode.....	200
ColorModel .....	200
ColorPicker .....	200
ColorProfileType .....	200
ColorReductionType.....	200

ColorSpaceType .....	200
CopyrightedType.....	200
CreateFields .....	201
CropToType .....	201
DCSType.....	201
DepthMapSource .....	201
DescValueType .....	201
DialogModes .....	201
Direction .....	201
DisplacementMapType .....	202
Dither .....	202
DocPositionStyle.....	202
DocumentFill.....	202
DocumentMode.....	202
EditLogItemsType.....	202
ElementPlacement.....	202
EliminateFields .....	202
ExportType.....	202
Extension .....	202
FileNamingType.....	203
FontPreviewType.....	203
FontSize.....	203
ForcedColors .....	203
FormatOptions .....	203
GalleryConstrainType.....	203
GalleryFontType.....	204
GallerySecurityTextColorType .....	204
GallerySecurityTextPositionType .....	204
GallerySecurityTextRotateType .....	204
GallerySecurityType .....	204
GalleryThumbSizeType.....	204
Geometry.....	204
GridLineStyle .....	204
GridSize .....	204
GuideLineStyle.....	205
IllustratorPathType.....	205
Intent.....	205
Justification.....	205
Language.....	205
LayerCompression.....	205
LayerKind.....	206
LensType.....	206
MagnificationType .....	206
MatteType .....	206
MeasurementRange .....	206
MeasurementSource .....	206
NewDocumentMode.....	206
NoiseDistribution.....	207
OffsetUndefinedAreas .....	207
OpenDocumentMode.....	207
OpenDocumentType.....	207

OperatingSystem.....	207
Orientation.....	207
OtherPaintingCursors.....	208
PaintingCursors.....	208
PaletteType.....	208
PathKind.....	208
PDFCompatibility.....	208
PDFEncoding.....	208
PDFResample.....	209
PDFStandard.....	209
PhotoCDCColorSpace.....	209
PhotoCDSIZE.....	209
PICTBitsPerPixels.....	209
PICTCompression.....	209
PicturePackageTextType.....	209
PointKind.....	210
PointType.....	210
PolarConversionType.....	210
Preview.....	210
PrintColorHandling.....	210
PurgeTarget.....	210
QueryStateType.....	210
RadialBlurMethod.....	210
RadialBlurQuality.....	210
RasterizeType.....	210
ReferenceFormType.....	210
ResampleMethod.....	211
RippleSize.....	211
SaveBehavior.....	211
SaveDocumentType.....	211
SaveEncoding.....	211
SaveLogItemsType.....	211
SaveOptions.....	211
SelectionType.....	212
ShapeOperation.....	212
SmartBlurMode.....	212
SmartBlurQuality.....	212
SourceSpaceType.....	212
SpherizeMode.....	212
StrikeThruType.....	212
StrokeLocation.....	212
TargaBitsPerPixels.....	212
TextCase.....	213
TextComposer.....	213
TextType.....	213
TextureType.....	213
TIFFEncoding.....	213
ToolType.....	213
TransitionType.....	213
TrimType.....	214
TypeUnits.....	214

---

UndefinedAreas .....	214
UnderlineType .....	214
Units.....	214
Urgency.....	214
WarpStyle .....	214
WaveType.....	215
WhiteBalanceType.....	215
ZigZagType.....	215
<b>Appendix A: Event ID Codes .....</b>	<b>216</b>
<b>Index .....</b>	<b>224</b>

This reference describes the objects and methods in the Adobe® Photoshop® CC 2014® JavaScript™ type library. A companion document, *Photoshop CC 2014 Scripting Guide*, describes basic scripting concepts and the Photoshop object model. This document provides reference details of the Photoshop object model, and additional information on JavaScript-specific features.

Adobe Photoshop CC 2014 uses ExtendScript, Adobe’s extended implementation of JavaScript. See [JavaScript support in Adobe Photoshop CC 2014](#) for additional information.

This book contains the following sections:

- This introduction, which describes scripting support in Adobe Photoshop CC 2014, and lists changes to the JavaScript interface since the previous release.
- [JavaScript Object Reference](#), which provides a complete reference for all Photoshop DOM objects and commands.
- [Scripting Constants](#), which lists all enumerations used in the Photoshop type library.

## JavaScript support in Adobe Photoshop CC 2014

For a JavaScript file to be recognized by Photoshop as a valid script file, it must use either a `.js` or a `.jsx` extension.

On the Mac OS, there is no difference in the way scripts with the two extensions function. On Windows, if the script files is opened from inside Photoshop, there is no difference between using the `.js` and `.jsx` extension. However, if the script is launched by double-clicking on it, a script with the `.js` extension is interpreted with the Microsoft JScript engine, and it cannot launch Adobe Photoshop CC 2014. For Windows, using the `.jsx` extension is preferable, since it interprets the script with the ExtendScript engine.

All of the Adobe Creative Cloud applications, including Adobe Photoshop CC 2014, use ExtendScript, Adobe’s extended implementation of JavaScript. ExtendScript files are distinguished by the `.jsx` extension. ExtendScript offers all standard JavaScript features, plus additional features and utilities, such as:

- A debugging environment (the ExtendScript Toolkit)
- A localization utility
- Tools that allow you to combine scripts and direct them to particular applications
- Platform-independent file and folder representation

Many of the JavaScript objects and methods use objects defined in ExtendScript, such as the `File` object, the `Folder` object, and the `UnitValue` object. For that reason, using the `.jsx` extension for your script files is preferable.

For details of these and additional features, see the *JavaScript Tools Guide*. This document is installed with Creative Cloud applications at these locations:

- In Windows:  
C:\Program Files\Adobe\Adobe Utilities\ExtendScript Toolkit CC 2014\SDK



- In Mac OS:

Applications/Utilities/Adobe Utilities/ExtendScript Toolkit CC/SDK

The latest versions of this document and of the ExtendScript Toolkit, can also be downloaded from Adobe Developer Center, <http://www.adobe.com/devnet/>.

## Executing scripts

The Adobe Photoshop CC 2014 interface includes a Scripts menu (**File > Scripts**) which provides quick and easy access to your JavaScripts. Scripts can be listed directly as menu items that run when you select them, or you can navigate to and run any JavaScript in your file system.

If Adobe Photoshop CC 2014 encounters an error during script execution, it displays the error message.

## Installing scripts

To install a JavaScript in the Scripts menu, place it in the Scripts folder (**Photoshop CC 2014/Presets/Scripts**). The names of the scripts in the Scripts folder, without the file name extension, will be displayed in the Scripts menu. Any number of scripts may be installed in the Scripts menu.

Scripts added to the Scripts folder while Adobe Photoshop CC 2014 is running will not appear in the Scripts menu until the next time you launch the application.

All scripts found in the Scripts folder and sub-folders are displayed at the top level of the **File > Scripts** menu. The addition of sub-folders does not add a hierarchical organization to the Scripts menu.

## Executing other scripts

The **Browse** item at the end of the **Scripts** menu (**File > Scripts > Browse**) allows you to execute scripts which are not installed in the Scripts folder. You can also use Browse to select scripts installed in the Scripts folder after the application was last launched.

Selecting **Browse** displays a file browser dialog which allows you to select a script file for execution. Only `.js` or `.jsx` files are displayed in the browse dialog. When you select a script file, it is executed the same way as an installed script.

## Startup scripts

On startup, Adobe Photoshop CC 2014 executes all `.jsx` files that it finds in the startup folders.

- On Windows, the startup folder for user-defined scripts is:

C:\Program Files\Common Files\Adobe\Startup Scripts CC\Adobe Photoshop

- On Mac OS, the startup folder for user-defined scripts is:

~/Library/Application Support/Adobe/Startup Scripts CC/Adobe Photoshop

If a script is meant to be executed only by Adobe Photoshop CC 2014, it must include code such as the following:

```
if( BridgeTalk.appName == "photoshop" ) {  
    //continue executing script  
}
```

For additional details, see the *JavaScript Tools Guide*.

## Object model usage and naming

The JavaScript API follows JavaScript naming conventions in that all classes (object types) begin with uppercase letters and have mixed case. Typically, in JavaScript, you instantiate classes using the `new` operator:

```
new ClassName ();
```

However, in the Photoshop Object Model, it is often not necessary to do this. Major object types are collected into collection classes; for example, a list of `Document` objects is contained in a `Documents` collection object. You then access the collection object through a corresponding collection property in its container in the object hierarchy.

For example, the collection of all open documents is contained in the top-level `Application` object. You can access this through the global variable `app`, or simply reference its properties directly at the top level:

```
app.documents[0] // get the first loaded documented
documents[0] // this is the same
```

A collection property has the same name as the collection object, but begins with lowercase. For example, a `Document` contains a collection of `LayerSets`, and a `LayerSet` contains a collection of `ArtLayers`. To access one `ArtLayer` object in a set:

```
var myLayer = activeDocument.layerSets[0].artLayers[0];
```

The collections, as in this example, can be treated as arrays, which is useful for iteration. They also provide methods to create their contained objects, and to access them by name:

```
var newLayer = activeDocument.artLayers.add(); // Create a new ArtLayer object
newLayer.name = "My Layer"; // name it for later reference
...
var layerRef = activeDocument.artLayers.getByName("My Layer");
```

Some objects, such as the `Font` objects contained in the `app.fonts` collection, are created by the application, and never by your scripts.

Your scripts do use the JavaScript `new` operator to create helper objects, such as those that encapsulate a set of options for opening or saving a document in a particular format:

```
var opts = new PDFOpenOptions();
opts.page = 10;
app.open(myPDFFile, opts);
```

# 2

## JavaScript Object Reference

The Photoshop objects (the JavaScript type library for Adobe® Photoshop® CC 2014) are presented alphabetically and in tabular format in this chapter. Sample code for several object model classes is given to help illustrate the syntax as well as usage of the object class.

### Object descriptions

Object properties and methods are described in separate tables for each object. The following sections describe the conventions used in these descriptions.

#### Properties notation

The Properties table for an object lists the following:

- The properties defined in each object.
- The value type for each property.

When the value type is a constant or another object, the value is a hypertext link to the listing for that constant or object.

- The property's input status: read-only or read-write.
- A description that explains what the property does.

Property	Value type	What it is
<code>displayDialogs</code>	<a href="#">DialogModes</a>	Read-write. The dialog mode for the application, which controls what types of dialogs should be displayed when running scripts.

For constants, like [DialogModes](#) in the sample, click the link to go to the table that shows allowed values. Constants are represented by objects, and allowed values are properties of those objects. Specify a constant value in the form *ConstantName.VALUE*. For example:

```
app.displayDialogs = DialogModes.ERROR;
```

#### Methods notation

The Methods table for an object lists the following:

- The method name.
- The parameters list.
- The parameter value types, on lines corresponding to each parameter.
- Return value type
- A description of what the method does, and further descriptions of parameters, if needed.

Method	Parameter type	Returns	What it does
<b>crop</b> (bounds [, angle] [, width] [, height])	array of 4 <a href="#">UnitValue</a> number <a href="#">UnitValue</a> <a href="#">UnitValue</a>		Crops the document. The <code>bounds</code> parameter is an array of four coordinates for the region remaining after cropping, [left, top, right, bottom].

When a parameter type or return value is a constant or another object, the value is a hypertext link to the listing for that constant or object.

Parameters can be required or optional. Optional parameters are indicated in the table by square brackets ([ ]). In the example, the first parameter, `bounds`, is required. The remaining parameters are all optional.

You must pass a value for each required parameter. You can leave out optional parameters if there are no remaining values to pass; however, if you wish to use the default value for any optional parameter that is not the last one specified, pass `undefined` as a placeholder. You must enter the values in the order they are listed, so that the JavaScript compiler knows which value you are entering.

For example, the following passes only the required parameter (using a previously-defined variable for the bounding region):

```
app.activeDocument.crop( myRegion );
```

The following skips the `angle` parameter, specifies the `width` value, and omits the final `height` value:

```
var myWidth = new UnitValue( "500 pixels" );  
app.executeAction( myRegion, undefined, myWidth );
```

## ActionDescriptor

This object provides a dictionary-style mechanism for storing data as key-value pairs. It can be used for low-level access into Photoshop. See an example of this usage in [‘Selection sample script’ on page 168](#).

Many configuration files use serialized action descriptors to represent their data. It is used, for example, to encapsulate playback options in [Application.playbackParameters](#), and is returned by [Application.getCustomOptions\(\)](#).

### Properties

Property	Value type	What it is
<b>count</b>	number	Read-only. The number of keys contained in the descriptor.
<b>typename</b>	string	Read-only. The class name of the referenced <code>actionDescriptor</code> object.

### Methods

Method	Parameter type	Returns	What it does
<b>clear</b> ( )			Clears the descriptor.
<b>erase</b> (key)	number		Erases a key from the descriptor.
<b>fromStream</b> (value)	string		Creates a descriptor from a stream of bytes; for reading from disk.
<b>getBoolean</b> (key)	number	boolean	Gets the value of a key of type boolean.
<b>getClass</b> (key)	number	number	Gets the value of a key of type class.
<b>getData</b> (key)	number	string	Gets raw byte data as a string value.
<b>getDouble</b> (key)	number	number	Gets the value of a key of type double.
<b>getEnumerationType</b> (key)	number	number	Gets the enumeration type of a key.
<b>getEnumerationValue</b> (key)	number	number	Gets the enumeration value of a key.
<b>getInteger</b> (key)	number	number	Gets the value of a key of type integer.
<b>getKey</b> (index)	number	number	Gets the ID of the <i>N</i> th key, provided by index.

Method	Parameter type	Returns	What it does (Continued)
<b>getLargeInteger</b> (key)	number	number	Gets the value of a key of type large integer.
<b>getList</b> (key)	number	<a href="#">ActionList</a>	Gets the value of a key of type list.
<b>getObjectType</b> (key)	number	number	Gets the class ID of an object in a key of type object.
<b>getObjectValue</b> (key)	number	<a href="#">ActionDescriptor</a>	Gets the value of a key of type object.
<b>getPath</b> (key)	number	<a href="#">File</a>	Gets the value of a key of type File.
<b>getReference</b> (key)	number	<a href="#">ActionReference</a>	Gets the value of a key of type <a href="#">ActionReference</a> .
<b>getString</b> (key)	number	string	Gets the value of a key of type string.
<b>getType</b> (key)	number	<a href="#">DescValueType</a>	Gets the type of a key.
<b>getUnitDoubleType</b> (key)	number	number	Gets the unit type of a key of type UnitDouble.
<b>getUnitDoubleValue</b> (key)	number	number	Gets the value of a key of type UnitDouble.
<b>hasKey</b> (key)	number	boolean	Checks whether the descriptor contains the provided key.
<b>isEqual</b> (otherDesc)	<a href="#">ActionDescriptor</a>	boolean	Determines whether the descriptor is the same as another descriptor.
<b>putBoolean</b> (key, value)	number boolean		Sets the value for a key whose type is boolean.
<b>putClass</b> (key, value)	number number		Sets the value for a key whose type is class.
<b>putData</b> (key, value)	number string		Puts raw byte data as a string value.
<b>putDouble</b> (key, value)	number number		Sets the value for a key whose type is double.
<b>putEnumerated</b> (key, enumType, value)	number number number		Sets the enumeration type and value for a key.

Method	Parameter type	Returns	What it does (Continued)
<b>putInteger</b> (key, value)	number number		Sets the value for a key whose type is integer.
<b>putLargeInteger</b> (key, value)	number number		Sets the value for a key whose type is large integer.
<b>putList</b> (key, value)	number <a href="#">ActionList</a>		Sets the value for a key whose type is an <code>ActionList</code> object.
<b>putObject</b> (key, classID, value)	number number <a href="#">ActionDescriptor</a>		Sets the value for a key whose type is an object, represented by an Action Descriptor.
<b>putPath</b> (key, value)	number <a href="#">File</a>		Sets the value for a key whose type is path.
<b>putReference</b> (key, value)	number <a href="#">ActionReference</a>		Sets the value for a key whose type is an object reference.
<b>putString</b> (key, value)	number string		Sets the value for a key whose type is string.
<b>putUnitDouble</b> (key, unitID, value)	number number number		Sets the value for a key whose type is a unit value formatted as a double.
<b>toStream</b> ( )		string	Gets the entire descriptor as a stream of bytes, for writing to disk.

## ActionList

This object provides an array-style mechanism for storing data. It can be used for low-level access into Photoshop.

This object is ideal when storing data of the same type. All items in the list must be of the same type.

You can use the "put" methods, such as [putBoolean\(\)](#), to append new elements, and can clear the entire list using [clear\(\)](#), but cannot otherwise modify the list.

**Note:** The `ActionList` object is part of the Action Manager functionality. For details on using the Action Manager, see the *Photoshop CC 2014 Scripting Guide*.

## Properties

Property	Value type	What it is
<code>count</code>	number	Read-only. The number of commands that comprise the action.
<code>typename</code>	string	Read-only. The class name of the referenced <code>ActionList</code> object.

## Methods

With the exception of the `clear()` method, you use the methods of this object to either get the value of a specific type of data in the list or set (put) the value type.

Method	Parameter type	Returns	What it does
<code>clear()</code>			Clears the list.
<code>getBoolean(index)</code>	number	boolean	Gets the value of a list element of type boolean.
<code>getClass(index)</code>	number	number	Gets the value of a list element of type class.
<code>getData(index)</code>	number	string	Gets raw byte data as a string value.
<code>getDouble(index)</code>	number	number	Gets the value of a list element of type double.
<code>getEnumerationType(index)</code>	number	number	Gets the enumeration type of a list element.
<code>getEnumerationValue(index)</code>	number	number	Gets the enumeration value of a list element.
<code>getInteger(index)</code>	number	number	Gets the value of a list element of type integer.



Method	Parameter type	Returns	What it does (Continued)
<b>getLargeInteger</b> (index)	number	number	Gets the value of a list element of type large integer.
<b>getList</b> (index)	number	<a href="#">ActionList</a>	Gets the value of a list element of type list.
<b>getObjectType</b> (index)	number	number	Gets the class ID of a list element of type object.
<b>getObjectValue</b> (index)	number	<a href="#">ActionDescriptor</a>	Gets the value of a list element of type object.
<b>getPath</b> (index)	number	<a href="#">File</a>	Gets the value of a list element of type File.
<b>getReference</b> (index)	number	<a href="#">ActionReference</a>	Gets the value of a list element of type <a href="#">ActionReference</a> .
<b>getString</b> (index)	number	string	Gets the value of a list element of type string.
<b>getType</b> (index)	number	<a href="#">DescValueType</a>	Gets the type of a list element.
<b>getUnitDoubleType</b> (index)	number	number	Gets the unit value type of a list element of type Double.
<b>getUnitDoubleValue</b> (index)	number	number	Gets the unit value of a list element of type double.
<b>putBoolean</b> (value)	boolean		Appends a new value, true or false.
<b>putClass</b> (value)	number		Appends a new value, a class or data type.
<b>putData</b> (value)	string		Appends a new value, a string containing raw byte data.
<b>putDouble</b> (value)	number		Appends a new value, a double.
<b>putEnumerated</b> (enumType, value)	number number		Appends a new value, an enumerated (constant) value.
<b>putInteger</b> (value)	number		Appends a new value, an integer.
<b>putLargeInteger</b> (value)	number		Appends a new value, a large integer.
<b>putList</b> (value)	<a href="#">ActionList</a>		Appends a new value, a nested action list.

Method	Parameter type	Returns	What it does (Continued)
<b>putObject</b> (classID, value)	number <a href="#">ActionDescriptor</a>		Appends a new value, an object.
<b>putPath</b> (value)	<a href="#">File</a>		Appends a new value, a path.
<b>putReference</b> (value)	<a href="#">ActionReference</a>		Appends a new value, a reference to an object created in the script.
<b>putString</b> (value)	string		Appends a new value, a string.
<b>putUnitDouble</b> (classID, value)	number number		Appends a new value, a unit/value pair.

## ActionReference

This object provides information about what the action is referring to. For example, when referring to the name of something you might use `keyName`. The reference would also need to know what name you are referring to. In this case you could use `classDocument` for the name of the document or `classLayer` for the name of the layer. It can be used for low-level access into `Photoshop.Contains` data associated with an [ActionDescriptor](#).

### Properties

Property	Value type	What it does
<code>typename</code>	string	Read-only. The class name of the referenced Action object.

### Methods

Method	Parameter type	Returns	What it does
<code>getContainer</code> ( )		<a href="#">ActionReference</a>	Gets a reference contained in this reference.  Container references provide additional pieces to the reference. This looks like another reference, but it is actually part of the same reference.
<code>getDesiredClass</code> ( )		number	Gets a number representing the class of the object.
<code>getEnumeratedType</code> ( )		number	Gets the enumeration type.
<code>getEnumeratedValue</code> ( )		number	Gets the enumeration value.
<code>getForm</code> ( )		<a href="#">ReferenceFormType</a>	Gets the form of this action reference.
<code>getIdentifier</code> ( )		number	Gets the identifier value for a reference whose form is identifier.
<code>getIndex</code> ( )		number	Gets the index value for a reference in a list or array.
<code>getName</code> ( )		string	Gets the name of a reference.
<code>getOffset</code> ( )		number	Gets the offset of the object's index value.
<code>getProperty</code> ( )		number	Gets the property ID value.

Method	Parameter type	Returns	What it does (Continued)
<b>putClass</b> (desiredClass)	number		Puts a new class form and class type into the reference.
<b>putEnumerated</b> (desiredClass, enumType, value)	number number number		Puts an enumeration type and ID into a reference along with the desired class for the reference.
<b>putIdentifier</b> (desiredClass, value)	number number		Puts a new identifier and value into the reference.
<b>putIndex</b> (desiredClass, value)	number number		Puts a new index and value into the reference.
<b>putName</b> (desiredClass, value)	number string		Puts a new name and value into the reference.
<b>putOffset</b> (desiredClass, value)	number number		Puts a new offset and value into the reference.
<b>putProperty</b> (desiredClass, value)	number number		Puts a new property and value into the reference.

## Application

The Adobe Adobe Photoshop CC 2014 application object, which is the root of the object model and provides access to all other objects. This object provides application-wide information, such as application defaults and available fonts. It provides many important methods, such as those for opening files and loading documents.

To access the properties and methods, you can use the pre-defined global variable `app`. For example:

```
var docRef = app.documents.add(800, 600, 72, "docRef", NewDocumentMode.RGB);
```

The properties and methods of the `Application` object are also available at the top level; you can omit references to the `Application` object altogether. For example:

```
var docRef = documents.add(800, 600, 72, "docRef", NewDocumentMode.RGB);
```

This usage can be somewhat ambiguous; for clarity, it is recommended that you use an explicit reference to `app`.

## Properties

Property	Value type	What it is
<code>activeDocument</code>	<a href="#">Document</a>	Read-write. The frontmost document.  Setting this property is equivalent to clicking an open document in the Adobe Photoshop CC 2014 application to bring it to the front of the screen.  <b>Tip:</b> If there is no open document, accessing this property throws an exception.
<code>backgroundColor</code>	<a href="#">SolidColor</a>	Read-write. The default background color and color style for documents.
<code>build</code>	string	Read-only. Information about the application.
<code>colorSettings</code>	string	Read-write. The name of the current color settings, as selected with Edit > Color Settings.
<code>displayDialogs</code>	<a href="#">DialogModes</a>	Read-write. The dialog mode for the application, which controls what types of dialogs should be displayed when running scripts.
<code>documents</code>	<a href="#">Documents</a>	Read-only. The collection of open documents.  This is the primary point of access for documents that are currently open in the application. The array allows you to access any open document, or to iterate through all open documents.
<code>fonts</code>	<a href="#">TextFonts</a>	Read-only. The fonts installed on this system.
<code>foregroundColor</code>	<a href="#">SolidColor</a>	Read-write. The default foreground color (used to paint, fill, and stroke selections).
<code>freeMemory</code>	number	Read-only. The amount of unused memory available to Adobe Photoshop CC 2014.

Property	Value type	What it is (Continued)
<code>locale</code>	string	Read-only. The language location of the application.  An Adobe locale code consists of a 2-letter ISO-639 language code and an optional 2-letter ISO 3166 country code separated by an underscore. Case is significant. For example, <code>en_US</code> , <code>en_UK</code> , <code>ja_JE</code> , <code>de_DE</code> , <code>fr_FR</code> .
<code>macintoshFileTypes</code>	array of string	Read-only. A list of file image types Adobe Photoshop CC 2014 can open.
<code>measurementLog</code>	<a href="#">MeasurementLog</a>	The log of measurements taken.
<code>name</code>	string	Read-only. The application's name.
<code>notifiers</code>	<a href="#">Notifiers</a>	Read-only. The collection of notifiers currently configured (in the Scripts Events Manager menu in the Adobe Photoshop CC 2014 application).
<code>notifiersEnabled</code>	boolean	Read-write. True if all notifiers are enabled.
<code>path</code>	<a href="#">File</a>	Read-only. The full path to the location of the Adobe Photoshop CC 2014 application.
<code>playbackDisplayDialogs</code>	<a href="#">DialogModes</a>	Read-write. The dialog mode for playback mode, which controls what types of dialog to display when playing back a recorded action with the Actions palette.
<code>playbackParameters</code>	<a href="#">ActionDescriptor</a>	Read-write. Stores and retrieves parameters used as part of a recorded action. Can be used, for example, to control playback speed.
<code>preferences</code>	<a href="#">Preferences</a>	Read-only. The application preference settings (equivalent to selecting <b>Edit &gt; Preferences</b> in the Adobe Photoshop CC 2014 application in Windows or Photoshop > Preferences in Mac OS).
<code>preferencesFolder</code>	<a href="#">File</a>	Read-only. The full path to the Preferences folder.
<code>recentFiles</code>	array of <a href="#">File</a>	Read-only. Files in the Recent Files list.
<code>scriptingBuildDate</code>	string	Read-only. The build date of the Scripting interface.
<code>scriptingVersion</code>	string	Read-only. The version of the Scripting interface.
<code>systemInformation</code>	string	Read-only. Runtime details of the application and system.
<code>typename</code>	string	Read-only. The class name of the referenced <code>app</code> object.

Property	Value type	What it is (Continued)
<b>version</b>	string	Read-only. The version of Adobe Photoshop application you are running.
<b>windowsFileTypes</b>	array of string	Read-only. A list of file image extensions Adobe Photoshop CC 2014 can open.

## Methods

Method	Parameter type	Returns	What it does
<b>batch</b> (inputFiles, action, from [, options])	array of <a href="#">File</a> string string <a href="#">BatchOptions</a>	string	Runs the batch automation routine (similar to the <b>File &gt; Automate &gt; Batch</b> command).  The <code>inputFiles</code> parameter specifies the sources for the files to be manipulated by the batch command.
<b>beep</b> ( )			Causes a "beep" sound.
<b>bringToFront</b> ( )			Makes Adobe Photoshop CC 2014 the active (front-most) application.
<b>charIDToTypeID</b> (charID)	string	number	Converts from a four character code (character ID) to a runtime ID.
<b>doAction</b> (action, from)	string string		Plays an action from the Actions palette. The <code>action</code> parameter is the name of the action, the <code>from</code> parameter is the name of the action set.
<b>eraseCustomOptions</b> (key)	string		Erases the user object with specified ID value from the Photoshop registry.
<b>executeAction</b> (eventID [, descriptor] [, displayDialogs])	number <a href="#">ActionDescriptor</a> <a href="#">DialogModes</a>	<a href="#">ActionDescriptor</a>	Plays an Action Manager event.
<b>executeActionGet</b> (reference)	<a href="#">ActionReference</a>	<a href="#">ActionDescriptor</a>	Obtains information about a predefined or recorded action.
<b>featureEnabled</b> (name)	string	boolean	Determines whether the feature specified by <code>name</code> is enabled.  The following features are supported as values for <code>name</code> :  "photoshop/extended" "photoshop/standard" "photoshop/trial"

Method	Parameter type	Returns	What it does (Continued)
<b>getCustomOptions</b> (key)	string	<a href="#">ActionDescriptor</a>	Retrieves user objects in the Photoshop registry for the ID with value key.
<b>isQuicktimeAvailable</b> ( )		boolean	Returns true if Quicktime is installed.
<b>load</b> (document)	<a href="#">File</a>		Loads a support file (as opposed to a Photoshop image document) from the specified location.
<b>makeContactSheet</b> (inputFiles [, options])	array of <a href="#">File</a> <a href="#">ContactSheetOptions</a>	string	DEPRECATED for Adobe Photoshop CS4.
<b>makePDFPresentation</b> (inputFiles, outputFiles [, options])	array of <a href="#">File</a> <a href="#">File</a> <a href="#">PresentationOptions</a>	string	DEPRECATED for Adobe Photoshop CS4.
<b>makePhotoGallery</b> (inputFolder, outputFolder [, options])	<a href="#">File</a> <a href="#">File</a> <a href="#">GalleryOptions</a>	string	DEPRECATED for Adobe Photoshop CS4.
<b>makePhotomerge</b> (inputFiles)	array of <a href="#">File</a>	string	DEPRECATED for Adobe Photoshop CC 2014. Use provided script:  <pre>runphotomergeFromScript = true; \$.evalFile( app.path + "Presets/Scripts/Photomerge.jsx") photomerge.createPanorama( fileList, displayDialog );</pre> Merges multiple files into one, with user interaction required.
<b>makePicturePackage</b> (inputFiles [, options])	array of <a href="#">File</a> <a href="#">PicturePackageOptions</a>	string	DEPRECATED for Adobe Photoshop CS4.



Method	Parameter type	Returns	What it does (Continued)
<b>open</b> (document [, as] [, asSmartObject])	<a href="#">File</a> object or <a href="#">OpenDocumentType</a> boolean	<a href="#">Document</a>	<p>Opens the specified document.</p> <p>Use the optional <code>as</code> parameter to specify the file format using the constants in <a href="#">OpenDocumentType</a>; or, you can specify a file format together with its open options using these objects:</p> <p><a href="#">CameraRAWOpenOptions</a>  <a href="#">DICOMOpenOptions</a>  <a href="#">EPSOpenOptions</a>  <a href="#">PDFOpenOptions</a>  <a href="#">PhotoCDOpenOptions</a>  <a href="#">RawFormatOpenOptions</a></p> <p>Use the optional parameter <code>asSmartObject</code> (default: <code>false</code>) to create a smart object around the opened document.</p> <p>See the <a href="#">Application sample scripts</a> for an example of using the <a href="#">File</a> object in the <code>open</code> method.</p>
<b>openDialog</b> ()		array of <a href="#">File</a>	<p>Invokes the Photoshop Open dialog box for the user to select files.</p> <p>Returns an array of <a href="#">File</a> objects for the files selected in the dialog.</p>
<b>purge</b> (target)	<a href="#">PurgeTarget</a>		<p>Purges one or more caches.</p>
<b>putCustomOptions</b> (key, customObject [, persistent])	string <a href="#">ActionDescriptor</a> boolean		<p>Saves a customized settings object in the Photoshop registry.</p> <p><code>key</code> is the unique identifier for your custom settings.</p> <p><code>customObject</code> is the object to save in the registry.</p> <p><code>persistent</code> indicates whether the object should persist once the script has finished.</p>
<b>refresh</b> ()			<p>Pauses the script while the application refreshes. Use to slow down execution and show the results to the user as the script runs. Use carefully; your script runs much more slowly when using this method.</p>
<b>refreshFonts</b> ()			<p>Force the font list to get updated.</p>
<b>runMenuItem</b> (menuID)	number		<p>Run a menu item given the menu ID.</p>

Method	Parameter type	Returns	What it does (Continued)
<b>showColorPicker</b> ( )		boolean	Returns false if dialog is cancelled, true otherwise.
<b>stringIDToTypeID</b> (stringID)	string	number	Converts from a string ID to a runtime ID.
<b>togglePalettes</b> ( )			Toggle palette visibility.
<b>TypeIDToCharID</b> (TypeID)	number	string	Converts from a runtime ID to a character ID.
<b>TypeIDToStringID</b> (TypeID)	number	string	Converts from a runtime ID to a string ID.

## Application sample scripts

### Application.jsx

This script invokes an alert box to display Properties important to an application such as version number, the path to the application, the amount of memory available, and the number of documents open.

When a user presses the OK button on the alert box, a second dialog opens, which asks users whether they would like the foreground and background colors set for the document presently open. If no document is open, the script opens a new document for the user.

The script (with no document open) produces a progression of three dialogs.

```
//Create a Welcome message
// Use the name and version properties of the application object to
// Append the application's name and version to the Welcome message
// use "\r" to insert a carriage return
// use the combination operator += to append info to the message
var message = "Welcome to " + app.name
message += " version " + app.version + "\r\r"

// find out where Adobe Photoshop CC 2014 is installed
// and add the path to the message
// add the optional parameter fsName to the path property
// to display the file system name in the most common format
message += "I'm installed in " + app.path.fsName + "\r\r"

// see how much memory Adobe Photoshop CC 2014 has to play with
message += "You have this much memory available for Adobe Photoshop CC 2014: " +
app.freeMemory + "\r\r"

// use the length property of the documents object to
// see how many documents are open
var documentsOpen = app.documents.length
message += "You currently have " + documentsOpen + " document(s) open.\r\r"

// display the message to the user
alert(message)

// answer will be true for a "Yes" answer and false for a "No" answer
var answer = confirm("Set the foreground and background to my favorite colors?")
```

```
// set the colors
if (answer) {
    // I don't have a favorite color. Why did I ask you may wonder?
    app.foregroundColor.rgb.red = Math.random() * 255
    app.foregroundColor.rgb.green = Math.random() * 255
    app.foregroundColor.rgb.blue = Math.random() * 255
    app.backgroundColor.rgb.red = Math.random() * 255
    app.backgroundColor.rgb.green = Math.random() * 255
    app.backgroundColor.rgb.blue = Math.random() * 255
}

// Open a document
if (app.documents.length == 0) {

    // use the application's path and the offset to the samples folder
    var sampleDocToOpen = File(app.path + "/Samples/Fish.psd")

    // compose a message with the name of the file
    message = "Would you like me to open a sample for you? ("
    message += sampleDocToOpen.fsName
    message += ")"

    // ask the user another question
    answer = confirm(message)

    // open the document accordingly
    if (answer) {
        open(sampleDocToOpen)
    }
}
```

### PDFPresentation.jsx

This script presents a progression of images as an Adobe PDF slide show.

```
// use all the files in the Samples folder
var inputFolder = new Folder(app.path + "/Samples/")

// see if we have something interesting
if (inputFolder != null) {

    // get all the files found in this folder that are Adobe Photoshop CC 2014
    (.psd format)
    var inputFiles = inputFolder.GetFiles("*.psd")

    // output to the desktop
    var outputFile = File("~/Desktop/JavaScriptPresentation.pdf")

    // there are defaults but I like to set the options myself
    var options = new PresentationOptions
    options.presentation = true
    options.view = true
    options.autoAdvance = true
    options.interval = 5
    options.loop = true
    options.transition = TransitionType.RANDOM

    // create the presentation
    makePDFPresentation(inputFiles, outputFile, options)
```

```
alert("Presentation file saved to: " + outputFile.fsName)
}
```

## ArtLayer

An object within a document that contains the visual elements of the image (equivalent to a layer in the Adobe Photoshop CC 2014 application).

Access an art layer in a document through the [Document.artLayers](#) collection. You can access a layer by name; for example:

```
var layerRef = app.activeDocument.artLayers.getByName("my layer");
layerRef.allLocked = true;
```

Access the art layers in a layer set through the [LayerSet.artLayers](#) collection in the parent set.

## Properties

Property	Value type	What it is
<b>allLocked</b>	boolean	Read-write. True to completely lock the contents and settings of this layer.
<b>blendMode</b>	<a href="#">BlendMode</a>	Read-write. The blending mode.
<b>bounds</b>	array of <a href="#">UnitValue</a>	Read-only. An array of coordinates that describes the bounding rectangle of the layer.
<b>boundsNoEffects</b>	array of <a href="#">UnitValue</a>	Read-only. An array of coordinates that describes the bounding rectangle of the layer not including effects.
<b>fillOpacity</b>	number [0.0..100]	Read-write. The interior opacity of the layer, a percentage value.
<b>filterMaskDensity</b>	double	Read-write. The density of the filter mask (between 0.0 and 250.0)
<b>filterMaskFeather</b>	double	Read-write. The feather of the filter mask (between 0.0 and 250.0)
<b>grouped</b>	boolean	Read-write. True if this layer is grouped with the layer beneath it.
<b>isBackgroundLayer</b>	boolean	Read-write. True if this is the background layer of the document. A document can have only one background layer. If there is no background layer, setting this to true causes this to become the background layer.
<b>kind</b>	<a href="#">LayerKind</a>	Read-write. Sets the type (such as 'text layer') for an empty layer.  Valid only when the layer is empty and when <code>isBackgroundLayer</code> is false. See <a href="#">isBackgroundLayer</a> .  You can use the <code>kind</code> property to make a background layer a normal layer; however, to make a layer a background layer, you must set <code>isBackgroundLayer</code> to true.

Property	Value type	What it is (Continued)
<b>layerMaskDensity</b>	double	Read-write. The density of the layer mask (between 0.0 and 100.0)
<b>layerMaskFeather</b>	double	Read-write. The feather of the layer mask (between 0.0 and 250.0)
<b>linkedLayers</b>	array of <a href="#">ArtLayer</a> or <a href="#">LayerSet</a>	Read-only. The layers linked to this layer. See <a href="#">ArtLayer.link</a> .
<b>name</b>	string	Read-write. The name.
<b>opacity</b>	number [0.0..100.0].	Read-write. The master opacity of the layer, a percentage value.
<b>parent</b>	<a href="#">Document</a>	Read-only. The object's container.
<b>pixelsLocked</b>	boolean	Read-write. True if the pixels in the layer's image cannot be edited using the paintbrush tool.
<b>positionLocked</b>	boolean	Read-write. True if the pixels in the layer's image cannot be moved within the layer.
<b>textItem</b>	<a href="#">TextItem</a>	Read-only. The text item that is associated with the layer. Valid only when <code>kind = LayerKind.TEXT</code> .
<b>transparentPixelsLocked</b>	boolean	Read-write. True if editing is confined to the opaque portions of the layer.
<b>typename</b>	string	Read-only. The class name of the referenced <code>artLayer</code> object.
<b>vectorMaskDensity</b>	double	Read-write. The density of the vector mask (between 0.0 and 250.0)
<b>vectorMaskFeather</b>	double	Read-write. The feather of the vector mask (between 0.0 and 250.0)
<b>visible</b>	boolean	Read-write. True if the layer is visible.
<b>xmpMetadata</b>	<a href="#">xmpMetadata</a>	Read-write. Metadata for the layer.

## Methods

Method	Parameter type	Returns	What it does
<b>adjustBrightnessContrast</b> (brightness, contrast)	number number		Adjusts the brightness in the range [-100..100] and contrast [-100..100].
<b>adjustColorBalance</b> ([shadows] [, midtones] [, highlights] [, preserveLuminosity])	array of number array of number array of number boolean		Adjusts the color balance of the layer's component channels. For shadows, midtones, and highlights, the array must include three values in the range [-100..100], which represent cyan or red, magenta or green, and yellow or blue, when the document mode is CMYK or RGB.  See <a href="#">Document.mode</a> .
<b>adjustCurves</b> (curveShape)	array of array of number		Adjusts the tonal range of the selected channel using up to fourteen points.  Each value in the <code>curveShape</code> array is a point pair, an array of an x and y integer value.
<b>adjustLevels</b> (inputRangeStart, inputRangeEnd, inputRangeGamma, outputRangeStart, outputRangeEnd)	number [0..253] number [(start + 2)..255] number [0.10..9.99] number [0..253] number [(start + 2)..255]		Adjusts the levels of the selected channels
<b>applyAddNoise</b> (amount, distribution, monochromatic)	number [0.1..400] <a href="#">NoiseDistribution</a> boolean		Applies the Add Noise filter amount is a percentage value.
<b>applyAverage</b> ( )			Applies the Average filter.
<b>applyBlur</b> ( )			Applies the Blur filter.
<b>applyBlurMore</b> ( )			Applies the Blur More filter.
<b>applyClouds</b> ( )			Applies the Clouds filter.
<b>applyCustomFilter</b> (characteristics, scale, offset)	array of number number number		Applies a custom filter.  The <code>characteristics</code> array has 25 members.  See Adobe Photoshop CC 2014 Help for specific instructions.

Method	Parameter type	Returns	What it does (Continued)
<b>applyDeInterlace</b> (eliminateFields, createFields)	<a href="#">EliminateFields</a> <a href="#">CreateFields</a>		Applies the De-Interlace filter.
<b>applyDespeckle</b> ( )			Applies the Despeckle filter.
<b>applyDifferenceClouds</b> ( )			Applies the Difference Clouds filter.
<b>applyDiffuseGlow</b> (graininess, glowAmount, clearAmount)	number [0..10] number [0..20] number [0..20]		Applies the Diffuse Glow filter.
<b>applyDisplace</b> (horizontalScale, verticalScale, displacement, undefinedareas, displacementMapFiles)	number [-999..999] number [-999..999] <a href="#">DisplacementMapType</a> <a href="#">UndefinedAreas</a> <a href="#">File</a>		Applies the Displace filter using the specified horizontal and vertical scale, mapping type, treatment of undistorted areas, and path to the distortion image map.
<b>applyDustAndScratches</b> (radius, threshold)	number [1..100] number [0..255]		Applies the Dust & Scratches filter.
<b>applyGaussianBlur</b> (radius)	number [0.1..250.0]		Applies the Gaussian Blur filter within the specified radius (in pixels)
<b>applyGlassEffect</b> (distortion, smoothness, scaling [, invert] [, texture] [, textureFile])	number [0..20] number [1..15] number [50..200] boolean <a href="#">TextureType</a> <a href="#">File</a>		Applies the Glass filter.  scaling is a percentage value.
<b>applyHighPass</b> (radius)	number [0.1..250.0]		Applies the High Pass filter within the specified radius.



Method	Parameter type	Returns	What it does (Continued)
<b>applyLensBlur</b> ([source] [, focalDistance] [, invertDepthMap] [, shape] [, radius] [, bladeCurvature] [, rotation] [, brightness] [, threshold] [, amount] [, distribution] [, monochromatic] )	<a href="#">DepthMapSource</a> number boolean <a href="#">Geometry</a> number number number number number <a href="#">NoiseDistribution</a> boolean		Applies the Lens Blur filter. source: The source for the depth map (default: DepthMapSource.NONE) focalDistance: The blur focal distance for the depth map (default: 0). invertDepthMask: True if the depth map is inverted (default: false). shape: The shape of the iris (default: Geometry.HEXAGON) radius: The radius of the iris (default: 15). bladeCurvature: The blade curvature of the iris (default: 0). rotation: The rotation of the iris (default: 0) brightness: The brightness for the specular highlights (default: 0). threshold: The threshold for the specular highlights (default: 0). amount: The amount of noise (default: 0) distribution: The distribution value for the noise (default: NoiseDistribution.UNIFORM). monochromatic: True if the noise is monochromatic (default: false).
<b>applyLensFlare</b> (brightness, flareCenter, lensType)	number array ( <a href="#">UnitValue</a> ) <a href="#">LensType</a>		Applies the Lens Flare filter with the specified brightness (0 - 300, as a percentage), the x and y coordinates (unit value) of the flare center, and the lens type.
<b>applyMaximum</b> (radius)	number [1..100]		Applies the Maximum filter within the specified radius (in pixels).
<b>applyMedianNoise</b> (radius)	number [1..100]		Applies the Median Noise filter within the specified radius (in pixels).

Method	Parameter type	Returns	What it does (Continued)
<b>applyMinimum</b> (radius)	number [1..100]		Applies the Minimum filter within the specified radius (in pixels) (1 - 100).
<b>applyMotionBlur</b> (angle, radius)	number [-360..360] number [1..999]		Applies the Motion Blur filter.
<b>applyNTSC</b> ( )			Applies the NTSC colors filter.
<b>applyOceanRipple</b> (size, magnitude)	number [1..15] number [0..20]		Applies the Ocean Ripple filter.
<b>applyOffset</b> (horizontal, vertical, undefinedAreas)	<a href="#">UnitValue</a> <a href="#">UnitValue</a> <a href="#">OffsetUndefinedAreas</a>		Moves the layer the specified amount horizontally and vertically (min/max amounts depend on layer size), leaving an undefined area at the layer's original location.
<b>applyPinch</b> (amount)	number [-100..100]		Applies the Pinch filter. amount is a percentage value.
<b>applyPolarCoordinates</b> (conversion)	<a href="#">PolarConversionType</a>		Applies the Polar Coordinates filter.
<b>applyRadialBlur</b> (amount, blurMethod, blurQuality)	number [1..100] <a href="#">RadialBlurMethod</a> <a href="#">RadialBlurQuality</a>		Applies the Radial Blur filter in the specified amount, using either a spin or zoom effect and the specified quality.
<b>applyRipple</b> (amount, size)	number [-999..999] <a href="#">RippleSize</a>		Applies the Ripple filter in the specified amount, throughout the image and in the specified size.
<b>applySharpen</b> ( )			Applies the Sharpen filter.
<b>applySharpenEdges</b> ( )			Applies the Sharpen Edges filter.
<b>applySharpenMore</b> ( )			Applies the Sharpen More filter.
<b>applyShear</b> (curve, undefinedAreas)	array of array of number <a href="#">UndefinedAreas</a>		Applies the Shear filter. The curve defines a curve with [2..255] points. Each value in the curve array is a point pair, an array of an x and y integer value.

Method	Parameter type	Returns	What it does (Continued)
<b>applySmartBlur</b> (radius, threshold, blurQuality, mode)	number [0.1..100.0] number [0.1..100.0] <a href="#">SmartBlurQuality</a> <a href="#">SmartBlurMode</a>		Applies the Smart Blur filter.
<b>applySpherize</b> (amount, mode)	number [-100..100] <a href="#">SpherizeMode</a>		Applies the Spherize filter. amount is a percentage value.
<b>applyStyle</b> (styleName)	string		Applies the specified style to the layer. You must use a style from the Styles list in the Layer Styles Palette.
<b>applyTextureFill</b> (textureFile)	<a href="#">File</a>		Applies the Texture Fill filter.
<b>applyTwirl</b> (angle)	number [-999..999]		Applies the Twirl filter.
<b>applyUnsharpMask</b> (amount, radius, threshold)	number [1..500] number [0.1..250.0] number [0..255]		Applies the Unsharp Mask filter. (amount is a percentage value.)
<b>applyWave</b> (generatorNumber, minimumWavelength, maximumWavelength, minimumAmplitude, maximumAmplitude, horizontalScale, verticalScale, waveType, undefinedAreas, randomSeed)	number [1..999] number [1..998] number [2..min+1] number [1..998] number [2..min+1] number [1..100] number [1..100] <a href="#">WaveType</a> <a href="#">UndefinedAreas</a> number		Applies the Wave filter. Scale factors are percentage values.
<b>applyZigZag</b> (amount, ridges, style)	number [-100..100] number [0..20] <a href="#">ZigZagType</a>		Applies the Zigzag filter.
<b>autoContrast</b> ( )			Adjusts the contrast of the selected channels automatically.
<b>autoLevels</b> ( )			Adjusts the levels of the selected channels using the auto levels option.
<b>clear</b> ( )			Cuts the layer without moving it to the clipboard.

Method	Parameter type	Returns	What it does (Continued)
<b>copy</b> ( [merge] )	boolean		Copies the layer to the clipboard. When the optional argument is set to <code>true</code> , a merged copy is performed (that is, all visible layers are copied to the clipboard).
<b>cut</b> ( )			Cuts the layer to the clipboard.
<b>desaturate</b> ( )			Converts a color image to a grayscale image in the current color mode by assigning equal values of each component color to each pixel.
<b>duplicate</b> ( [relativeObject] [, insertionLocation] )	<a href="#">ArtLayer</a> or <a href="#">LayerSet</a> <a href="#">ElementPlacement</a>	<a href="#">ArtLayer</a> or <a href="#">LayerSet</a>	Creates a duplicate of the object on the screen.
<b>equalize</b> ( )			Redistributes the brightness values of pixels in an image to more evenly represent the entire range of brightness levels within the image.
<b>invert</b> ( )			Inverts the colors in the layer by converting the brightness value of each pixel in the channels to the inverse value on the 256-step color-values scale.
<b>link</b> (with)	<a href="#">ArtLayer</a> or <a href="#">LayerSet</a>		Links the layer with the specified layer.
<b>merge</b> ( )		<a href="#">ArtLayer</a>	Merges the layer down, removing the layer from the document; returns a reference to the art layer that this layer is merged into.

Method	Parameter type	Returns	What it does (Continued)
<b>mixChannels</b> (outputChannels [, monochrome])	array of array of number boolean		<p>Modifies a targeted (output) color channel using a mix of the existing color channels in the image.</p> <p>The <code>outputChannels</code> parameter is an array of channel specifications. For each component channel, specify a list of adjustment values in the range [-200..200] followed by a 'constant' value [-200..200].)</p> <p>When <code>monochrome = true</code>, the maximum number of channel value specifications is 1.</p> <p>Valid only when <code>docRef.mode = DocumentMode.RGB</code> or <code>DocumentMode.CMYK</code>.</p> <p>RGB arrays must include four values. CMYK arrays must include five values.</p>
<b>move</b> (relativeObject, insertionLocation)	<a href="#">ArtLayer</a> or <a href="#">LayerSet</a> <a href="#">ElementPlacement</a>		<p>Moves the layer relative to the object specified in parameters.</p> <p>For art layers, only the constant values <code>ElementPlacement.PLACEBEFORE</code> and <code>ElementPlacement.PLACEAFTER</code> are valid.</p> <p>For layer sets, only the constant values <code>ElementPlacement.PLACEBEFORE</code> and <code>ElementPlacement.INSIDE</code> are valid.</p>
<b>photoFilter</b> ([fillColor] [, density] [, preserveLuminosity])	<a href="#">SolidColor</a> number [1..100] boolean		<p>Adjust the layer's color balance and temperature as if a color filter had been applied.</p> <p><code>density</code> is a percentage value.</p>
<b>posterize</b> (levels)	number [2..225]		<p>Specifies the number of tonal levels for each channel and then maps pixels to the closest matching level.</p>
<b>rasterize</b> (target)	<a href="#">RasterizeType</a>		<p>Converts the targeted contents in the layer into a flat, raster image.</p>
<b>remove</b> ()			<p>Deletes the object.</p>

Method	Parameter type	Returns	What it does (Continued)
<b>resize</b> ([horizontal] [, vertical] [, anchor])	number number <a href="#">AnchorPosition</a>		Resizes the layer to the specified dimensions (as a percentage of its current size) and places it in the specified position.
<b>rotate</b> (angle [, anchor])	number <a href="#">AnchorPosition</a>		Rotates rotates the layer around the specified anchor point (default: MIDDLECENTER).
<b>selectiveColor</b> (selectionMethod [, reds] [, yellows] [, greens] [, cyans] [, blues] [, magentas] [, whites] [, neutrals] [, blacks])	<a href="#">AdjustmentReference</a> array of number array of number array of number array of number array of number array of number array of number array of number		Modifies the amount of a process color in a specified primary color without affecting the other primary colors.  Each color array must have four values.
<b>shadowHighlight</b> ([shadowAmount] [, shadowWidth] [, shadowRadius] [, highlightAmount] [, highlightWidth] [, highlightRadius] [, colorCorrection] [, midtoneContrast] [, blackClip] [, whiteClip])	number [0..100] number [0..100] number [0..2500] number [0..100] number [0..100] number [0..2500] number [-100..100] number [-100..100] number [0.000..50.000] number [0.000..50.000]		Adjusts the range of tones in the image's shadows and highlights.  Amounts and widths are percentage values. Radius values are in pixels.
<b>threshold</b> (level)	number [1..255]		Converts grayscale or color images to high-contrast, B/W images by converting pixels lighter than the specified threshold to white and pixels darker than the threshold to black.
<b>translate</b> ([deltaX] [, deltaY])	<a href="#">UnitValue</a> <a href="#">UnitValue</a>		Moves the layer the specified amount (in the given unit) relative to its current position.
<b>unlink</b> ( )			Unlinks the layer.

## ArtLayer sample Script

The following script opens all the files in the samples folder, creating one multi-layered document. Each layer is pasted into one of four quadrants and given 50% transparency. Finally the layers are sorted by name.

### ArtLayer.jsx

```
// Save the current preferences
var startRulerUnits = app.preferences.rulerUnits
var startTypeUnits = app.preferences.typeUnits
var startDisplayDialogs = app.displayDialogs

// Set Adobe Photoshop CC 2014 to use pixels and display no dialogs
app.preferences.rulerUnits = Units.PIXELS
app.preferences.typeUnits = TypeUnits.PIXELS
app.displayDialogs = DialogModes.NO

//Close all the open documents
while (app.documents.length) {
    app.activeDocument.close()
}

// Create a new document to merge all the samples into
var mergedDoc = app.documents.add(1000, 1000, 72, "Merged Samples",
NewDocumentMode.RGB, DocumentFill.TRANSPARENT, 1)

// Use the path to the application and append the samples folder
var samplesFolder = Folder(app.path + "/Samples/")

//Get all the files in the folder
var fileList = samplesFolder.GetFiles()

// open each file
for (var i = 0; i < fileList.length; i++) {
    // The fileList is folders and files so open only files
    if (fileList[i] instanceof File) {
        open(fileList[i])

        // use the document name for the layer name in the merged document
        var docName = app.activeDocument.name

        // flatten the document so we get everything and then copy
        app.activeDocument.flatten()
        app.activeDocument.selection.selectAll()
        app.activeDocument.selection.copy()

        // don't save anything we did
        app.activeDocument.close(SaveOptions.DONOTSAVECHANGES)

        // make a random selection on the document to paste into
        // by dividing the document up in 4 quadrants and pasting
        // into one of them by selecting that area
        var topLeftH = Math.floor(Math.random() * 2)
        var topLeftV = Math.floor(Math.random() * 2)
        var docH = app.activeDocument.width.value / 2
        var docV = app.activeDocument.height.value / 2
        var selRegion = Array(Array(topLeftH * docH, topLeftV * docV),
            Array(topLeftH * docH + docH, topLeftV * docV),
            Array(topLeftH * docH, topLeftV * docV + docV),
            Array(topLeftH * docH + docH, topLeftV * docV + docV))
        app.activeDocument.selection.select(selRegion)
        app.activeDocument.paste()

        // change the layer name and opacity
        app.activeDocument.activeLayer.name = docName
        app.activeDocument.activeLayer.fillOpacity = 50
    }
}
```

```
    }  
  }  
  
  // sort the layers by name  
  for (var x = 0; x < app.activeDocument.layers.length; x++) {  
    for (var y = 0; y < app.activeDocument.layers.length - 1 - x; y++) {  
      // Compare in a non-case sensitive way  
      var doc1 = app.activeDocument.layers[y].name  
      var doc2 = app.activeDocument.layers[y + 1].name  
      if (doc1.toUpperCase() > doc2.toUpperCase()) {  
        app.activeDocument.layers[y].move(app.activeDocument.layers[y+1],  
          ElementPlacement.PLACEAFTER)  
      }  
    }  
  }  
}  
  
// Reset the application preferences  
app.preferences.rulerUnits = startRulerUnits  
app.preferences.typeUnits = startTypeUnits  
app.displayDialogs = startDisplayDialogs
```



## ArtLayers

The collection of [ArtLayer](#) objects in a document or layer set.

Access through the [Document.artLayers](#) or [LayerSet.artLayers](#) collection. For example:

```
var layerRef = docRef.artLayers.add()
```

### Properties

Property	Value type	What it is
<b>length</b>	number	Read-only. The number of elements in the <code>artLayers</code> collection.
<b>parent</b>	<a href="#">Document</a>	Read-only. The object's container.
<b>typename</b>	string	Read-only. The class name of the referenced <code>artLayers</code> object.

### Methods

Method	Parameter type	Returns	What it does
<b>add</b> ( )		<a href="#">ArtLayer</a>	Creates a new art layer in the document and adds the new object to this collection.
<b>getByName</b> (name)	string	<a href="#">ArtLayer</a>	Get the first element in the <code>artLayers</code> collection with the provided name.
<b>removeAll</b> ( )			Removes all elements from the <code>artLayers</code> collection.

## BatchOptions

Options for running a batch operation using the [Application.batch\(\)](#) method.

JavaScript only supports folders as sources for batch commands. Specify the batch source folder as the `inputFiles` parameter of the [Application.batch\(\)](#) method.

### Properties

Property	Value type	What it is
<code>destination</code>	<a href="#">BatchDestinationType</a>	Read-write. The type of destination for the processed files (default: <code>BatchDestinationType.NODESTINATION</code> ).
<code>destinationFolder</code>	<a href="#">Folder</a>	Read-write. The folder location for the processed files.  Valid only when <a href="#">destination</a> = <code>BatchDestinationType.FOLDER</code> .
<code>errorFile</code>	<a href="#">File</a>	Read-write. The file in which to log errors encountered.  To display errors on the screen (and stop batch processing when errors occur) leave blank.
<code>fileNaming</code>	array of <a href="#">FileNamingType</a>	Read-write. A list of file naming options (maximum: 6).  Valid only when <a href="#">destination</a> = <code>BatchDestinationType.FOLDER</code> .
<code>macintoshCompatible</code>	boolean	Read-write. True to make the final file names Macintosh compatible (default: <code>true</code> ).  Valid only when <a href="#">destination</a> = <code>BatchDestinationType.FOLDER</code> .
<code>overrideOpen</code>	boolean	Read-write. True to override action open commands (default: <code>false</code> ).
<code>overrideSave</code>	boolean	Read-write. True to override save as action steps with the specified destination (default: <code>false</code> ).  Valid only when <a href="#">destination</a> = <code>BatchDestinationType.FOLDER</code> OR <code>SAVEANDCLOSE</code> .
<code>startingSerial</code>	number	Read-write. The starting serial number to use in naming files (default: 1).  Valid only when <a href="#">destination</a> = <code>BatchDestinationType.FOLDER</code> .
<code>suppressOpen</code>	boolean	Read-write. True to suppress the file open options dialogs (default: <code>false</code> ).

Property	Value type	What it is (Continued)
<b>suppressProfile</b>	boolean	Read-write. True to suppress the color profile warnings (default: <code>false</code> ).
<b>typename</b>	string	Read-only. The class name of the referenced <code>batchOptions</code> object.
<b>unixCompatible</b>	boolean	Read-write. True to make the final file name Unix compatible (default: <code>true</code> ). Valid only when <a href="#">destination</a> = <code>BatchDestinationType.FOLDER</code> .
<b>windowsCompatible</b>	boolean	Read-write. True to make the final file names Windows compatible (default: <code>true</code> ). Valid only when <a href="#">destination</a> = <code>BatchDestinationType.FOLDER</code> .

## BitmapConversionOptions

Options for converting an image to bitmap mode, using [Document.changeMode\(\)](#) with [ChangeMode.Bitmap](#).

Convert color images to grayscale before converting the image to bitmap mode. See the [ArtLayer.desaturate\(\)](#) method.

### Properties

Property	Value type	What it is
<b>angle</b>	number [-180..180]	Read-write. The angle (in degrees) at which to orient individual dots. See <a href="#">shape</a> .  Valid only when <a href="#">method</a> = <code>BitmapConversionType.HALFTONESCREEN</code> .
<b>frequency</b>	number [1.0..999.99]	Read-write. The number of printer dots (per inch) to use.  Valid only when <a href="#">method</a> = <code>BitmapConversionType.HALFTONESCREEN</code> .
<b>method</b>	<a href="#">BitmapConversionType</a>	Read-write. The conversion method to use (default: <code>BitmapConversionType.DIFFUSIONDITHER</code> ).
<b>patternName</b>	string	Read-write. The name of the pattern to use.  For information about pre-installed valid patterns, see Adobe Photoshop CC 2014 Help on the bitmap conversion command, or view the options available in the Custom Color drop down box after choosing the bitmap conversion command.  Valid only when <a href="#">method</a> = <code>BitmapConversionType.CUSTOMPATTERN</code> .
<b>resolution</b>	number	Read-write. The output resolution in pixels per inch (default: 72.0).
<b>shape</b>	<a href="#">BitmapHalfToneType</a>	Read-write. The dot shape to use.  Valid only when <a href="#">method</a> = <code>BitmapConversionType.HALFTONESCREEN</code> .
<b>typename</b>	string	Read-only. The class name of the referenced <code>bitmapConversionOptions</code> object.

## BMPSaveOptions

Options for saving a document in BMP format using the [Document.saveAs\(\)](#) method.

### Properties

Property	Value type	What it is
<code>alphaChannels</code>	boolean	Read-write. True to save the alpha channels.
<code>depth</code>	<a href="#">BMPDepthType</a>	Read-write. The number of bits per channel.
<code>flipRowOrder</code>	boolean	Read-write. True to write the image from top to bottom (default: <code>false</code> ). Available only when <a href="#">osType</a> = <code>OperatingSystem.WINDOWS</code> .
<code>osType</code>	<a href="#">OperatingSystem</a>	Read-write. The target OS. (default: <code>OperatingSystem.WINDOWS</code> ).
<code>rleCompression</code>	boolean	Read-write. True to use RLE compression. Available only when <a href="#">osType</a> = <code>OperatingSystem.WINDOWS</code> .
<code>typename</code>	string	Read-only. The class name of the referenced <code>BMPSaveOptions</code> object.

## CameraRAWOpenOptions

Options for opening a document in Camera RAW format using the [Application.open\(\)](#) method.

### Properties

Property	Value type	What it is
<b>bitsPerChannel</b>	<a href="#">BitsPerChannelType</a>	Read-write. The number of bits per channel.
<b>blueHue</b>	number [-100..100]	Read-write. The blue hue of the shot.
<b>blueSaturation</b>	number [-100..100]	Read-write. The blue saturation of the shot.
<b>brightness</b>	number [0..150]	Read-write. The brightness of the shot.
<b>chromaticAberrationBY</b>	number [-100..100]	Read-write. The chromatic aberration B/Y of the shot.
<b>chromaticAberrationRC</b>	number [-100..100]	Read-write. The chromatic aberration R/C of the shot.
<b>colorNoiseReduction</b>	number [0..100]	Read-write. The color noise reduction of the shot.
<b>colorSpace</b>	<a href="#">ColorSpaceType</a>	Read-write. The colorspace for the image.
<b>contrast</b>	number [-50..100]	Read-write. The contrast of the shot.
<b>exposure</b>	number [-4.0..4.0]	Read-write. The exposure of the shot.
<b>greenHue</b>	number [-100..100]	Read-write. The green hue of the shot.
<b>greenSaturation</b>	number [-100..100]	Read-write. The green saturation of the shot.
<b>luminanceSmoothing</b>	number [0..100]	Read-write. The luminance smoothing of the shot.
<b>redHue</b>	number [-100..100]	Read-write. The red hue of the shot.
<b>redSaturation</b>	number [-100..100]	Read-write. The red saturation of the shot.
<b>resolution</b>	number [1..999]	Read-write. The resolution of the document in pixels per inch.
<b>saturation</b>	number [-100..100]	Read-write. The saturation of the shot.
<b>settings</b>	<a href="#">CameraRAWSettingsType</a>	Read-write. The global settings for all Camera RAW options. Default: <code>CameraRAWSettingsType.CAMERA</code> .
<b>shadows</b>	number [0..100]	Read-write. The shadows of the shot.
<b>shadowTint</b>	number [-100..100]	Read-write. The shadow tint of the shot.
<b>sharpness</b>	number [0..100]	Read-write. The sharpness of the shot.
<b>size</b>	<a href="#">CameraRAWSize</a>	Read-write. The size of the new document.
<b>temperature</b>	number [2000..50000]	Read-write. The temperature of the shot.

Property	Value type	What it is (Continued)
<b>tint</b>	number [-150..150]	Read-write. The tint of the shot.
<b>typename</b>	string	Read-only. The class name of the referenced <code>cameraRAWOpenOptions</code> object.
<b>vignettingAmount</b>	number [-100..100]	Read-write. The vignetting amount of the shot.
<b>vignettingMidpoint</b>	number [-100..100]	Read-write. The vignetting mid point of the shot.
<b>whiteBalance</b>	<a href="#">WhiteBalanceType</a>	Read-write. The white balance options for the image. These are lighting conditions that affect color balance.

# Channel

Information about a color element in the image.

Access through the [Document.channels](#) collection. You can access an individual channel object in this list by index or by name. For example, this accesses a channel object in the active document by name and assigns an `opacity` value:

```
var channelRef = app.activeDocument.channels.getByNamed("my channel");
channelRef.opacity = 22;
```

A channel is analogous to a plate in the printing process that applies a single color. The document's color mode determines the number of default channels; for example, an RGB document has three channels, red, green, and blue. A color can also have an alpha channel, which stores selections as masks, or a spot channel, which stores spot colors.

## Properties

Property	Value type	What it is
<code>color</code>	<a href="#">SolidColor</a>	Read-write. The color of the channel. Not valid when <code>kind</code> = <code>ChannelType.COMPONENT</code> .
<code>histogram</code>	array of number	Read-only. A histogram of the color of the channel. The array contains 256 members. Not valid when <code>kind</code> = <code>ChannelType.COMPONENT</code> . For component channel histogram values, use the <a href="#">histogram</a> property of the <a href="#">Document</a> object instead.
<code>kind</code>	<a href="#">ChannelType</a>	Read-write. The type of the channel.
<code>name</code>	string	Read-write. The name of the channel.
<code>opacity</code>	number [0..100]	Read-write. The opacity to use for alpha channels or the solidity to use for spot channels. Valid only when <code>kind</code> = <code>ChannelType.MASKEDAREA</code> or <code>SELECTEDAREA</code> .
<code>parent</code>	<a href="#">Document</a>	Read-only. The containing document.
<code>typename</code>	string	Read-only. The class name of the referenced <code>channel</code> object.
<code>visible</code>	boolean	Read-write. True if the channel is visible.

## Methods

Method	Parameter type	Returns	What it does
<code>duplicate</code> ( [targetDocument] )	<a href="#">Document</a>	<a href="#">Channel</a>	Duplicates the channel.



<b>Method</b>	<b>Parameter type</b>	<b>Returns</b>	<b>What it does</b>
<b>merge</b> ( )			Merges a spot channel into the component channels.
<b>remove</b> ( )			Deletes the channel.

## Channels

The collection of [Channel](#) objects in a document.

Access through the [Document.channels](#) collection property. For example:

```
var channelRef = app.activeDocument.channels.add()
```

## Properties

Property	Value type	What it is
<code>length</code>	number	Read-only. The number of elements in the <code>channels</code> collection.
<code>parent</code>	<a href="#">Document</a>	Read-only. The containing document.
<code>typename</code>	string	Read-only. The class name of the referenced <code>channels</code> object.

## Methods

Method	Parameter type	Returns	What it does
<code>add</code> ( )		<a href="#">Channel</a>	Creates a new channel object and adds it to this collection.
<code>getByName</code> (name)	string	<a href="#">Channel</a>	Get the first element in the <code>channels</code> collection with the provided name.
<code>removeAll</code> ( )			Removes all alpha channel objects from the <code>channels</code> collection.

## Channels sample script

The following script opens a file if one is not already open, and then writes a histogram report (`histogram.log`) for the channels in the active document.

**Note:** This script contains a switch construction that uses a `break` statement. The `break` statement requires an ending semicolon (;), as in the following sample:

```
break;
```

### Histogram.jsx

```
// Function to activate all the channels according to the documents mode
// Takes a document reference for input
function TurnOnDocumentHistogramChannels(inDocument) {

    // see how many channels we need to activate
    var visibleChannelCount = 0

    // based on the mode of the document
    switch (inDocument.mode) {

        case DocumentMode.BITMAP:
```

```
        case DocumentMode.GRAYSCALE:
        case DocumentMode.INDEXEDCOLOR:
            visibleChannelCount = 1
            break;

        case DocumentMode.DUOTONE:
            visibleChannelCount = 2
            break;

        case DocumentMode.RGB:
        case DocumentMode.LAB:
            visibleChannelCount = 3
            break;

        case DocumentMode.CMYK:
            visibleChannelCount = 4
            break;

        case DocumentMode.MULTICHANNEL:
        default:
            visibleChannelCount = inDocument.channels.length + 1
            break;
    }

    // now get the channels to activate into a local array
    var aChannelArray = new Array()

    // index for the active channels array
    var aChannelIndex = 0

    for(var channelIndex = 0; channelIndex < inDocument.channels.length;
        channelIndex++) {
        if (channelIndex < visibleChannelCount) {
            aChannelArray[aChannelIndex++] = inDocument.channels[channelIndex]
        }
    }

    // now activate them
    inDocument.activeChannels = aChannelArray
}

// Save the current preferences
var startRulerUnits = app.preferences.rulerUnits
var startTypeUnits = app.preferences.typeUnits
var startDisplayDialogs = app.displayDialogs

// Set Adobe Photoshop CC 2014 to use pixels and display no dialogs
app.preferences.rulerUnits = Units.PIXELS
app.preferences.typeUnits = TypeUnits.PIXELS
app.displayDialogs = DialogModes.NO

// if there are no documents open then try to open a sample file
if (app.documents.length == 0) {
    open(File(app.path + "/Samples/Fish.psd"))
}

// get a reference to the working document
var docRef = app.activeDocument
```

```
// create the output file
// first figure out which kind of line feeds we need
if ($.os.search(/windows/i) != -1) {
    fileLineFeed = "Windows"
} else {
    fileLineFeed = "Macintosh"
}

// create the output file accordingly
fileOut = new File("~/Desktop/Histogram.log")
fileOut.lineFeed = fileLineFeed
fileOut.open("w", "TEXT", "????")

// write out a header
fileOut.write("Histogram report for " + docRef.name)

// find out how many pixels I have
var totalCount = docRef.width.value * docRef.height.value

// more info to the out file
fileOut.write(" with a total pixel count of " + totalCount + "\n")

// channel indexer
var channelIndex = 0

// remember which channels are currently active
var myActiveChannels = app.activeDocument.activeChannels

// document histogram only works in these modes
if (docRef.mode == DocumentMode.RGB ||
    docRef.mode == DocumentMode.INDEXEDCOLOR ||
    docRef.mode == DocumentMode.CMYK) {

    // activate the main channels so we can get the documents histogram
    TurnOnDocumentHistogramChannels(docRef)

    // Output the documents histogram
    OutputHistogram(docRef.histogram, "Luminosity", fileOut)
}

// local reference to work from
var myChannels = docRef.channels

// loop through each channel and output the histogram
for (var channelIndex = 0; channelIndex < myChannels.length; channelIndex++) {

    // the channel has to be visible to get a histogram
    myChannels[channelIndex].visible= true

    // turn off all the other channels
    for (var secondaryIndex = 0; secondaryIndex < myChannels.length;
        secondaryIndex++) {
        if (channelIndex != secondaryIndex) {
            myChannels[secondaryIndex].visible= false
        }
    }

    // Use the function to dump the histogram
    OutputHistogram(myChannels[channelIndex].histogram,
        myChannels[channelIndex].name, fileOut)
```

```
}

// close down the output file
fileOut.close()
alert("Histogram file saved to: " + fileOut.fsName)

// reset the active channels
docRef.activeChannels = myActiveChannels

// Reset the application preferences
app.preferences.rulerUnits = startRulerUnits
app.preferences.typeUnits = startTypeUnits
app.displayDialogs = startDisplayDialogs

// Utility function that takes a histogram and name
// and dumps to the output file
function OutputHistogram(inHistogram, inHistogramName, inOutFile) {

    // find ouch which count has the largest number
    // I scale everything to this number for the output
    var largestCount = 0

    // a simple indexer I can reuse
    var histogramIndex = 0

    // see how many samples we have total
    var histogramCount = 0

    // search through all and find the largest single item
    for (histogramIndex = 0; histogramIndex < inHistogram.length;
        histogramIndex++) {
        histogramCount += inHistogram[histogramIndex]
        if (inHistogram[histogramIndex] > largestCount)
            largestCount = inHistogram[histogramIndex]
    }

    // These should match
    if (histogramCount != totalCount) {
        alert("Something bad is happening!")
    }

    // see how much each "X" is going to count as
    var pixelsPerX = largestCount / 100

    // output this data to the file
    inOutFile.write("One X = " + pixelsPerX + " pixels.\n")

    // output the name of this histogram
    inOutFile.write(inHistogramName + "\n")

    // loop through all the items and output in the following format
    // 001
    // 002
    for (histogramIndex = 0; histogramIndex < inHistogram.length;
        histogramIndex++) {

        // I need an extra "0" for this line item to keep everything in line
        if (histogramIndex < 10)
            inOutFile.write("0")
    }
}
```

```
// I need an extra "0" for this line item to keep everything in line
if (histogramIndex < 100)
    inOutFile.write("0")

// output the index to file
inOutFile.write(histogramIndex)

// some spacing to make it look nice
inOutFile.write(" ")

// figure out how many X's I need
var outputX = inHistogram[histogramIndex] / largestCount * 100

// output the X's
for (var a = 0; a < outputX; a++)
    inOutFile.write("X")

    inOutFile.write("\n")
}

inOutFile.write("\n")
}
```

## CMYKColor

Defines a CMYK color, used in the [SolidColor](#) object.

See also [GrayColor](#), [HSBColor](#), [LabColor](#), [NoColor](#), [RGBColor](#)

### Properties

Property	Value type	What it is
<b>black</b>	number [0.0..100.00]	Read-write. The black color value (as percent).
<b>cyan</b>	number [0.0..100.00]	Read-write. The cyan color value (as percent).
<b>magenta</b>	number [0.0..100.00]	Read-write. The magenta color value (as percent).
<b>typename</b>	string	Read-only. The class name of the referenced <code>CMYKColor</code> object.
<b>yellow</b>	number [0.0..100.00]	Read-write. The yellow color value (as percent).

## ColorSampler

A color sampler for a document. Access through the [Document.colorSamplers](#) collection. For example:

```
var colorSamplerRef = app.activeDocument.colorSamplers[0];
var currentColor = colorSamplerRef.color;
```

**Note:** For additional information about color samplers, see Adobe Photoshop CC 2014 help on the Color Sampler Tool.

### Properties

Property	Value type	What it is
<code>color</code>	<a href="#">SolidColor</a>	Read-only. The color of the color sampler.
<code>position</code>	array of <a href="#">UnitValue</a>	Read-only. The position of the color sampler in the document. The array (x,y) represents the horizontal and vertical location of the count item.
<code>parent</code>	<a href="#">Document</a>	Read-only. The containing document.
<code>typename</code>	string	Read-only. The class name of the referenced <code>ColorSampler</code> object.

### Methods

Method	Parameter type	Returns	What it does
<code>move</code> (position)	array of <a href="#">UnitValue</a>		Moves the color sampler to a new location in the document.  The <code>position</code> parameter (x,y) represents the new horizontal and vertical locations of the moved color sampler.
<code>remove</code> ( )			Deletes the <code>ColorSampler</code> object.



## ColorSamplers

The collection of [ColorSampler](#) objects in a document. Access through the [Document.colorSamplers](#) collection property. For example:

```
app.activeDocument.colorSamplers.removeAll()
```

### Properties

Property	Value type	What it is
<code>length</code>	number	Read-only. The number of elements in the <code>ColorSamplers</code> collection.
<code>parent</code>	<a href="#">Document</a>	Read-only. The containing document.
<code>typename</code>	string	Read-only. The class name of the referenced <code>ColorSamplers</code> object.

### Methods

Method	Parameter type	Returns	What it does
<code>add</code> ( <code>position</code> )	array of <a href="#">UnitValue</a>	<a href="#">ColorSampler</a>	Creates a new color sampler object and adds it to this collection.  The <code>position</code> parameter (x,y) represents the new horizontal and vertical locations of the moved color sampler.
<code>removeAll</code> ( )			Removes all <code>ColorSampler</code> objects from the <code>ColorSamplers</code> collection.

## ContactSheetOptions

Options for creating a contact sheet with the [Application.makeContactSheet\(\)](#) method.

### Properties

Property	Value type	What it is
<b>acrossFirst</b>	boolean	Read-write. True to place the images horizontally (left to right, then top to bottom) first (default: <code>true</code> ).
<b>bestFit</b>	boolean	Read-write. True to rotate images for the best fit (default: <code>false</code> ).
<b>caption</b>	boolean	Read-write. True to use the filename as a caption for the image (default: <code>true</code> ).
<b>columnCount</b>	number [1..100]	Read-write. The number of columns to include (default: 5).
<b>flatten</b>	boolean	Read-write. True to flatten all layers in the final document (default: <code>true</code> ).
<b>font</b>	<a href="#">GalleryFontType</a>	Read-write. The font used for the caption (default: <code>GalleryFontType.ARIAL</code> ).
<b>fontSize</b>	number	Read-write. The font size to use for the caption (default: 12).
<b>height</b>	number [0..29000]	Read-write. The height (in pixels) of the resulting document (default: 720).
<b>horizontal</b>	number	Read-write. The horizontal spacing (in pixels) between images (default: 1).
<b>mode</b>	<a href="#">NewDocumentMode</a>	Read-write. The document color mode (default: <code>NewDocumentMode.RGB</code> ).
<b>resolution</b>	number [35..1200]	Read-write. The resolution of the document in pixels per inch (default: 72.0).
<b>rowCount</b>	number [1..100]	Read-write. The number of rows to use (default: 6).
<b>typename</b>	string	Read-only. The class name of the referenced <code>contactSheetOptions</code> object.
<b>useAutoSpacing</b>	boolean	Read-write. True to auto space the images (default: <code>true</code> ).
<b>vertical</b>	number [0..29000]	Read-write. The vertical spacing (in pixels) between images (default: 1). Valid only when <a href="#">useAutoSpacing</a> = <code>false</code> .
<b>width</b>	number [100..29000]	Read-write. The width (in pixels) of the resulting document (default: 576).

## CountItem

A counted item in a document. Access through the [Document.countItems](#) collection. See the [Document.autoCount\(\)](#) method.

**Note:** This feature is available in the Extended Version only.

For additional information about count items, see Adobe Photoshop CC 2014 help on the Count Tool.

### Properties

Property	Value type	What it is
<code>position</code>	array of <a href="#">UnitValue</a>	Read-only. The position of the count item in the document.
<code>parent</code>	<a href="#">Document</a>	Read-only. The containing document.
<code>typename</code>	string	Read-only. The class name of the referenced <code>CountItem</code> object.

### Methods

Method	Parameter type	Returns	What it does
<code>remove</code> <code>()</code>			Deletes the <code>CountItem</code> object.

## CountItems

The collection of [CountItem](#) objects in the document.

Access through the [Document.countItems](#) collection property. For example:

```
app.activeDocument.countItems.removeAll()
```

**Note:** This feature is available in the Extended Version only.

## Properties

Property	Value type	What it is
<b>length</b>	number	Read-only. The number of elements in the <code>CountItems</code> collection.
<b>parent</b>	<a href="#">Document</a>	Read-only. The containing document.
<b>typename</b>	string	Read-only. The class name of the referenced <code>CountItems</code> object.

## Methods

Method	Parameter type	Returns	What it does
<b>add</b> (position)	array of <a href="#">UnitValue</a>	<a href="#">CountItem</a>	Creates a new count item object and adds it to this collection.  Parameter <code>position (x,y)</code> represents the horizontal and vertical positions, respectively, of the <code>CountItem</code> object.
<b>getByName</b> (name)	string	<a href="#">CountItem</a>	Get the first element in the <code>CountItems</code> collection with the provided name.
<b>removeAll</b> ( )			Removes all <code>CountItem</code> objects from the <code>CountItems</code> collection.

## DCS1\_SaveOptions

Options for saving a CMYK document in DCS1 format using the [Document.saveAs\(\)](#) method.

### Properties

Property	Value type	What it is
<code>dcs</code>	<a href="#">DCSType</a>	Read-write. (default: <code>DCSType.COLORCOMPOSITE</code> ).
<code>embedColorProfile</code>	boolean	Read-write. True to embed the color profile in the document
<code>encoding</code>	<a href="#">SaveEncoding</a>	Read-write. The type of encoding to use for document (default: <code>SaveEncoding.BINARY</code> ).
<code>halftoneScreen</code>	boolean	Read-write. True to include halftone screen (default: <code>false</code> ).
<code>interpolation</code>	boolean	Read-write. True to use image interpolation (default: <code>false</code> )
<code>preview</code>	<a href="#">Preview</a>	Read-write. The type of preview (default: <code>Preview.MACOSEIGHTBIT</code> ).
<code>transferFunction</code>	boolean	Read-write. True to include the Transfer functions to compensate for dot gain between the image and film (default: <code>false</code> ).
<code>typename</code>	string	Read-only. The class name of the referenced <code>DCS1_SaveOptions</code> object.
<code>vectorData</code>	boolean	Read-write. True to include vector data. Valid only if the document includes vector data (unrasterized text).

## DCS2\_SaveOptions

Options for saving a CMYK document in DCS2 format using the [Document.saveAs\(\)](#) method.

### Properties

Property	Value type	What it is
<b>dcs</b>	<a href="#">DCSType</a>	Read-write. The type of composite file to create (default: <code>DCSType.NO_COMPOSITE</code> ).
<b>embedColorProfile</b>	boolean	Read-write. True to embed the color profile in the document.
<b>encoding</b>	<a href="#">SaveEncoding</a>	Read-write. The type of encoding to use (default: <code>SaveEncoding.BINARY</code> ).
<b>halftoneScreen</b>	boolean	Read-write. True to include the halftone screen (default: <code>false</code> ).
<b>interpolation</b>	boolean	Read-write. True to use image interpolation (default: <code>false</code> ).
<b>multiFileDCS</b>	boolean	Read-write. True to save color channels as multiple files or a single file (default: <code>false</code> ).
<b>preview</b>	<a href="#">Preview</a>	Read-write. The preview type (default: <code>Preview.MACOSEIGHTBIT</code> ).
<b>spotColors</b>	boolean	Read-write. True to save spot colors.
<b>transferFunction</b>	boolean	Read-write. True to include the Transfer functions to compensate for dot gain between the image and film (default: <code>false</code> ).
<b>typename</b>	string	Read-only. The class name of the referenced <code>DCS2_SaveOptions</code> object.
<b>vectorData</b>	boolean	Read-write. True to include vector data. Valid only if the document includes vector data (unrasterized text).

## DICOMOpenOptions

Options for opening a document in DICOM format using the [Application.open\(\)](#) method.

**Note:** This feature is available in the Extended Version only.

### Properties

Property	Value type	What it is
<code>anonymize</code>	boolean	Read-write. True to make the patient information anonymous.
<code>columns</code>	number	Read-write. Number of columns in n-up configuration.
<code>reverse</code>	boolean	Read-write. True to reverse (invert) the image.
<code>rows</code>	number	Read-write. The number of rows in n-up configuration.
<code>showOverlays</code>	boolean	Read-write. True to show overlays.
<code>typename</code>	string	Read-only. The class name of the referenced <code>DICOMOpenOptions</code> object.
<code>windowLevel</code>	number	Read-write. The contrast of the image in Hounsfield units.
<code>windowWidth</code>	number	Read-write. The brightness of the image in Hounsfield units.

## Document

The active containment object for layers and all other objects in the script; the basic canvas for the file.

- Access the object for the currently active document through [Application.activeDocument](#).
- You can access other documents, or iterate through all open documents using the list in the [Application.documents](#) collection. You can access individual documents in the list by index, or use [Documents.getByIndex\(\)](#) to retrieve them by name.
- Create documents programmatically using the [Documents.add\(\)](#) method.

See [Document sample script](#) and the [Documents](#) collection object for examples.

**Note:** In Adobe Photoshop CC 2014, a document can also be referred to as an image or a canvas.

- The term *image* refers to the entire document and its contents. You can trim or crop an image. You resize an image using the [resizeImage\(\)](#) method.
- The term *canvas* refers to the space in which the document sits on the screen. You can rotate or flip the canvas. You resize the canvas using the [resizeCanvas\(\)](#) method.

## Properties

Property	Value type	What it is
<code>activeChannels</code>	array of <a href="#">Channel</a>	Read-write. The selected channels.
<code>activeHistoryBrushSource</code>	<a href="#">Guide</a>	Read-write. The history state to use with the history brush.
<code>activeHistoryState</code>	<a href="#">Guide</a>	Read-write. The selected <code>HistoryState</code> object.
<code>activeLayer</code>	<a href="#">ArtLayer</a> or <a href="#">LayerSet</a>	Read-write. The selected layer.
<code>artLayers</code>	<a href="#">ArtLayers</a>	Read-only. The art layers collection.
<code>backgroundLayer</code>	<a href="#">ArtLayer</a>	Read-only. The background layer of the document.
<code>bitsPerChannel</code>	<a href="#">BitsPerChannelType</a>	Read-write. The number of bits per channel.
<code>channels</code>	<a href="#">Channels</a>	Read-only. The channels collection.
<code>colorProfileName</code>	string	Read-write. The name of the color profile. Valid only when <a href="#">colorProfileType</a> = <code>ColorProfile.CUSTOM OR WORKING</code> .
<code>colorProfileType</code>	<a href="#">ColorProfileType</a>	Read-write. Whether the document uses the working color profile, a custom profile, or no profile.
<code>colorSamplers</code>	<a href="#">ColorSamplers</a>	Read-only. The current color samplers associated with this document.
<code>componentChannels</code>	array of <a href="#">Channel</a>	Read-only. The color channels that make up the document; for instance, the Red, Green, and Blue channels for an RGB document.



Property	Value type	What it is (Continued)
<code>countItems</code>	<a href="#">CountItems</a>	Read-only. The current count items.  <b>Note:</b> For additional information about count items, see Adobe Photoshop CC 2014 help on the Count Tool.
<code>fullName</code>	<a href="#">File</a>	Read-only. The full path name of the document.
<code>guides</code>	<a href="#">Guides</a>	Read-only. The guides collection.
<code>height</code>	<a href="#">UnitValue</a>	Read-only. The height of the document (unit value).
<code>histogram</code>	array of number	Read-only. A histogram showing the number of pixels at each color intensity level for the composite channel. The array contains 256 members.  Valid only when <code>mode</code> = <code>DocumentMode.RGB</code> , <code>CMYK</code> ; or <code>INDEXEDCOLOR</code> .
<code>historyStates</code>	<a href="#">HistoryStates</a>	Read-only. The history states collection.
<code>info</code>	<a href="#">DocumentInfo</a>	Read-only. Metadata about the document.
<code>layerComps</code>	<a href="#">LayerComps</a>	Read-only. The layer compositions collection.
<code>layers</code>	<a href="#">Layers</a>	Read-only. The layers collection.
<code>layerSets</code>	<a href="#">LayerSets</a>	Read-only. The layer set collection.
<code>managed</code>	boolean	Read-only. True if the document is a workgroup document.
<code>measurementScale</code>	<a href="#">MeasurementScale</a>	Read-only. The measurement scale for the document.  <b>Note:</b> The measurement scale feature is available in the Extended version only.
<code>mode</code>	<a href="#">DocumentMode</a>	Read-only. The color profile.
<code>name</code>	string	Read-only. The document's name.
<code>parent</code>	<a href="#">Application</a>	Read-only. The application object that contains this document.
<code>path</code>	<a href="#">File</a>	Read-only. The path to the document.
<code>pathItems</code>	<a href="#">PathItems</a>	Read-only. The path items collection.
<code>pixelAspectRatio</code>	number [0.100..10.000]	Read-write. The (custom) pixel aspect ratio to use.
<code>printSettings</code>	<a href="#">DocumentPrintSettings</a>	Read-only. The print settings for the document.

Property	Value type	What it is (Continued)
<code>quickMaskMode</code>	boolean	Read-write. True if the document is in Quick Mask mode.
<code>resolution</code>	number	Read-only. The document's resolution (in pixels per inch).
<code>saved</code>	boolean	Read-only. True if the document has been saved since the last change.
<code>selection</code>	<a href="#">Selection</a>	Read-only. The selected area of the document.
<code>typename</code>	string	Read-only. The class name of the <code>Document</code> object.
<code>width</code>	<a href="#">UnitValue</a>	Read-only. The width of the document (unit value).
<code>xmpMetadata</code>	<a href="#">xmpMetadata</a>	Read-only. XMP metadata for the document. Camera RAW settings for the image are stored here for example.

## Methods

Method	Parameter type	Returns	What it does
<b>autoCount</b> (channel, threshold)	<a href="#">Channel</a> number		Counts the number of objects in a document. Available in the Extended Version only.  Creates a <a href="#">CountItem</a> object for each object counted.  For additional information about how to set up objects to count, see the Count Tool in the Adobe Photoshop CC 2014 Help
<b>changeMode</b> (destinationMode [, options])	<a href="#">ChangeMode</a> <a href="#">BitmapConversionOptions</a> or <a href="#">IndexedConversionOptions</a>		Changes the color profile of the document.
<b>close</b> ([saving])	<a href="#">SaveOptions</a>		Closes the document. If any changes have been made, the script presents an alert with three options: save, do not save, prompt to save. The optional parameter specifies a selection in the alert box (default: <code>SaveOptionsType.PROMPTTOSAVECHANGES</code> ).
<b>convertProfile</b> (destinationProfile, intent [, blackPointCompensation] [, dither])	string <a href="#">Intent</a> boolean boolean		Changes the color profile.  The <code>destinationProfile</code> parameter must be either a string that names the color mode or <code>Working RGB</code> , <code>Working CMYK</code> , <code>Working Gray</code> , <code>Lab Color</code> (meaning one of the working color spaces or Lab color).
<b>crop</b> (bounds [, angle] [, width] [, height])	array of 4 <a href="#">UnitValue</a> number <a href="#">UnitValue</a> <a href="#">UnitValue</a>		Crops the document. The <code>bounds</code> parameter is an array of four coordinates for the region remaining after cropping, [left, top, right, bottom].
<b>duplicate</b> ([name ] [, mergeLayersOnly] )	string boolean	<a href="#">Document</a>	Creates a duplicate of the <code>document</code> object.  The optional parameter <code>name</code> provides the name for the duplicated document.  The optional parameter <code>mergeLayersOnly</code> indicates whether to only duplicate merged layers.

Method	Parameter type	Returns	What it does (Continued)
<b>exportDocument</b> (exportIn [, exportAs] [, options])	<a href="#">File</a> <a href="#">ExportType</a> <a href="#">ExportOptionsIllustrator</a> —OR— <a href="#">ExportOptionsSaveForWeb</a>		Exports the paths in the document to an Illustrator file, or exports the document to a file with Web or device viewing optimizations.  This is equivalent to choosing <b>File &gt; Export &gt; Paths To Illustrator</b> , or <b>File &gt; Save For Web and Devices</b> .
<b>flatten</b> ( )			Flattens all layers in the document.
<b>flipCanvas</b> (direction)	<a href="#">Direction</a>		Flips the image within the canvas in the specified direction.
<b>importAnnotations</b> (file)	<a href="#">File</a>		Imports annotations into the document.
<b>mergeVisibleLayers</b> ( )			Flattens all visible layers in the document.
<b>paste</b> ([intoSelection])	boolean	<a href="#">ArtLayer</a>	Pastes the contents of the clipboard into the document. If the optional argument is set to <code>true</code> and a selection is active, the contents are pasted into the selection.
<b>print</b> ([sourceSpace] [, printSpace] [, intent] [blackPointCompensation])	<a href="#">SourceSpaceType</a> string <a href="#">Intent</a> boolean		Prints the document.  <code>printSpace</code> specifies the color space for the printer. Valid values are <code>nothing</code> (that is, the same as the source); or <code>Working RGB</code> , <code>Working CMYK</code> , <code>Working Gray</code> , <code>Lab Color</code> (meaning one of the working color spaces or Lab color); or a string specifying a specific colorspace (default is same as source).
<b>printOneCopy</b> ( )			Print one copy of the document.
<b>rasterizeAllLayers</b> ( )			Rasterizes all layers.
<b>recordMeasurements</b> ([source] [, dataPoints])	<a href="#">MeasurementSource</a> array of string		Record measurements of document.
<b>resizeCanvas</b> ([width] [, height] [, anchor])	<a href="#">UnitValue</a> <a href="#">UnitValue</a> <a href="#">AnchorPosition</a>		Changes the size of the canvas to display more or less of the image but does not change the image size. See <a href="#">resizeImage</a> .

Method	Parameter type	Returns	What it does (Continued)
<b>resizeImage</b> ([width] [, height] [, resolution] [, resampleMethod] [, amount])	<a href="#">UnitValue</a> <a href="#">UnitValue</a> number <a href="#">ResampleMethod</a> number		Changes the size of the image.  The <code>amount</code> parameter controls the amount of noise value when using preserve details (Range: 0 - 100).
<b>revealAll</b> ()			Expands the document to show clipped sections.
<b>rotateCanvas</b> (angle)	number		Rotates the canvas (including the image) in clockwise direction.
<b>save</b> ()			Saves the document.
<b>saveAs</b> (saveIn [, options] [, asCopy] [, extensionType])	<a href="#">File</a> object (see description) boolean <a href="#">Extension</a>		Saves the document in a specific format.  Specify the save options appropriate to the format by passing one of these objects:  <a href="#">BMPSaveOptions</a> <a href="#">DCS1 SaveOptions</a> <a href="#">DCS2 SaveOptions</a> <a href="#">EPSSaveOptions</a> <a href="#">GIFSaveOptions</a> <a href="#">JPEGSaveOptions</a> <a href="#">PDFSaveOptions</a> <a href="#">PhotoshopSaveOptions</a> <a href="#">PICTFileSaveOptions</a> <a href="#">PICTResourceSaveOptions</a> <a href="#">PixarSaveOptions</a> <a href="#">PNGSaveOptions</a> <a href="#">RawSaveOptions</a> <a href="#">SGIRGBSaveOptions</a> <a href="#">TargaSaveOptions</a> <a href="#">TiffSaveOptions</a>
<b>splitChannels</b> ()		array of <a href="#">Document</a>	Splits the document channels into separate images.
<b>suspendHistory</b> (historyString javascriptString)	string string		Provides a single entry in history states for the entire script provided by <code>javascriptString</code> . Allows a single undo for all actions taken in the script.  The <code>historyString</code> parameter provides the string to use for the history state.  The <code>javascriptString</code> parameter provides a string of JavaScript code to execute while history is suspended.
<b>trap</b> (width)	number		Applies trapping to a CMYK document.  Valid only when <code>docRef.mode = DocumentMode.CMYK</code> .

Method	Parameter type	Returns	What it does (Continued)
<b>trim</b> ([type] [, top] [, left] [, bottom] [, right])	<a href="#">TrimType</a> boolean boolean boolean boolean		Trims the transparent area around the image on the specified sides of the canvas.  Default is <code>true</code> for all Boolean parameters.

## Document sample script

The following script creates a document that contains two images (a sunflower and a duck) obtained from the Adobe Photoshop CC 2014 Samples folder and employs the following steps:

- Determines which image is larger.
- Resizes the smaller image to match the larger image.
- Creates a merged document twice as high as either image in order to hold both images.
- Selects part of the document and pastes the sunflower into the selection.
- Inverts the selection and pastes the duck into the lower part of the document.
- Positions the sunflower over the duck.

### Document.jsx

```
// Save the current preferences
var startRulerUnits = app.preferences.rulerUnits
var startTypeUnits = app.preferences.typeUnits
var startDisplayDialogs = app.displayDialogs

// Set Adobe Photoshop CC 2014 to use pixels and display no dialogs
app.preferences.rulerUnits = Units.PIXELS
app.preferences.typeUnits = TypeUnits.PIXELS
app.displayDialogs = DialogModes.NO

// first close all the open documents
while (app.documents.length) {
    app.activeDocument.close()
}

// Open the sunflower and duck files from the samples folder
var flowerDoc = open(File(app.path + "/Samples/Sunflower.psd"))
var duckDoc = open(File(app.path + "/Samples/Ducky.tif"))

// Find out which document is larger
// Resize the smaller document the to the larger document's size
// The resize requires the document be the active/front document
if ((flowerDoc.width.value * flowerDoc.height.value) >
    (duckDoc.width.value * duckDoc.height.value)) {
    app.activeDocument = duckDoc
    duckDoc.resize(flowerDoc.width, flowerDoc.height)
}
else {
    app.activeDocument = flowerDoc
    flowerDoc.resizeImage(duckDoc.width, duckDoc.height)
}

// Create a new document twice as high as two files
```

```
var mergedDoc = app.documents.add(duckDoc.width, duckDoc.height * 2,
duckDoc.resolution, "FlowerOverDuck")

// Copy the flower to the top; make it the active document so we can manipulate it
app.activeDocument = flowerDoc
flowerDoc.activeLayer.copy()

//Paste the flower to the merged document, making the merged document active
app.activeDocument = mergedDoc

// Select a square area at the top of the new document
var selRegion = Array(Array(0, 0),
    Array(mergedDoc.width.value, 0),
    Array(mergedDoc.width.value, mergedDoc.height.value / 2),
    Array(0, mergedDoc.height.value / 2),
    Array(0, 0))
// Create the selection
mergedDoc.selection.select(selRegion)

//Paste in the flower
mergedDoc.paste(TRUE)

// do the same thing for the duck
app.activeDocument = duckDoc
duckDoc.activeLayer.copy()

app.activeDocument = mergedDoc
mergedDoc.selection.select(selRegion)

// Inverting the selection so the bottom of the document is now selected
mergedDoc.selection.invert()

// Paste the duck
mergedDoc.paste(TRUE)

// get rid of our originals without modifying them
duckDoc.close(SaveOptions.DONOTSAVECHANGES)
flowerDoc.close(SaveOptions.DONOTSAVECHANGES)

// Reset the application preferences
app.preferences.rulerUnits = startRulerUnits
app.preferences.typeUnits = startTypeUnits
app.displayDialogs = startDisplayDialogs
```

# DocumentPrintSettings

The print settings for a document.

## Properties

Property	Value type	What it is
<code>backgroundColor</code>	<a href="#">SolidColor</a>	Read-write. Background color of page.
<code>bleedWidth</code>	<a href="#">UnitValue</a>	Read-write. Bleed width
<code>caption</code>	boolean	Read-write. Print the caption found in FileInfo.
<code>centerCropMarks</code>	boolean	Read-write. Print center crop marks.
<code>colorBars</code>	boolean	Read-write. Print color calibration bars.
<code>copies</code>	number	Read-write. Number of copies to print.
<code>cornerCropMarks</code>	boolean	Read-write. Print corner crop marks.
<code>colorHandling</code>	<a href="#">PrintColorHandling</a>	Read-only. Color handling.
<code>activePrinter</code>	string	Read-write. The currently active printer.
<code>flip</code>	boolean	Read-write. Flip the image horizontally.
<code>hardProof</code>	boolean	Read-write. Print a hard proof.
<code>interpolate</code>	boolean	Read-write.
<code>labels</code>	boolean	Read-write. Prints the document title.
<code>mapBlack</code>	boolean	Read-write. Map blacks.
<code>negative</code>	boolean	Read-write. Invert the image colors.
<code>renderIntent</code>	Intent	Read-write. Color conversion intent when print space is different from the source space.
<code>posX</code>	<a href="#">UnitValue</a>	Read-only. The x position of the image on page.
<code>posY</code>	<a href="#">UnitValue</a>	Read-only. The y position of the image on page.
<code>printBorder</code>	<a href="#">UnitValue</a>	Read-write. The width of the print border.
<code>printerName</code>	string	Read-write. Name of the printer.
<code>printSpace</code>	string	Read-write. color space for printer. Can be nothing (meaning same as source); 'Working RGB', 'Working CMYK', 'Working Gray', 'Lab Color' (meaning one of the working spaces or Lab color); or a string specifying a specific colorspace (default is same as source)
<code>registrationMarks</code>	boolean	Read-write. Print registration marks.



---

<b>Property</b>	<b>Value type</b>	<b>What it is (Continued)</b>
<code>scale</code>	number	Read-only. Scale of image on page.
<code>vectorData</code>	boolean	Read-write. Include vector data.

## Methods

Method	Parameter type	Returns	What it does
<b>setPagePosition</b> (docPosition, posX, posY, scale)	<a href="#">DocPositionStyle</a> <a href="#">UnitValue</a> <a href="#">UnitValue</a> number		Set the position of the image on the page.

## DocumentInfo

Metadata about a document object.

Access through the [Document.info](#) property. For example, the following sets the `author`, `caption`, and `copyrighted` properties:

```
var docRef = open(fileList[i])
// set the file info
docRef.info.author = "Mr. Adobe programmer"
docRef.info.caption = "Adobe Photo shoot"
docRef.info.copyrighted = CopyrightedType.COPYRIGHTEDWORK
```

These values can be set interactively by choosing **File > File Info**.

## Properties

Property	Value type	What it is
<code>author</code>	string	Read-write.
<code>authorPosition</code>	string	Read-write.
<code>caption</code>	string	Read-write.
<code>captionWriter</code>	string	Read-write.
<code>category</code>	string	Read-write.
<code>city</code>	string	Read-write.
<code>copyrighted</code>	<a href="#">CopyrightedType</a>	Read-write. The copyrighted status.
<code>copyrightNotice</code>	string	Read-write.
<code>country</code>	string	Read-write.
<code>creationDate</code>	string	Read-write.
<code>credit</code>	string	Read-write.
<code>exif</code>	array of array [ <i>tag data</i> ]	Read-only. Camera data that includes camera settings used when the image was taken.  Each array member is a tag pair, an array of [ <i>tag</i> , <i>tag_data</i> ]; for example, [ "camera" "Cannon"].
<code>headline</code>	string	Read-write.
<code>instructions</code>	string	Read-write.
<code>jobName</code>	string	Read-write.
<code>keywords</code>	array of string	Read-write. A list of keywords that can identify the document or its contents.
<code>ownerUrl</code>	string	Read-write.

Property	Value type	What it is (Continued)
<b>parent</b>	<a href="#">Document</a>	Read-only. The <code>info</code> object's container.
<b>provinceState</b>	string	Read-write.
<b>source</b>	string	Read-write.
<b>supplementalCategories</b>	array of string	Read-write.
<b>title</b>	string	Read-write.
<b>transmissionReference</b>	string	Read-write.
<b>typename</b>	string	Read-only. The class name of the referenced <code>info</code> object.
<b>urgency</b>	<a href="#">Urgency</a>	Read-write.

## DocumentInfo sample Script

The following script sets document info (metadata) for all of the files in a specified folder and then saves the modified files as low-quality JPEG images in a new folder without changing the originals.

- Ask the user to specify the folder that contains the original files and the output folder for the JPEG images, and then check that the folders exist.
- Open each file and use the `documentInfo` object properties to tag it with the following metadata:
  - author: Adobe programmer
  - caption: Adobe Photo shoot
  - captionWriter: Adobe programmer
  - city: San Jose
  - copyrightNotice: Copyright (c) Adobe programmer Photography
  - copyrighted status: Copyrighted Work
  - country: USA
  - state: CA
- Save the new documents in JPEG format with a low quality setting.

### DocumentInfo.jsx

```
// Save the current preferences
var startDisplayDialogs = app.displayDialogs

// Set Adobe Photoshop CC 2014 to use pixels and display no dialogs
app.displayDialogs = DialogModes.NO

// ask the user for the input and output folders
var inputFolder = Folder.selectDialog("Select a folder to tag")
var outputFolder = Folder.selectDialog("Select a folder for the output files")

// see if we got something interesting from the dialog
if (inputFolder != null && outputFolder != null) {
    // get all the files found in this folder
    var fileList = inputFolder.GetFiles()
```

```
// save the outputs in JPEG
var jpegOptions = new JPEGSaveOptions()
// set the jpeg quality really low so the files are small
jpegOptions.quality = 1
// open each one in turn
for (var i = 0; i < fileList.length; i++) {
  // The fileList includes both folders and files so open only files
  if (fileList[i] instanceof File && fileList[i].hidden == false) {
    // get a reference to the new document
    var docRef = open(fileList[i])

    // tag all of the documents with photo shoot information
    docRef.info.author = "Adobe programmer"
    docRef.info.caption = "Adobe Photo shoot"
    docRef.info.captionWriter = "Adobe programmer"
    docRef.info.city = "San Jose"
    docRef.info.copyrightNotice = "Copyright (c) Adobe programmer
      Photography"
    docRef.info.copyrighted = CopyrightedType.COPYRIGHTEDWORK
    docRef.info.country = "USA"
    docRef.info.provinceState = "CA"

    // change the date to a Adobe Photoshop CC 2014 date format
    // "YYYYMMDD"
    var theDate = new Date()
    // the year is from 1900 ???
    var theYear = (theDate.getYear() + 1900).toString()
    // convert the month from 0..12 to 00..12
    var theMonth = theDate.getMonth().toString()
    if (theDate.getMonth() < 10) {
      theMonth = "0" + theMonth
    }
    // convert the day from 0..31 to 00..31
    var theDay = theDate.getDate().toString()
    if (theDate.getDate() < 10) {
      theDay = "0" + theDay
    }
    // stick them all together
    docRef.info.creationDate = theYear + theMonth + theDay

    // flatten because we are saving to JPEG
    docRef.flatten()
    // go to 8 bit because we are saving to JPEG
    docRef.bitsPerChannel = BitsPerChannelType.EIGHT

    // save and close
    docRef.saveAs(new File(outputFolder + "/Output" + i + ".jpg"), jpegOptions)

    // don't modify the original
    docRef.close(SaveOptions.DONOTSAVECHANGES)
  }
}

// Reset the application preferences
app.displayDialogs = startDisplayDialogs
```

## Documents

The collection of open [Document](#) objects.

Access this list through the [Application.documents](#) collection property, which is available through the `app` global variable, or directly at the top level. For example, the following adds a new document to the collection:

```
app.documents.add(800, 500, 72, "myDocument", NewDocumentMode.RGB)
```

—or—

```
documents.add(800, 500, 72, "myDocument", NewDocumentMode.RGB)
```

## Properties

Property	Value type	What it is
<b>length</b>	number	Read-only. The number of elements in the <code>documents</code> collection.
<b>parent</b>	<a href="#">Application</a>	Read-only. The containing application.
<b>typename</b>	string	Read-only. The class name of the referenced <code>documents</code> object.

## Methods

Method	Parameter type	Returns	What it does
<b>add</b> ( [width] [, height] [, resolution] [, name] [, mode] [, initialFill] [, pixelAspectRatio] [, bitsPerChannel]  [, colorProfileName] )	<a href="#">UnitValue</a> <a href="#">UnitValue</a> number string <a href="#">NewDocumentMode</a> <a href="#">DocumentFill</a> number [0.1..10.00] <a href="#">BitsPerChannelType</a> string	<a href="#">Document</a>	Creates a new document object and adds it to this collection.  <code>pixelAspectRatio</code> : Default is 1.0, a square aspect ratio.  <code>bitsPerChannelType</code> : Default is <code>BitsPerChannelType.EIGHT</code> .
<b>getByName</b> (name)	string	<a href="#">Document</a>	Gets the first element in the <code>documents</code> collection with the provided name

## EPSOpenOptions

Options for opening a document in EPS format using the [Application.open\(\)](#) method.

### Properties

Property	Value type	What it is
<b>antiAlias</b>	boolean	Read-write. True to use antialias.
<b>constrainProportions</b>	boolean	Read-write. True to constrain the proportions of the image.
<b>height</b>	<a href="#">UnitValue</a>	Read-write. The height of the image (unit value).
<b>mode</b>	<a href="#">OpenDocumentMode</a>	Read-write. The color profile to use as the document mode.
<b>resolution</b>	number	Read-write. The resolution of the document in pixels per inch.
<b>typename</b>	string	Read-only. The class name of the referenced <code>EPSOpenOptions</code> object.
<b>width</b>	<a href="#">UnitValue</a>	Read-write. The width of the image (unit value).

## EPSSaveOptions

Options for saving a document in EPS format using the [Document.saveAs\(\)](#) method.

### Properties

Property	Value type	What it is
<b>embedColorProfile</b>	boolean	Read-write. True to embed the color profile in this document.
<b>encoding</b>	<a href="#">SaveEncoding</a>	Read-write. The type of encoding to use (default: <code>SaveEncoding.BINARY</code> ).
<b>halftoneScreen</b>	boolean	Read-write. True to include the halftone screen (default: <code>false</code> ).
<b>interpolation</b>	boolean	Read-write. True to use image interpolation (default: <code>false</code> ).
<b>preview</b>	<a href="#">Preview</a>	Read-write. The preview type.
<b>psColorManagement</b>	boolean	Read-write. True to use Postscript color management (default: <code>false</code> ).
<b>transferFunction</b>	boolean	Read-write. True to include the Transfer functions to compensate for dot gain between the image and film (default: <code>false</code> ).
<b>transparentWhites</b>	boolean	Read-write. True to display white areas as transparent.  Valid only when <code>document.mode = DocumentMode.BITMAP</code> . See also <a href="#">changeMode()</a> .
<b>typename</b>	string	Read-only. The class name of the referenced <code>EPSSaveOptions</code> object.
<b>vectorData</b>	boolean	Read-write. True to include vector data.  Valid only if the document includes vector data (text).



## ExportOptionsIllustrator

Options for exporting [PathItem](#) objects to an Adobe Illustrator® file using using the [Document.exportDocument\(\)](#) method. These options are the options that you can provide when you choose **File > Export > Paths To Illustrator**.

### Properties

Property	Value type	What it is
<code>path</code>	<a href="#">IllustratorPathType</a>	Read-write. The type of path to export (default: <code>IllustratorPathType.DOCUMENTBOUNDS</code> ).
<code>pathName</code>	string	Read-write. The name of the path to export. Valid only when <a href="#">path</a> = <code>IllustratorPathType.NAMEDPATH</code> .
<code>typename</code>	string	Read-only. The class name of the referenced <code>exportOptionsIllustrator</code> object.

## ExportOptionsSaveForWeb

Options for optimizing a document for the web or devices using the [Document.exportDocument\(\)](#) method. These are the options that you can provide when you choose **File > Save For Web and Devices**.

### Properties

Property	Value type	What it is
<b>blur</b>	number	Read-write. Applies blur to the image to reduce artifacts (default: 0.0).
<b>colorReduction</b>	<a href="#">ColorReductionType</a>	Read-write. The color reduction algorithm (default: <code>ColorReductionType.SELECTIVE</code> ).
<b>colors</b>	number	Read-write. The number of colors in the palette (default: 256).
<b>dither</b>	<a href="#">Dither</a>	Read-write. The type of dither (default: <code>Dither.DIFFUSION</code> ).
<b>ditherAmount</b>	number	Read-write. The amount of dither (default: 100). Valid only when <a href="#">dither</a> = <code>Dither.DIFFUSION</code> .
<b>format</b>	<a href="#">SaveDocumentType</a>	Read-write. The file format to use (default: <code>SaveDocumentType.COMPUSERVEGIF</code> ).  <b>Note:</b> For this property, only <code>COMPUSERVEGIF</code> , <code>JPEG</code> , <code>PNG-8</code> , <code>PNG-24</code> , and <code>BMP</code> are supported.
<b>includeProfile</b>	boolean	Read-write. True to include the document's embedded color profile (default: <code>false</code> ).
<b>interlaced</b>	boolean	Read-write. True to download in multiple passes; progressive (default: <code>false</code> ).
<b>lossy</b>	number	Read-write. The amount of lossiness allowed (default: 0).
<b>matteColor</b>	<a href="#">RGBColor</a>	Read-write. The colors to blend transparent pixels against.
<b>optimized</b>	boolean	Read-write. True to create smaller but less compatible files (default: <code>true</code> ). Valid only when <a href="#">format</a> = <code>SaveDocumentType.JPEG</code> .
<b>PNG8</b>	boolean	Read-write. Indicates the number of bits; <code>true</code> = 8, <code>false</code> = 24 (default: <code>true</code> ). Valid only when <a href="#">format</a> = <code>SaveDocumentType.PNG</code> .

Property	Value type	What it is (Continued)
<b>quality</b>	number [0..100]	Read-write. The quality of the produced image as a percentage; default: 60.
<b>transparency</b>	boolean	Read-write. Indication of transparent areas of the image should be included in the saved image(default: true).
<b>transparencyAmount</b>	number	Read-write. The amount of transparency dither (default: 100). Valid only if <a href="#">transparency</a> = true.
<b>transparencyDither</b>	<a href="#">Dither</a>	Read-write. The transparency dither algorithm (default: transparencyDither = Dither.NONE).
<b>typename</b>	string	Read-only. The class name of the referenced <code>ExportOptionsSaveForWeb</code> object.
<b>webSnap</b>	number	Read-write. The tolerance amount within which to snap close colors to web palette colors (default: 0).

## File

## Folder

ExtendScript defines the JavaScript classes `File` and `Folder` to encapsulate file-system references in a platform-independent manner; see ['JavaScript support in Adobe Photoshop CC 2014' on page 32](#). For references details of these classes, see the *JavaScript Tools Guide*.

## GalleryBannerOptions

Options for the [bannerOptions](#) property of the [GalleryOptions](#) object.

**Tip:** You can preserve default values for many of these properties by setting the [GalleryOptions](#) property [preserveAllMetadata](#) to true; this is the same as choosing **File > Automate > Web Photo Gallery**, and then choosing **Preserve all metadata** in the Options area of the Web Photo Gallery dialog.

### Properties

Property	Value type	What it is
<code>contactInfo</code>	string	Read-write. The web photo gallery contact info.
<code>date</code>	string	Read-write. The web photo gallery date (default: current date).
<code>font</code>	<a href="#">GalleryFontType</a>	Read-write. The font setting for the banner text (default: <code>GalleryFontType.ARIAL</code> ).
<code>fontSize</code>	number [1..7]	Read-write. The font size for the banner text (default: 3).
<code>photographer</code>	string	Read-write. The web photo gallery photographer.
<code>siteName</code>	string	Read-write. The web photo gallery site name (default: <code>Adobe Web Photo Gallery</code> ).
<code>typename</code>	string	Read-only. The class name of the referenced <code>galleryBannerOptions</code> object.

## GalleryCustomColorOptions

Options for the [customColorOptions](#) property of the [GalleryOptions](#) object.

**Tip:** You can preserve default values for many of these properties by setting the [GalleryOptions](#) property [preserveAllMetadata](#) to true; this is the same as choosing **File > Automate > Web Photo Gallery**, and then choosing **Preserve all metadata** in the Options area of the Web Photo Gallery dialog.

### Properties

Property	Value type	What it is
<code>activeLinkColor</code>	<a href="#">RGBColor</a>	Read-write. The color to use to indicate an active link.
<code>backgroundColor</code>	<a href="#">RGBColor</a>	Read-write. The background color.
<code>bannerColor</code>	<a href="#">RGBColor</a>	Read-write. The banner color.
<code>linkColor</code>	<a href="#">RGBColor</a>	Read-write. The color to use to indicate a link.
<code>textColor</code>	<a href="#">RGBColor</a>	Read-write. The text color.
<code>typename</code>	string	Read-only. The class name of the referenced <code>galleryCustomColorOptions</code> object.
<code>visitedLinkColor</code>	<a href="#">RGBColor</a>	Read-write. The color to use to indicate a visited link.

## GalleryImagesOptions

Options for the [imagesOptions](#) property of the [GalleryOptions](#) object.

**Tip:** You can preserve default values for many of these properties by setting the [GalleryOptions](#) property [preserveAllMetadata](#) to true; this is the same as choosing **File > Automate > Web Photo Gallery**, and then choosing **Preserve all metadata** in the Options area of the Web Photo Gallery dialog.

### Properties

Property	Value type	What it is
<b>border</b>	number [0..99]	Read-write. The size (in pixels) of the border that separates images (default: 0).
<b>caption</b>	boolean	Read-write. True to generate image captions (default: <code>false</code> ).
<b>dimension</b>	number	Read-write. The resized image dimensions in pixels (default: 350). Valid only when <a href="#">resizeImages</a> = <code>true</code> .
<b>font</b>	<a href="#">GalleryFontType</a>	Read-write. The font to use for image captions (default: <code>GalleryFontType.ARIAL</code> ).
<b>fontSize</b>	number [1..7]	Read-write. The font size for image captions (default: 3). Valid only when <a href="#">caption</a> = <code>true</code> .
<b>imageQuality</b>	number [0..12]	Read-write. The quality setting for a JPEG image (default: 5).
<b>includeCopyright</b>	boolean	Read-write. True to include copyright information in captions (default: <code>false</code> ). Valid only when <a href="#">caption</a> = <code>true</code> .
<b>includeCredits</b>	boolean	Read-write. True to include the credits in image captions (default: <code>false</code> ). Valid only when <a href="#">caption</a> = <code>true</code> .
<b>includeFilename</b>	boolean	Read-write. True to include the file name in image captions (default: <code>true</code> ). Valid only when <a href="#">caption</a> = <code>true</code> .
<b>includeTitle</b>	boolean	Read-write. True to include the title in image captions (default: <code>false</code> ). Valid only when <a href="#">caption</a> = <code>true</code> .
<b>numericLinks</b>	boolean	Read-write. True to add numeric links (default: <code>true</code> ).

Property	Value type	What it is (Continued)
<b>resizeConstraint</b>	<a href="#">GalleryConstrainType</a>	Read-write. The image dimensions to constrain in the gallery image (default: <code>GalleryConstrainType.CONSTRAINBOTH</code> ). Valid only when <a href="#">resizeImages</a> = <code>true</code> .
<b>resizeImages</b>	boolean	Read-write. True to automatically resize images for placement on the gallery pages (default: <code>true</code> ).
<b>typename</b>	string	Read-only. The class name of the referenced <code>galleryImagesOptions</code> object.



## GalleryOptions

Options for a Web photo gallery, created with [Application.makePhotoGallery\(\)](#).

**Tip:** You can preserve default values for many of these properties by choosing **File > Automate > Web Photo Gallery**, and then choosing **Preserve all metadata** in the Options area of the Web Photo Gallery dialog.

### Properties

Property	Value type	What it is
<code>addSizeAttributes</code>	boolean	Read-write. True to add width and height attributes for images (default: <code>true</code> ).
<code>bannerOptions</code>	<a href="#">GalleryBannerOptions</a>	Read-write. The options related to banner settings.
<code>customColorOptions</code>	<a href="#">GalleryCustomColorOptions</a>	Read-write. The options related to custom color settings.
<code>emailAddress</code>	string	Read-write. The email address to show on the web page.
<code>imagesOptions</code>	<a href="#">GalleryImagesOptions</a>	Read-write. The options related to images settings.
<code>includeSubFolders</code>	boolean	Read-write. True to include all files found in sub folders of the input folder (default: <code>true</code> ).
<code>layoutStyle</code>	string	Read-write. The style to use for laying out the web page (default: <code>Centered Frame 1 - Basic</code> ).
<code>preserveAllMetadata</code>	boolean	Read-write. True to save metadata (default: <code>false</code> ).
<code>securityOptions</code>	<a href="#">GallerySecurityOptions</a>	Read-write. The options related to security settings.
<code>thumbnailOptions</code>	<a href="#">GalleryThumbnailOptions</a>	Read-write. The options related to thumbnail image settings.
<code>typename</code>	string	Read-only. The class name of the referenced <code>galleryOptions</code> object.
<code>useShortExtension</code>	boolean	Read-write. True to use the short web page extension <code>.htm</code> . If false, use the web page extension <code>.html</code> (default: <code>true</code> ).
<code>useUTF8Encoding</code>	boolean	Read-write. True to use UTF-8 encoding for the web page (default: <code>false</code> ).

## GallerySecurityOptions

Options for the [securityOptions](#) property of the [GalleryOptions](#) object.

**Tip:** You can preserve default values for many of these properties by setting the [GalleryOptions](#) property [preserveAllMetadata](#) to true; this is the same as choosing **File > Automate > Web Photo Gallery**, and then choosing **Preserve all metadata** in the Options area of the Web Photo Gallery dialog.

### Properties

Property	Value type	What it is
<code>content</code>	<a href="#">GallerySecurityType</a>	Read-write. The web photo gallery security content (default: <code>GallerySecurityType.NONE</code> ).
<code>font</code>	<a href="#">GalleryFontType</a>	Read-write. The web photo gallery security font (default: <code>GalleryFontType.ARIAL</code> ).
<code>fontSize</code>	number [1..72]	Read-write. The web photo gallery security font size (default: 3).
<code>opacity</code>	number	Read-write. The web page security opacity as a percent (default: 100).
<code>text</code>	string	Read-write. The web photo gallery security custom text.
<code>textColor</code>	<a href="#">GallerySecurityTextColorType</a>	Read-write. The web page security text color.
<code>textPosition</code>	<a href="#">GallerySecurityTextPositionType</a>	Read-write. The web photo gallery security text position (default: <code>GallerySecurityTextPositionType.CENTERED</code> ).
<code>textRotate</code>	<a href="#">GallerySecurityTextRotateType</a>	Read-write. The web photo gallery security text orientation to use (default: <code>GallerySecurityTextRotateType.ZERO</code> ).
<code>typename</code>	string	Read-only. The class name of the referenced <code>gallerySecurityOptions</code> object.

## GalleryThumbnailOptions

Options for the [thumbnailOptions](#) property of the [GalleryOptions](#) object.

**Tip:** You can preserve default values for many of these properties by setting the [GalleryOptions](#) property [preserveAllMetadata](#) to true; this is the same as choosing **File > Automate > Web Photo Gallery**, and then choosing **Preserve all metadata** in the Options area of the Web Photo Gallery dialog.

### Properties

Property	Value type	What it is
<b>border</b>	number [0..99]	Read-write. The amount of border pixels you want around your thumbnail images (default: 0).
<b>caption</b>	boolean	Read-write. True if there is a caption (default: false).
<b>columnCount</b>	number	Read-write. The number of columns on the page (default: 5).
<b>dimension</b>	number	Read-write. The web photo gallery thumbnail dimension in pixels (default: 75).
<b>font</b>	<a href="#">GalleryFontType</a>	Read-write. The web photo gallery font (default: <code>GalleryFontType.ARIAL</code> ).
<b>fontSize</b>	number [1..7]	Read-write. The font size for thumbnail images text (default: 3).
<b>includeCopyright</b>	boolean	Read-write. True to include copyright information for thumbnails (default: false).
<b>includeCredits</b>	boolean	Read-write. True to include credits for thumbnails (default: false).
<b>includeFilename</b>	boolean	Read-write. True to include file names for thumbnails (default: false).
<b>includeTitle</b>	boolean	Read-write. True to include titles for thumbnails (default: false).
<b>rowCount</b>	number	Read-write. The number of rows on the page (default: 3).
<b>size</b>	<a href="#">GalleryThumbSizeType</a>	Read-write. The thumbnail image size (default: <code>GalleryThumbSizeType.MEDIUM</code> ).
<b>typename</b>	string	Read-only. The class name of the referenced <code>GalleryThumbnailOptions</code> object.

## GIFSaveOptions

Options for saving a document in GIF format using the [Document.saveAs\(\)](#) method.

### Properties

Property	Value type	What it is
<b>colors</b>	number	Read-write. The number of palette colors. Valid only when <a href="#">palette</a> = <code>Palette.LOCALADAPTIVE</code> , <code>LOCALPERCEPTUAL</code> , <code>LOCALSELECTIVE</code> , <code>MACOSPALETTE</code> , <code>UNIFORM</code> , <code>WEBPALETTE</code> ; OR <code>WINDOWSPALETTE</code> .
<b>dither</b>	<a href="#">Dither</a>	Read-write. The dither type.
<b>ditherAmount</b>	number [1..100]	Read-write. The amount of dither (default: 75). Valid only when <a href="#">dither</a> = <code>Dither.DIFFUSION</code> .
<b>forced</b>	<a href="#">ForcedColors</a>	Read-write. The type of colors to force into the color palette.
<b>interlaced</b>	boolean	Read-write. True if rows should be interlaced (default: <code>false</code> ).
<b>matte</b>	<a href="#">MatteType</a>	Read-write. The color to use to fill anti-aliased edges adjacent to transparent areas of the image (default: <code>MatteType.WHITE</code> ). When <a href="#">transparency</a> = <code>false</code> , the matte color is applied to transparent areas.
<b>palette</b>	<a href="#">PaletteType</a>	Read-write. The type of palette to use (default: <code>Palette.LOCALSELECTIVE</code> ).
<b>preserveExactColors</b>	boolean	Read-write. True to protect colors in the image that contain entries in the color table from being dithered. Valid only when <a href="#">dither</a> = <code>Dither.DIFFUSION</code> .
<b>transparency</b>	boolean	Read-write. True to preserve transparent areas of the image during conversion to GIF format.
<b>typename</b>	string	Read-only. The class name of the referenced <code>GIFSaveOptions</code> object.

## GrayColor

Defines a gray color, used in the [SolidColor](#) object.

See also [CMYKColor](#), [HSBColor](#), [LabColor](#), [NoColor](#), [RGBColor](#)

### Properties

Property	Value type	What it is
<code>gray</code>	number [0.0..100.0]	Read-write. The gray value (default: 0.0).
<code>typename</code>	string	Read-only. The class name of the referenced <code>grayColor</code> object.

# Guide

## Properties

Property	Value type	What it is
<code>direction</code>	<a href="#">Direction</a>	Read-write. Indicates whether the guide is vertical or horizontal.
<code>coordinate</code>	<a href="#">UnitValue</a>	Read-write. Location of the guide from origin of image.

## Guides

The collection of open [Guide](#) objects.

Access this list through the [Document.guides](#) collection property, which is available through the `activeDocument` object. For example, the following adds a new guide to the collection:

```
activeDocument.guides.add (Direction.HORIZONTAL,UnitValue(20,20))
```

## Properties

Property	Value type	What it is
<code>length</code>	number	Read-only. The number of elements in the <code>guides</code> collection.
<code>parent</code>	<a href="#">Document</a>	Read-only. The containing document.
<code>typename</code>	string	Read-only. The class name of the referenced <code>guides</code> object.

## Methods

Method	Parameter type	Returns	What it does
<code>add</code> ( <code>direction</code> , <code>coordinate</code> )	<a href="#">Direction</a> <a href="#">UnitValue</a>	<a href="#">Guide</a>	Creates a new guide object and adds it to this collection.
<code>getByName</code> ( <code>name</code> )	string	<a href="#">Guide</a>	Gets the first element in the <code>guides</code> collection with the provided name

## HistoryState

A version of the document stored automatically (and added to the [HistoryStates](#) collection), which preserves the document's state, each time the document is changed.

Access through [Document.historyStates](#) collection. You can access a state in the list by name. For example, this assigns a property value in the state object named "AddLayerMask":

```
var stateRef = app.activeDocument.historyState.getByName("AddLayerMask");
stateRef.snapshot = true;
```

### Properties

Property	Value type	What it is
<b>name</b>	string	Read-only. The <code>HistoryState</code> object's name.
<b>parent</b>	<a href="#">Document</a>	Read-only. The containing document.
<b>snapshot</b>	boolean	Read-only. True if the history state is a snapshot.
<b>typename</b>	string	Read-only. The class name of the referenced <code>HistoryState</code> object.



# HistoryStates

The collection of [Guide](#) objects in the document.

Access through [Document.historyStates](#) collection property. For example, this accesses one of the states in the collection by index:

```
myState = app.activeDocument.historyStates[7];
```

## Properties

Property	Value type	What it is
<b>length</b>	number	Read-only. The number of elements in the <code>HistoryStates</code> collection.
<b>parent</b>	<a href="#">Document</a>	Read-only. The containing document.
<b>typename</b>	string	Read-only. The class name of the referenced <code>HistoryStates</code> object.

## Methods

Method	Parameter type	Returns	What it does
<b>getByName</b> (name)	string	<a href="#">Guide</a>	Get the first element in the <code>HistoryStates</code> collection with the provided name.

## HSBColor

Defines an HSB color, used in the [SolidColor](#) object.

See also [CMYKColor](#), [GrayColor](#), [LabColor](#), [NoColor](#), [RGBColor](#)

### Properties

Property	Value type	What it is
<b>brightness</b>	number [0.0..100.0]	Read-write. The brightness value.
<b>hue</b>	number [0.0..360.0]	Read-write. The hue value.
<b>saturation</b>	number [0.0..100.0]	Read-write. The saturation value.
<b>typename</b>	string	Read-only. The class name of the referenced <code>HSBColor</code> object.

# IndexedConversionOptions

Options for converting an RGB image to an indexed color model using [Document.changeMode\(\)](#).

## Properties

Property	Value type	What it is
<b>colors</b>	number	Read-write. The number of palette colors.  Valid only when <a href="#">palette</a> = <code>Palette.LOCALADAPTIVE</code> , <code>LOCALPERCEPTUAL</code> , <code>LOCALSELECTIVE</code> , <code>MACOSPALETTE</code> , <code>UNIFORM</code> , <code>WEBPALETTE</code> , or <code>WINDOWSPALETTE</code> .
<b>dither</b>	<a href="#">Dither</a>	Read-write. The dither type.
<b>ditherAmount</b>	number [1..100]	Read-write. The amount of dither.  Valid only when <a href="#">dither</a> = <code>Dither.diffusion</code> .
<b>forced</b>	<a href="#">ForcedColors</a>	Read-write. The type of colors to force into the color palette.
<b>matte</b>	<a href="#">MatteType</a>	Read-write. The color to use to fill anti-aliased edges adjacent to transparent areas of the image (default: <code>MatteType.WHITE</code> ).  When <a href="#">transparency</a> = <code>false</code> , the matte color is applied to transparent areas.
<b>palette</b>	<a href="#">PaletteType</a>	Read-write. The palette type (default: <code>Palette.EXACT</code> ).
<b>preserveExactColors</b>	boolean	Read-write. True to protect colors in the image that contain entries in the color table from being dithered.  Valid only when <a href="#">dither</a> = <code>Dither.DIFFUSION</code> .
<b>transparency</b>	boolean	Read-write. True to preserve transparent areas of the image during conversion to GIF format.
<b>typename</b>	string	Read-only. The class name of the referenced <code>IndexedConversionOptions</code> object.

## JPEGSaveOptions

Options for saving a document in JPEG format using the [Document.saveAs\(\)](#) method.

### Properties

Property	Value type	What it is
<code>embedColorProfile</code>	boolean	Read-write. True to embed the color profile in the document.
<code>formatOptions</code>	<a href="#">FormatOptions</a>	Read-write. The download format to use (default: <code>FormatOptions.STANDARDBASELINE</code> ).
<code>matte</code>	<a href="#">MatteType</a>	Read-write. The color to use to fill anti-aliased edges adjacent to transparent areas of the image (default: <code>MatteType.WHITE</code> ).  When transparency is turned off for an image, the matte color is applied to transparent areas.
<code>quality</code>	number [0..12]	Read-write. The image quality setting to use; affects file size and compression (default: 3).
<code>scans</code>	number [3..5]	Read-write. The number of scans to make to incrementally display the image on the page (default: 3).  Valid only for when <a href="#">formatOptions</a> = <code>FormatOptions.PROGRESSIVE</code> .
<code>typename</code>	string	Read-only. The class name of the referenced <code>JPEGSaveOptions</code> object.

## LabColor

Defines an LAB color, used in the [SolidColor](#) object.

See also [CMYKColor](#), [GrayColor](#), [HSBColor](#), [NoColor](#), [RGBColor](#)

### Properties

Property	Value type	What it is
<b>a</b>	number [-128.0..127.0]	Read-write. The a-value.
<b>b</b>	number [-128.0..127.0]	Read-write. The b-value.
<b>l</b>	number [0.0..100.0]	Read-write. The L-value.
<b>typename</b>	string	Read-only. The class name of the referenced <code>LabColor</code> object.

## LayerComp

A snapshot of a state of the layers in a document, which can be used to view different page layouts or compositions.

Access through [Document.layerComps](#) collection. You can access a layer comp by its name. For example, this sets the `comment` property value for a `LayerComp` object named `myLayerComp`:

```
var layercompRef = app.activeDocument.layerComps.getByName("myLayerComp");
layercompRef.comment = "View from shoreline";
```

### Properties

Property	Value type	What it is
<code>appearance</code>	boolean	Read-write. True to use layer appearance (layer styles) settings.
<code>comment</code>	string	Read-write. A description of the layer comp.
<code>name</code>	string	Read-write. The name of the layer comp.
<code>parent</code>	<a href="#">Document</a>	Read-write. The containing document.
<code>position</code>	boolean	Read-write. True to use layer position.
<code>selected</code>	boolean	Read-only. True if the layer comp is currently selected.
<code>typename</code>	string	Read-only. The class name of the referenced <code>layerComp</code> object.
<code>visibility</code>	boolean	Read-write. True to use layer visibility settings .

### Methods

Method	Parameter type	Returns	What it does
<code>apply</code> ( )			Applies the layer comp to the document.
<code>recapture</code> ( )			Recaptures the current layer state(s) for this layer comp.
<code>remove</code> ( )			Deletes the <code>layerComp</code> object.
<code>resetfromComp</code> ( )			Resets the layer comp state to the document state.

# LayerComps

The collection of [LayerComp](#) objects in the document.

Access through the [Document.layerComps](#) collection property. For example:

```
app.activeDocument.layerComps.add("myLayerComp", "View from Shoreline",
    true, true, true);
```

## Properties

Property	Value type	What it is
<b>length</b>	number	Read-only. The number of elements in the <code>layerComps</code> collection.
<b>parent</b>	<a href="#">Document</a>	Read-only. The containing document.
<b>typename</b>	string	Read-only. The class name of the referenced <code>layerComps</code> object.

## Methods

Method	Parameter type	Returns	What it does
<b>add</b> (name, comment, appearance, position, visibility)	string string boolean boolean boolean	<a href="#">LayerComp</a>	Creates a new layer composition object and adds it to this collection.
<b>getByName</b> (name)	string	<a href="#">LayerComp</a>	Gets the first element in the collection with the provided name.
<b>removeAll</b> ( )			Removes all member objects from the <code>layerComps</code> collection.

## Layers

The collection of layer objects, including [ArtLayer](#) and [LayerSet](#) objects, in the document. Access through [Document.layers](#), or the [LayerSet.layers](#) collections properties.

For example, this uses the `length` property to count the number of `layer` objects in the active document, then displays the number on the screen:

```
var layerNum = app.activeDocument.layers.length
alert(layerNum)
```

## Properties

Property	Value type	What it is
<code>length</code>	number	Read-only. The number of elements in the <code>layers</code> collection.
<code>parent</code>	<a href="#">Document</a> or <a href="#">LayerSet</a>	Read-only. The containing document or layer set.
<code>typename</code>	string	Read-only. The class name of the referenced <code>layers</code> object.

## Methods

Method	Parameter type	Returns	What it does
<code>getByName</code> (name)	string	Layer	Gets the first element in the <code>layers</code> collection with the provided name.
<code>removeAll</code> ( )			Removes all layers from the collection.



## LayerSet

A group of layer objects, which can include [ArtLayer](#) objects and other (nested) `LayerSet` objects. A single command can manipulate all layers in the set.

Access top-level layers sets in a document through the [Document.layerSets](#) collection. You can access a layer set by name. For example, the following sets the `allLocked` value for "myLayerSet":

```
var layerSetRef = app.activeDocument.layerSets.getByName("myLayerSet");
layerSetRef.allLocked = true
```

Access nested layer sets through the [LayerSet.layerSets](#) collection in the parent set. For example:

```
app.activeDocument.layerSets[0].layerSets[0];
```

## Properties

Property	Value type	What it is
<code>allLocked</code>	boolean	Read-write. True if the contents in the layers in this set are not editable.
<code>artLayers</code>	<a href="#">ArtLayers</a>	Read-only. The art layers in this layer set.
<code>blendMode</code>	<a href="#">BlendMode</a>	Read-write. The blend mode to use for the layer set.
<code>bounds</code>	array of <a href="#">UnitValue</a>	Read-only. The bounding rectangle of the layer set.
<code>enabledChannels</code>	array of <a href="#">Channel</a>	Read-write. The channels enabled for the layer set; must be a list of component channels. See <a href="#">Channel.kind</a> .
<code>layers</code>	<a href="#">Layers</a>	Read-only. The layers in this layer set.
<code>layerSets</code>	<a href="#">LayerSets</a>	Read-only. Nested layer sets contained within this layer set.
<code>linkedLayers</code>	array of <a href="#">ArtLayer</a> and/or <a href="#">LayerSet</a>	Read-only. The layers linked to this <code>layerSet</code> object.
<code>name</code>	string	Read-write. The name of this layer set.
<code>opacity</code>	number [0.0..100.0]	Read-write. The master opacity of the set.
<code>parent</code>	<a href="#">Document</a> or <a href="#">LayerSet</a>	Read-only. The containing document or layer set.
<code>typename</code>	string	Read-only. The class name of the referenced <code>LayerSet</code> object.
<code>visible</code>	boolean	Read-write. True if the set is visible.

## Methods

Method	Parameter type	Returns	What it does
<b>duplicate</b> ([relativeObject]  [, insertionLocation])	<a href="#">ArtLayer</a> or <a href="#">LayerSet</a> <a href="#">ElementPlacement</a>	<a href="#">LayerSet</a>	Creates a duplicate of the object.
<b>link</b> (with)	<a href="#">ArtLayer</a> or <a href="#">LayerSet</a>		Links the layer set with another layer.
<b>merge</b> ( )		<a href="#">ArtLayer</a>	Merges the layerset; returns a reference to the art layer created by this method.
<b>move</b> (relativeObject,  insertionLocation)	<a href="#">ArtLayer</a> or <a href="#">LayerSet</a> <a href="#">ElementPlacement</a>		Moves the object.
<b>remove</b> ( )			Deletes the object.
<b>resize</b> ([horizontal] [, vertical] [, anchor])	number number <a href="#">AnchorPosition</a>		Resizes all layers in the layer set to to the specified dimensions (as a percentage of its current size) and places the layer set in the specified position.
<b>rotate</b> (angle [, anchor])	number <a href="#">AnchorPosition</a>		Rotates all layers in the layer set around the specified anchor point (default: <code>AnchorPosition.MIDDLECENTER</code> )
<b>translate</b> ([deltaX] [, deltaY])	<a href="#">UnitValue</a> <a href="#">UnitValue</a>		Moves the position relative to its current position.
<b>unlink</b> ( )			Unlinks the layer set.

## LayerSets

The collection of [LayerSet](#) objects in the document.

Access the top-level layer sets in a document through the [Document.layerSets](#) collection property. For example:

```
var layerSetRef = app.activeDocument.layerSets.add()
```

Access the nested layer sets through the [LayerSet.layerSets](#) collection property in the parent set. For example:

```
var layerSetRef = app.activeDocument.layerSets.getByName("myParentSet");
var childSet = layerSetRef.layerSets.getByName("myChildSet");
```

## Properties

Property	Value type	What it is
<b>length</b>	number	Read-only. The number of elements in the <code>LayerSets</code> collection.
<b>parent</b>	<a href="#">Document</a> or <a href="#">LayerSet</a>	Read-only. The containing document or layer set.
<b>typename</b>	string	Read-only. The class name of the referenced <code>layerSets</code> object.

## Methods

Method	Parameter type	Returns	What it does
<b>add</b> ( )		<a href="#">LayerSet</a>	Creates a new layer set object and adds it to the collection.
<b>getByName</b> (name)	string	<a href="#">LayerSet</a>	Gets the first element in the collection with the provided name.
<b>removeAll</b> ( )			Removes all member layer sets, and any layers or layer sets they contain, from the document.

## LayerSets sample script

The following script creates three layer sets, then nests a second layer set in each layer set, and then creates a text layer in each nested set that displays the text "Layer in *n* Set Inside *n* Set", where *n* represents the ordinal number of the set (first, second, or third).

**Note:** This script uses the ExtendScript `$` debugging object. For further details, see the *JavaScript Tools Guide*.

### LayerSets.jsx

```
$.level = 1

//close all open documents
while (app.documents.length) {
```

```
    app.activeDocument.close()
}

// create a working document
var docRef = app.documents.add()

// create an array to hold the layer sets
var myLayerSets = new Array()

// Create an array to hold the text
var textArray = Array("First", "Second", "Third")

//Create an indexer variable
var i = 0

// Create three layer sets at the top level
for (i = 0; i < 3; i++) {
    myLayerSets[i] = new Array()
    myLayerSets[i][0] = docRef.layerSets.add()
}

// Rearrange the layer sets with the first one on top, second next, etc.
myLayerSets[1][0].moveAfter(myLayerSets[0][0])
myLayerSets[2][0].moveAfter(myLayerSets[1][0])

// Create a layer set inside each layer set
for (i = 0; i < 3; i++) {
    myLayerSets[i][0].name = textArray[i] + " Set"
    myLayerSets[i][1] = myLayerSets[i][0].layerSets.add()
    myLayerSets[i][1].name = "Inside " + textArray[i] + " Set"
}

// Create an array to hold the layers
var myLayers = new Array()

// Create a text layer with a description inside each layer set
for (i = 0; i < 3; i++) {
    myLayers[i] = myLayerSets[i][1].artLayers.add()
    myLayers[i].kind = LayerKind.TEXT
    myLayers[i].textItem.contents = "Layer in " + textArray[i] + " Set Inside "
        + textArray[i] + " Set"
    myLayers[i].textItem.position = Array(app.activeDocument.width * i * 0.33,
        app.activeDocument.height * (i + 1) * 0.25)
    myLayers[i].textItem.size = 12
}
```

## MeasurementLog

The measurement log for the application. Access through the [Application.measurementLog](#) property.

**Note:** This feature is available in the Extended Version only.

### Methods

Method	Parameter type	Returns	What it does
<b>exportMeasurements</b> ([file] [, range] [, dataPoints])	<a href="#">File</a> <a href="#">MeasurementRange</a> array of string		Export measurement to a file.
<b>deleteMeasurements</b> ([range])	<a href="#">MeasurementRange</a>		Delete measurements from the log.

## MeasurementScale

The measurement scale for the document. Access through the [Document.measurementScale](#) property. For example:

```
app.activeDocument.measurementScale.pixelLength = 25
```

**Note:** This feature is available in the Extended Version only.

### Properties

Property	Value type	What it is
<code>pixelLength</code>	number	Read-write. The length in pixels this scale equates to.
<code>logicalLength</code>	number	Read-write. The logical length this scale equates to.
<code>logicalUnits</code>	string	Read-write. The logical units for this scale.

## NoColor

Represents a missing color object, used in the [SolidColor](#) object.

See also [CMYKColor](#), [GrayColor](#), [HSBColor](#), [LabColor](#), [RGBColor](#)

### Properties

Property	Value type	What it is
<code>typename</code>	string	Read-only. The class name of the referenced <code>noColor</code> object.

## Notifier

An event-handler object that tells a script to execute specified code when a specified event occurs. Notifiers must be enabled using the [Application.notifiersEnabled](#) property.

Access through the [Application.notifiers](#) collection.

**Note:** Events that occur within scripts do not generally trigger notifiers, because they occur inside a "play script" event.

## Properties

Property	Value type	What it is
<code>event</code>	string	Read-only. The event identifier, a four-character code or a unique string.  For a list of four-character codes, see <a href="#">Appendix A: Event ID Codes</a> .
<code>eventClass</code>	string	Read-only. The class identifier, a four-character code or a unique string.  When an event applies to multiple types of objects, use this property to distinguish which object this notifier applies to. For example, the Make event ("Mk ") can apply to documents ("Dcmn"), channels ("Chnl") and other objects.
<code>eventFile</code>	<a href="#">File</a>	Read-only. The path to the file to execute when the event occurs and activates the notifier.
<code>parent</code>	<a href="#">Application</a>	Read-only. The containing application.
<code>typename</code>	string	Read-only. The class name of the referenced object.

## Methods

Method	Parameter type	Returns	What it does
<code>remove</code> ( )			Deletes this object.  You can also remove a <code>Notifier</code> object from the Script Events Manager drop-down list by deleting the file named <code>Script Events Manager.xml</code> from the Photoshop preferences folder. See Adobe Photoshop CC 2014 help for more information.



## Notifiers

The collection of [Notifier](#) objects in the document. Access through the [Application.notifiers](#) collection property. For example:

```
var notRef = app.notifiers.add("OnClickGoButton", eventFile)
```

Notifiers must be enabled using the [Application.notifiersEnabled](#) property.

## Properties

Property	Value type	What it is
<code>length</code>	number	Read-only. The number of elements in the <code>notifiers</code> collection.
<code>parent</code>	<a href="#">Application</a>	Read-only. The <code>notifiers</code> object's container
<code>typename</code>	string	Read-only. The class name of the referenced <code>notifiers</code> object.

## Methods

Method	Parameter type	Returns	What it does
<b>add</b> (event, eventFile [, eventClass])	string <a href="#">File</a> string	<a href="#">Notifier</a>	<p>Creates a notifier object and adds it to this collection.</p> <p><code>event</code> defines the class ID of the event: use a 4-character code or a unique string. See <a href="#">Appendix A: Event ID Codes</a>.</p> <p><code>eventFile</code> defines the script file that executes when the event occurs.</p> <p>When an event applies to multiple types of objects, use the <code>eventClass</code> (a 4-character ID or unique string) to distinguish which object this <code>Notifier</code> applies to. For example, the Make event ("Mk ") applies to documents ("Dcmn"), channels ("Chnl") and other objects.</p> <p><b>Tip:</b> When specifying an event or event class with a 4-character ID code, omit the single quotes in your code.</p>
<b>removeAll</b> ()			<p>Removes all member objects from the <code>notifiers</code> collection.</p> <p>You can also remove a <code>notifier</code> object from the Script Events Manager drop-down list by deleting the file named <code>Script Events Manager.xml</code> from the Photoshop preferences folder. See Adobe Photoshop CC 2014 help for more information.</p>

## PathItem

A path or drawing object, such as the outline of a shape or a straight or curved line, which contains sub paths that define its geometry.

Access through the collection in the [Document.pathItems](#) property. For example, this selects a named path item:

```
var currentPathItem = app.activeDocument.pathItems.getByName("myPath");
currentPathItem.select();
```

Create these objects by passing a set of [SubPathInfo](#) objects to the [PathItems.add\(\)](#) method. This method creates a [SubPathItem](#) object for each [SubPathInfo](#) object, and creates and returns a new [PathItem](#) object for the path represented by all of the subpaths.

## Properties

Property	Value type	What it is
<b>kind</b>	<a href="#">PathKind</a>	Read-write. The type.
<b>name</b>	string	Read-write. The name.
<b>parent</b>	<a href="#">Document</a>	Read-only. The containing document.
<b>subPathItems</b>	<a href="#">SubPathItems</a>	Read-only. The contained sub-path objects.
<b>typename</b>	string	Read-only. The class name of the referenced <code>pathItem</code> object.

## Methods

Method	Parameter type	Returns	What it does
<b>deselect</b> ( )			Deselects this <code>pathItem</code> object.
<b>duplicate</b> (name)	string		Duplicates this <code>pathItem</code> object with the new name.
<b>fillPath</b> ([fillColor] [, mode] [, opacity] [, preserveTransparency] [, feather] [, wholePath] [, antiAlias])	<a href="#">SolidColor</a> <a href="#">ColorBlendMode</a> number [0..100] boolean number [0.0..250.0] boolean boolean		Fills the area enclosed by this path.  <code>opacity</code> is a percentage.  <code>feather</code> is in pixels.  If <code>wholePath</code> is true, all subpaths are used when doing the fill (default: true).

Method	Parameter type	Returns	What it does
<b>makeClippingPath</b> ([flatness])	number [0.2..100]		Makes this the clipping path for this document. <i>flatness</i> tells the PostScript printer how to approximate curves in the path.
<b>makeSelection</b> ([feather] [, antiAlias] [, operation])	number [0.0..250.0] boolean <a href="#">SelectionType</a>		Makes a <a href="#">Selection</a> object whose border is this path. <i>feather</i> is in pixels.
<b>remove</b> ( )			Deletes this object.
<b>select</b> ( )			Makes this the active or selected <code>PathItem</code> object.
<b>strokePath</b> ([tool] [, simulatePressure])	<a href="#">ToolType</a> boolean		Strokes the path with the specified tool.

## PathItem sample script

The following creates a path in three segments: two diagonal lines that form a V, and a curved line above the V that makes it look like a 2D ice cream cone.

### Paths.jsx

```
// Save the current preferences
var startRulerUnits = app.preferences.rulerUnits
var startTypeUnits = app.preferences.typeUnits
var startDisplayDialogs = app.displayDialogs

// Set Adobe Photoshop CC 2014 to use pixels and display no dialogs
app.preferences.rulerUnits = Units.PIXELS
app.preferences.typeUnits = TypeUnits.PIXELS
app.displayDialogs = DialogModes.NO

// first close all the open documents
while (app.documents.length) {
    app.activeDocument.close()
}

// create a document to work with
var docRef = app.documents.add(5000, 7000, 72, "Simple Line")

//line 1--it's a straight line so the coordinates for anchor, left, and right
//for each point have the same coordinates
var lineArray = new Array()
    lineArray[0] = new PathPointInfo
    lineArray[0].kind = PointKind.CORNERPOINT
    lineArray[0].anchor = Array(100, 100)
```

```
    lineArray[0].leftDirection = lineArray[0].anchor
    lineArray[0].rightDirection = lineArray[0].anchor

    lineArray[1] = new PathPointInfo
    lineArray[1].kind = PointKind.CORNERPOINT
    lineArray[1].anchor = Array(150, 200)
    lineArray[1].leftDirection = lineArray[1].anchor
    lineArray[1].rightDirection = lineArray[1].anchor

var lineSubPathArray = new Array()
    lineSubPathArray[0] = new SubPathInfo()
    lineSubPathArray[0].operation = ShapeOperation.SHAPEXOR
    lineSubPathArray[0].closed = false
    lineSubPathArray[0].entireSubPath = lineArray

// line 2
var lineArray2 = new Array()
    lineArray2[0] = new PathPointInfo
    lineArray2[0].kind = PointKind.CORNERPOINT
    lineArray2[0].anchor = Array(150, 200)
    lineArray2[0].leftDirection = lineArray2[0].anchor
    lineArray2[0].rightDirection = lineArray2[0].anchor

    lineArray2[1] = new PathPointInfo
    lineArray2[1].kind = PointKind.CORNERPOINT
    lineArray2[1].anchor = Array(200, 100)
    lineArray2[1].leftDirection = lineArray2[1].anchor
    lineArray2[1].rightDirection = lineArray2[1].anchor

    lineSubPathArray[1] = new SubPathInfo()
    lineSubPathArray[1].operation = ShapeOperation.SHAPEXOR
    lineSubPathArray[1].closed = false
    lineSubPathArray[1].entireSubPath = lineArray2

//ice cream curve
//it's a curved line, so there are 3 points, not 2
//coordinates for the middle point (lineArray3[1]) are different.
//The left direction is positioned "above" the anchor on the screen.
//The right direction is positioned "below" the anchor
//You can change the coordinates for these points to see
//how the curve works...
var lineArray3 = new Array()
    lineArray3[0] = new PathPointInfo
    lineArray3[0].kind = PointKind.CORNERPOINT
    lineArray3[0].anchor = Array(200, 100)
    lineArray3[0].leftDirection = lineArray3[0].anchor
    lineArray3[0].rightDirection = lineArray3[0].anchor

    lineArray3[1] = new PathPointInfo
    lineArray3[1].kind = PointKind.CORNERPOINT
    lineArray3[1].anchor = Array(150, 50)
    lineArray3[1].leftDirection = Array(100, 50)
    lineArray3[1].rightDirection = Array(200, 50)

    lineArray3[2] = new PathPointInfo
    lineArray3[2].kind = PointKind.CORNERPOINT
    lineArray3[2].anchor = Array(100, 100)
    lineArray3[2].leftDirection = lineArray3[2].anchor
    lineArray3[2].rightDirection = lineArray3[2].anchor
```

```
    lineSubPathArray[2] = new SubPathInfo()
    lineSubPathArray[2].operation = ShapeOperation.SHAPEXOR
    lineSubPathArray[2].closed = false
    lineSubPathArray[2].entireSubPath = lineArray3

//create the path item
var myPathItem = docRef.pathItems.add("A Line", lineSubPathArray)

// stroke it so we can see something
myPathItem.strokePath(ToolType.BRUSH)

// Reset the application preferences
preferences.rulerUnits = startRulerUnits
preferences.typeUnits = startTypeUnits
displayDialogs = startDisplayDialogs
```

## PathItems

The collection of [PathItem](#) objects in a document.

Access through the [Document.pathItems](#) collection property. For example, this creates a new path item using a previously-defined set of subpaths:

```
app.activeDocument.pathItems.add("myPath", lineSubPathInfoArray);
```

## Properties

Property	Value type	What it is
<b>length</b>	number	Read-only. The number of <code>pathItem</code> objects in the <code>pathItems</code> collection.
<b>parent</b>	<a href="#">Document</a>	Read-only. The <code>pathItems</code> object's container.
<b>typename</b>	string	Read-only. The class name of the referenced <code>pathItems</code> object.

## Methods

Method	Parameter type	Returns	What it does
<b>add</b> (name, entirePath)	string array of <a href="#">SubPathInfo</a>	<a href="#">PathItem</a>	Creates a new path item object and adds it to this collection.  A new <a href="#">SubPathItem</a> object is created for each <code>SubPathInfo</code> object provided in <code>entirePath</code> , and those <code>SubPathItem</code> objects are added to the <a href="#">subPathItems</a> collection of the returned <a href="#">PathItem</a> .
<b>getByName</b> (name)	string	<a href="#">PathItem</a>	Get the first element in the <code>pathItems</code> collection with the provided name.
<b>removeAll</b> ( )			Removes all <code>pathItem</code> objects from the <code>pathItems</code> collection.

## PathPoint

Represents the anchor and control-handle endpoints for a path segment. Each point (the anchor point, left-direction point, and right-direction point) is an array containing X and Y position coordinates.

- Use the `PathPoint` object to retrieve information about the points that describe existing path segments. The properties are read-only. Access `PathPoint` objects through the `SubPathItem.pathPoints` property.
- Use `PathPointInfo` with `PathItems.add()` to create path points. The properties are writeable.

For paths that are straight segments (not curved), the coordinates of all three points are the same. For curved segments, the the coordinates are different. The difference between the anchor point and the left or right direction points determines the arc of the curve. You use the left direction point to bend the curve "outward" or make it convex; you use the right direction point to bend the curve "inward" or make it concave.

### Properties

Property	Value type	What it is
<code>anchor</code>	array of number	Read-only. The X and Y coordinates of the anchor point of the curve.
<code>kind</code>	<a href="#">PointKind</a>	Read-only. The role (corner or smooth) this point plays in the containing path segment.
<code>leftDirection</code>	array of number	Read-only. The location of the left-direction endpoint ('in' position).
<code>parent</code>	<a href="#">SubPathItem</a>	Read-only. The containing subpath object.
<code>rightDirection</code>	array of number	Read-only. The location of the right-direction endpoint ('out' position).
<code>typename</code>	string	Read-only. The class name of the referenced <code>PathPoint</code> object.

## PathPointInfo

Used to create a [PathPoint](#), which represents the anchor and control-handle endpoints for a path segment. Each point (the anchor point, left-direction point, and right-direction point) is an array containing X and Y position coordinates.

- Use the JavaScript `new` operator to create these objects, and store them in the [SubPathInfo.entireSubPath](#) property before using that object to create a path item with [PathItems.add\(\)](#).  
See the [PathPointInfo sample script](#) below.
- The resulting [SubPathItem](#) objects contain the resulting [PathPoint](#) objects. Use the [PathPoint](#) object to retrieve information about the points that describe existing path segments. The properties are read-only.

For paths that are straight segments (not curved), the coordinates of all three points are the same. For curved segments, the the coordinates are different. The difference between the anchor point and the left or right direction points determines the arc of the curve. You use the left direction point to bend the curve "outward" or make it convex; you use the right direction point to bend the curve "inward" or make it concave.

## Properties

Property	Value type	What it is
<b>anchor</b>	array of number	Read-write. The X and Y coordinates of the anchor point of the curve.
<b>kind</b>	<a href="#">PointKind</a>	Read-write. The role (corner or smooth) this point plays in the containing path segment.
<b>leftDirection</b>	array of number	Read-write. The location of the left-direction endpoint ('in' position).
<b>rightDirection</b>	array of number	Read-write. The location of the right-direction endpoint ('out' position).
<b>typename</b>	string	Read-only. The class name of the referenced <code>PathPointInfo</code> object.

## PathPointInfo sample script

```
function drawLine(doc, start, stop) {
    var startPoint = new PathPointInfo();
    startPoint.anchor = start;
    startPoint.leftDirection = start;
    startPoint.rightDirection = start;
    startPoint.kind = PointKind.CORNERPOINT;

    var stopPoint = new PathPointInfo();
    stopPoint.anchor = stop;
    stopPoint.leftDirection = stop;
    stopPoint.rightDirection = stop;
    stopPoint.kind = PointKind.CORNERPOINT;
}
```



```
var spi = new SubPathInfo();
spi.closed = false;
spi.operation = ShapeOperation.SHAPEXOR;
spi.entireSubPath = [startPoint, stopPoint];

var line = doc.pathItems.add("Line", [spi]);
line.strokePath(ToolType.PENCIL);
line.remove();
};

drawLine(app.activeDocument, [100,100], [200,200]);
```

## PathPoints

A collection of [PathPoint](#) objects that define a subpath, kept in the [SubPathItem.pathPoints](#) property.

### Properties

Property	Value type	What it is
<code>length</code>	number	Read-only. The number of elements in the collection.
<code>parent</code>	<a href="#">SubPathItem</a>	Read-only. The containing subpath object.
<code>typename</code>	string	Read-only. The class name of the referenced <code>PathPoints</code> object.

## PDFOpenOptions

Options for opening a document in generic Adobe PDF format using the [Application.open\(\)](#) method.

### Properties

Property	Value type	What it is
<b>antiAlias</b>	boolean	Read-write. True to use antialias.
<b>bitsPerChannel</b>	<a href="#">BitsPerChannelType</a>	Read-write. The number of bits per channel.
<b>constrainProportions</b>	boolean	DEPRECATED for Adobe Photoshop CC 2014.
<b>cropPage</b>	<a href="#">CropToType</a>	Read-write. The method of cropping to use.
<b>height</b>	<a href="#">UnitValue</a>	DEPRECATED for Adobe Photoshop CC 2014.
<b>mode</b>	<a href="#">OpenDocumentMode</a>	Read-write. The color model to use.
<b>name</b>	string	Read-write. The name of the object.
<b>page</b>	number	Read-write. The page or image to which to open the document, depending on the value of <a href="#">usePageNumber</a> .
<b>resolution</b>	number	Read-write. The resolution of the document (in pixels per inch).
<b>suppressWarnings</b>	boolean	Read-write. True to suppress warnings when opening the document.
<b>typename</b>	string	Read-only. The class name of the referenced <code>PDFOpenOptions</code> object.
<b>usePageNumber</b>	boolean	Read-write. When true, the <a href="#">page</a> property refers to a page number; when false, it refers to an image number.
<b>width</b>	<a href="#">UnitValue</a>	DEPRECATED for Adobe Photoshop CC 2014.

## PDFSaveOptions

Options for saving a document in Adobe PDF format using the [Document.saveAs\(\)](#) method.

### Properties

Property	Value type	What it is
<b>alphaChannels</b>	boolean	Read-write. True to save the alpha channels with the file.
<b>annotations</b>	boolean	Read-write. True to save comments with the file.
<b>colorConversion</b>	boolean	Read-write. True to convert the color profile to a destination profile.
<b>convertToEightBit</b>	boolean	Read-write. True to convert a 16-bit image to 8-bit for better compatibility with other applications.
<b>description</b>	string	Read-write. Description of the save options to use.
<b>destinationProfile</b>	string	Read-write. Description of the final RGB or CMYK output device, such as a monitor or a press standard.
<b>downgradeColorProfile</b>	boolean	DEPRECATED for Adobe Photoshop CC 2014.
<b>downSample</b>	<a href="#">PDFResample</a>	Read-write. The down sample method to use.
<b>downSampleSize</b>	number	Read-write. The size to downsample images if they exceed the limit in pixels per inch.
<b>downSampleSizeLimit</b>	number	Read-write. Limits downsampling or subsampling to images that exceed this value in pixels per inch.
<b>embedColorProfile</b>	boolean	Read-write. True to embed the color profile in the document.
<b>embedFonts</b>	boolean	DEPRECATED for Adobe Photoshop CC 2014.
<b>embedThumbnail</b>	boolean	Read-write. True to include a small preview image in Adobe PDF files.
<b>encoding</b>	<a href="#">PDFEncoding</a>	Read-write. The type of compression to use (default: <code>PDFEncoding.PDFZIP</code> ).
<b>interpolation</b>	boolean	DEPRECATED for Adobe Photoshop CC 2014.

Property	Value type	What it is (Continued)
<code>jpegQuality</code>	number [0..12]	Read-write. The quality of the produced image, which is inversely proportionate to the compression amount.  Valid only when <code>encoding</code> = <code>PDFEncoding.JPEG</code> .
<code>layers</code>	boolean	Read-write. True to save the document's layers.
<code>optimizeForWeb</code>	boolean	Read-write. True to improve performance of PDF files on Web servers.
<code>outputCondition</code>	string	Read-write. An optional comment field for inserting descriptions of the output condition. The text is stored in the PDF/X file.
<code>outputConditionID</code>	string	Read-write. Identifier for the output condition.
<code>PDFCompatibility</code>	<a href="#">PDFCompatibility</a>	Read-write. The PDF version to make the document compatible with.
<code>PDFStandard</code>	<a href="#">PDFStandard</a>	Read-write. The PDF standard to make the document compatible with.
<code>preserveEditing</code>	boolean	Read-write. True to reopen the PDF in Adobe Photoshop CC 2014 with native Photoshop data intact.
<code>presetFile</code>	string	Read-write. The preset file to use for settings.  <b>Note:</b> This option overrides other settings.
<code>profileInclusionPolicy</code>	boolean	Read-write. True to show which profiles to include.
<code>registryName</code>	string	Read-write. URL where the output condition is registered.
<code>spotColors</code>	boolean	Read-write. True to save spot colors.
<code>tileSize</code>	number	Read-write. Compression option.  Valid only when <code>encoding</code> = <code>PDFEncoding.JPEG2000</code> .
<code>transparency</code>	boolean	DEPRECATED for Adobe Photoshop CC 2014.
<code>typename</code>	string	Read-only. The class name of the referenced <code>PDFSaveOptions</code> object.
<code>useOutlines</code>	boolean	DEPRECATED for Adobe Photoshop CC 2014.

<b>Property</b>	<b>Value type</b>	<b>What it is (Continued)</b>
<b>vectorData</b>	boolean	DEPRECATED for Adobe Photoshop CC 2014.
<b>view</b>	boolean	Read-write. True to open the saved PDF in Adobe Acrobat.

## PhotoCDOpenOptions

**DEPRECATED** in Adobe Photoshop CC 2014. Kodak PhotoCD is now found in the Goodies folder on the Adobe Photoshop CC 2014 Install DVD.

Options for opening a document in Kodak Photo CD (PCD) format (including high-resolution files from Pro Photo CD discs) using the [Application.open\(\)](#) method.

### Properties

Property	Value type	What it is
<code>colorProfileName</code>	string	Read-write. The profile to use when reading the image.
<code>colorSpace</code>	<a href="#">PhotoCDColorSpace</a>	Read-write. The colorspace for the image.
<code>orientation</code>	<a href="#">Orientation</a>	Read-write. The image orientation.
<code>pixelSize</code>	<a href="#">PhotoCDSize</a>	Read-write. The image dimensions.
<code>resolution</code>	number	Read-write. The image resolution (in pixels per inch).
<code>typename</code>	string	Read-only. The class name of the referenced <code>photoCDOpenOptions</code> object.

# PhotoshopSaveOptions

Options for saving a document in PSD format using the [Document.saveAs\(\)](#) method.

## Properties

Property	Value type	What it is
<code>alphaChannels</code>	boolean	Read-write. True to save the alpha channels.
<code>annotations</code>	boolean	Read-write. True to save the annotations.
<code>embedColorProfile</code>	boolean	Read-write. True to embed the color profile in the document.
<code>layers</code>	boolean	Read-write. True to preserve the layers.
<code>spotColors</code>	boolean	Read-write. True to save the spot colors.
<code>typename</code>	string	Read-only. The class name of the referenced <code>photoshopSaveOptions</code> object.



## PICTFileSaveOptions

Options for saving a document in PICT format using the [Document.saveAs\(\)](#) method.

### Properties

Property	Value type	What it is
<code>alphaChannels</code>	boolean	Read-write. True to save the alpha channels.
<code>compression</code>	<a href="#">PICTCompression</a>	Read-write. The type of compression to use (default: <code>PICTCompression.NONE</code> ).
<code>embedColorProfile</code>	boolean	Read-write. True to embed the color profile in the document.
<code>resolution</code>	<a href="#">PICTBitsPerPixels</a>	Read-write. The number of bits per pixel.
<code>typename</code>	string	Read-only. The class name of the referenced <code>PICTFileSaveOptions</code> object.

## PICTResourceSaveOptions

Options for saving a document as a PICT Resource file using the [Document.saveAs\(\)](#) method.

### Properties

Property	Value type	What it is
<code>alphaChannels</code>	boolean	Read-write. True to save the alpha channels.
<code>compression</code>	<a href="#">PICTCompression</a>	Read-write. The type of compression to use (default: <code>PICTCompression.NONE</code> ).
<code>embedColorProfile</code>	boolean	Read-write. True to embed the color profile in the document.
<code>name</code>	string	Read-write. The name of the PICT resource.
<code>resolution</code>	<a href="#">PICTBitsPerPixels</a>	Read-write. The number of bits per pixel.
<code>resourceID</code>	number	Read-write. The ID of the PICT resource (default: 128).
<code>typename</code>	string	Read-only. The class name of the referenced <code>PICTResourceSaveOptions</code> object.

# PicturePackageOptions

Options for a picture package created with [Application.makePicturePackage\(\)](#).

## Properties

Property	Value type	What it is
<b>content</b>	<a href="#">PicturePackageTextType</a>	Read-write. The content information (default: <code>PicturePackageTextType.NONE</code> ).
<b>flatten</b>	boolean	Read-write. True if all layers in the final document are flattened (default: <code>true</code> ).
<b>font</b>	<a href="#">GalleryFontType</a>	Read-write. The font used for security text (default: <code>GalleryFontType.ARIAL</code> ).
<b>fontSize</b>	number	Read-write. The font size used for security text (default: <code>12</code> ).
<b>layout</b>	string	Read-write. The layout to use to generate the picture package (default: <code>" (2) 5x7"</code> ).
<b>mode</b>	<a href="#">NewDocumentMode</a>	Read-write. Read-write. The color profile to use as the document mode (default: <code>NewDocumentMode.RGB</code> ).
<b>opacity</b>	number	Read-write. The web page security opacity as a percent (default: <code>100</code> ).
<b>resolution</b>	number	Read-write. The resolution of the document in pixels per inch (default: <code>72 . 0</code> ).
<b>text</b>	string	Read-write. The picture package custom text. Valid only when <a href="#">content</a> = <code>PicturePackageType.USER</code> .
<b>textColor</b>	<a href="#">RGBColor</a>	Read-write. The color to use for security text.
<b>textPosition</b>	<a href="#">GallerySecurityTextPositionType</a>	Read-write. The security text position (default: <code>GallerySecurityTextPositionType.CENTERED</code> ).
<b>textRotate</b>	<a href="#">GallerySecurityTextRotateType</a>	Read-write. The orientation to use for security text (default: <code>GallerySecurityTextRotateType.ZERO</code> ).
<b>typename</b>	string	Read-only. The class name of the referenced <code>PicturePackageOptions</code> object.

## PixarSaveOptions

Options for saving a document in Pixar format using the [Document.saveAs\(\)](#) method.

### Properties

Property	Value type	What it is
<code>alphaChannels</code>	boolean	Read-write. True to save the alpha channels.
<code>typename</code>	string	Read-only. The class name of the referenced <code>PixarSaveOptions</code> object.

## PNGSaveOptions

Options for saving a document in PNG format using the [Document.saveAs\(\)](#) method.

### Properties

Property	Value type	What it is
<code>compression</code>	number [0..9]	Read-write. The compression value (default: 0).
<code>interlaced</code>	boolean	Read-write. True to interlace rows (default: <code>false</code> ).
<code>typename</code>	string	Read-only. The class name of the referenced <code>PNGSaveOptions</code> object.

## Preferences

Represents application preferences for Photoshop. Access this object through the [Application.preferences](#) property. For example:

```
app.preferences.rulerUnits = Units.PIXELS
app.preferences.typeUnits = TypeUnits.PIXELS
```

Setting values in this object is equivalent to selecting **Edit > Preferences** (in Windows) or **Photoshop > Preferences** (in Mac OS) in the Adobe Photoshop CC 2014 application. For explanations of individual settings, see Adobe Photoshop CC 2014 Help.

## Properties

Property	Value type	What it is
<code>additionalPluginFolder</code>	<a href="#">File</a>	Read-write. The path to an additional plug-in folder. Valid only when <a href="#">useAdditionalPluginFolder</a> = true.
<code>appendExtension</code>	<a href="#">SaveBehavior</a>	Read-write. The preferred policy for writing file extensions in Windows.
<code>askBeforeSavingLayeredTIFF</code>	boolean	Read-write. True to ask the user to verify layer preservation options when saving a file in TIFF format.
<code>autoUpdateOpenDocuments</code>	boolean	Read-write. True to automatically update open documents.
<code>beepWhenDone</code>	boolean	Read-write. True to beep when a process finishes.
<code>colorChannelsInColor</code>	boolean	Read-write. True to display component channels in the Channels palette in color.
<code>colorPicker</code>	<a href="#">ColorPicker</a>	Read-write. The preferred color selection tool.
<code>columnGutter</code>	number [0.1..600.0]	Read-write. The width of the column gutters (in points).
<code>columnWidth</code>	number [0.1..600.0]	Read-write. Column width (in points)
<code>createFirstSnapshot</code>	boolean	Read-write. True to automatically make the first snapshot when a new document is created.
<code>dynamicColorSliders</code>	boolean	Read-write. True if dynamic color sliders appear in the Color palette.
<code>editLogItems</code>	<a href="#">EditLogItemsType</a>	Read-write. The preferred level of detail in the history log. Valid only when <a href="#">useHistoryLog</a> = true.

Property	Value type	What it is (Continued)
<code>exportClipboard</code>	boolean	Read-write. True to retain Adobe Photoshop CC 2014 contents on the clipboard after you exit the application.
<code>fontPreviewSize</code>	<a href="#">FontPreviewType</a>	Read-write. The preferred type size to use for font previews in the type tool font menus.
<code>fullSizePreview</code>	boolean	Read-write. True to show image preview as a full size image, false to show thumbnail (in Mac OS only).
<code>gamutWarningOpacity</code>	number [0..100]	Read-write. Opacity value as a percentage.
<code>gridSize</code>	<a href="#">GridSize</a>	Read-write. The preferred size to use for squares in the grid.
<code>gridStyle</code>	<a href="#">GridLineStyle</a>	Read-write. The preferred formatting style for non-printing grid lines.
<code>gridSubDivisions</code>	number [1..100]	Read-write. Number of grid subdivisions.
<code>guideStyle</code>	<a href="#">GuideLineStyle</a>	Read-write. The preferred formatting style for non-printing guide lines.
<code>iconPreview</code>	boolean	Read-write. True to use icon previews (in Mac OS only).
<code>imageCacheLevels</code>	number [1..8]	Read-write. The number of images to hold in the cache.
<code>imagePreviews</code>	<a href="#">SaveBehavior</a>	Read-write. The preferred policy for writing image previews in Windows.
<code>interpolation</code>	<a href="#">ResampleMethod</a>	Read-write. The method to use to assign color values to any new pixels created when an image is resampled or resized.
<code>keyboardZoomResizesWindows</code>	boolean	Read-write. True to automatically resize the window when zooming in or out using keyboard shortcuts.
<code>macOSThumbnail</code>	boolean	Read-write. True to create a thumbnail when saving the image (in Mac OS only).
<code>maximizeCompatibility</code>	<a href="#">QueryStateType</a>	Read-write. The preferred policy for checking whether to maximize compatibility when opening PSD files.
<code>maxRAMuse</code>	number [5..100]	Read-write. The maximum percentage of available RAM used by Adobe Photoshop CC 2014 (5 - 100).
<code>nonLinearHistory</code>	boolean	Read-write. True to allow non-linear history.

Property	Value type	What it is (Continued)
<code>numberOfHistoryStates</code>	number	Read-write. The number of history states to preserve.
<code>otherCursors</code>	<a href="#">OtherPaintingCursors</a>	Read-write. The preferred type of pointer to use with certain tools.
<code>paintingCursors</code>	<a href="#">PaintingCursors</a>	Read-write. The preferred type of pointer to use with certain tools.
<code>parent</code>	<a href="#">Application</a>	Read-write. The containing application.
<code>pixelDoubling</code>	boolean	Read-write. True to halve the resolution (double the size of pixels) to make previews display more quickly.
<code>pointSize</code>	<a href="#">PointType</a>	Read-write. The point/pica size.
<code>recentFileListLength</code>	number [0..30]	Read-write. The number of items in the recent file list.
<code>rulerUnits</code>	<a href="#">Units</a>	Read-write. The unit the scripting system will use when receiving and returning values.
<code>saveLogItems</code>	<a href="#">SaveLogItemsType</a>	Read-write. The preferred location of history log data when saving the history items.
<code>saveLogItemsFile</code>	<a href="#">File</a>	Read-write. The path to the history log file, when the preferred location is a file.
<code>savePaletteLocations</code>	boolean	Read-write. True to make new palette locations the default location.
<code>showAsianTextOptions</code>	boolean	Read-write. True to display Asian text options in the Paragraph palette.
<code>showEnglishFontNames</code>	boolean	Read-write. True to list Asian font names in English.
<code>showSliceNumber</code>	boolean	Read-write. True to display slice numbers in the document window when using the Slice tool.
<code>showToolTips</code>	boolean	Read-write. True to show pop up definitions on mouse over.
<code>smartQuotes</code>	boolean	Read-write. True to use curly, false to use straight quote marks.
<code>textFontSize</code>	<a href="#">FontSize</a>	Read-write. Size of the small font used in panels and dialogs.
<code>typename</code>	string	Read-only. The class name of the referenced <code>preferences</code> object.



Property	Value type	What it is (Continued)
<code>typeUnits</code>	<a href="#">TypeUnits</a>	Read-write. The preferred unit for text character measurements.
<code>useAdditionalPluginFolder</code>	boolean	Read-write. True to use an additional folder for compatible plug-ins stored with a different application.
<code>useHistoryLog</code>	boolean	Read-write. True to create a log file for history states.
<code>useLowerCaseExtension</code>	boolean	Read-write. True to use lowercase for file extensions.
<code>useShiftKeyForToolSwitch</code>	boolean	Read-write. True to enable cycling through a set of hidden tools.
<code>useVideoAlpha</code>	boolean	Read-write. True to enable Adobe Photoshop CC 2014 to send transparency information to your computer's video board. (Requires hardware support.)
<code>windowsThumbnail</code>	boolean	Read-write. True to create a thumbnail when saving the image in Windows. (Requires hardware support.)

## PresentationOptions

Options for Adobe PDF presentations created using [Application.makePDFPresentation\(\)](#).

### Properties

Property	Value type	What it is
<b>autoAdvance</b>	boolean	Read-write. True to auto advance images when when viewing the presentation (default: <code>true</code> ). Valid only when <a href="#">presentation</a> = <code>true</code> .
<b>includeFilename</b>	boolean	Read-write. True to include the file name for the image (default: <code>false</code> ).
<b>interval</b>	number [1..60]	Read-write. The time in seconds before the view is auto advanced (default: 5). Valid only when <a href="#">autoAdvance</a> = <code>true</code> .
<b>loop</b>	boolean	Read-write. True to begin the presentation again after the last page (default: <code>false</code> ). Valid only when <a href="#">autoAdvance</a> = <code>true</code> .
<b>magnification</b>	<a href="#">MagnificationType</a>	Read-write. The magnification type to use when viewing the image.
<b>PDFFileOptions</b>	<a href="#">PDFSaveOptions</a>	Read-write. Options to use when creating the PDF file.
<b>presentation</b>	boolean	Read-write. True if the output will be a presentation (default: <code>false</code> ); when <code>false</code> , the output is a Multi-Page document.
<b>transition</b>	<a href="#">TransitionType</a>	Read-write. The method for transition from one image to the next (default: <code>TransitionType.NONE</code> ). Valid only when <a href="#">autoAdvance</a> = <code>true</code> .
<b>typename</b>	string	Read-only. The class name of the referenced <code>PresentationOptions</code> object.

## RawFormatOpenOptions

Options for opening a document in RAW format using the [Application.open\(\)](#) method.

### Properties

Property	Value type	What it is
<b>bitsPerChannel</b>	number	Read-write. The number of bits for each channel. The only valid values are <code>BitsPerChannelType.EIGHT</code> or <code>BitsPerChannelType.SIXTEEN</code> .
<b>byteOrder</b>	<a href="#">ByteOrder</a>	Read-write. The order in which multibyte values are read. Valid only when <a href="#">bitsPerChannel</a> = <code>BitsPerChannelType.SIXTEEN</code> .
<b>channelNumber</b>	number [1..56]	Read-write. The number of channels in the image. The value of cannot exceed the number of channels in the image. When <a href="#">bitsPerChannel</a> = <code>BitsPerChannelType.SIXTEEN</code> , the only valid values are 1, 3, or 4.
<b>headerSize</b>	number [0..1919999]	Read-write. The number of bytes of information that will appear in the file before actual image information begins; that is, the number of zeroes inserted at the beginning of the file as placeholders.
<b>height</b>	number	Read-write. The height of the image (in pixels).
<b>interleaveChannels</b>	boolean	Read-write. True to store color values sequentially.
<b>retainHeader</b>	boolean	Read-write. True to retain the header when saving. Valid only when <a href="#">headerSize</a> is 1 or greater.
<b>typename</b>	string	Read-only. The class name of the referenced <code>RawFormatOpenOptions</code> object.
<b>width</b>	number	Read-write. The image width in pixels.

## RawSaveOptions

Options for saving a document in RAW format using the [Document.saveAs\(\)](#) method.

### Properties

Property	Value type	What it is
<b>alphaChannels</b>	boolean	Read-write. True if alpha channels should be saved.
<b>spotColors</b>	boolean	Read-write. True if the spot colors should be saved.
<b>typename</b>	string	Read-only. The class name of the referenced <code>RawSaveOptions</code> object.

## RGBColor

Defines an RGB color, used in the [SolidColor](#) object.

See also [CMYKColor](#), [GrayColor](#), [HSBColor](#), [LabColor](#), [NoColor](#).

### Properties

Property	Value type	What it is
<b>blue</b>	number [0..255]	Read-write. The blue color value (default: 255).
<b>green</b>	number [0..255]	Read-write. The green color value (default: 255)
<b>hexValue</b>	string	Read-write. The hexadecimal representation of the color.
<b>red</b>	number [0..255]	Read-write. The red color value (default: 255)
<b>typename</b>	string	Read-only. The class name of the referenced <code>RGBColor</code> object.

## Selection

The selected area of a document or layer. Access through the [Document.selection](#) property. For example:

```
app.activeDocument.selection.fill(app.foregroundColor)
```

Many of the properties and methods use the [UnitValue](#) type, which combines measurement values with the measurement unit. For information about this type, see the *JavaScript Tools Guide*.

## Properties

Property	Value type	What it is
<b>bounds</b>	array of <a href="#">UnitValue</a>	Read-only. The bounding rectangle of the entire selection.
<b>parent</b>	<a href="#">Document</a>	Read-only. The object's container.
<b>solid</b>	boolean	Read-only. True if the bounding rectangle is a solid.
<b>typename</b>	string	Read-only. The class name of the referenced <code>selection</code> object.

## Methods

Method	Parameter type	Returns	What it does
<b>clear</b> ( )			Clears the selection and does not copy it to the clipboard.
<b>contract</b> (by)	<a href="#">UnitValue</a>		Contracts (reduces) the selection by the specified amount.
<b>copy</b> ( [merge] )	boolean		Copies the selection to the clipboard. When the optional argument is used and set to <code>true</code> , a merged copy is performed (all visible layers in the selection are copied).
<b>cut</b> ( )			Clears the current selection and copies it to the clipboard.
<b>deselect</b> ( )			Deselects the current selection.
<b>expand</b> (by)	<a href="#">UnitValue</a>		Expands the selection by the specified amount.
<b>feather</b> (by)	<a href="#">UnitValue</a>		Feathers the edges of the selection by the specified amount.

Method	Parameter type	Returns	What it does (Continued)
<b>fill</b> (filltype [, mode] [, opacity] [, preserveTransparency])	<a href="#">SolidColor</a> <a href="#">ColorBlendMode</a> number [1..100] boolean		Fills the selection.  opacity is a percentage value.
<b>grow</b> (tolerance, antiAlias)	number boolean		Grows the selection to include all adjacent pixels falling within the specified tolerance range.
<b>invert</b> ( )			Inverts the selection (deselects the selection and selects the rest of the layer or document).  <b>Tip:</b> To flip the selection shape, see <a href="#">rotate</a> .
<b>load</b> (from [, combination] [, inverting])	<a href="#">Channel</a> <a href="#">SelectionType</a> boolean		Loads the selection from the specified channel.
<b>makeWorkPath</b> ([tolerance])	number		Makes this selection item the work path for this document.
<b>resize</b> ([horizontal] [, vertical] [, anchor])	number number <a href="#">AnchorPosition</a>		Resizes the selected area to the specified dimensions and anchor position.
<b>resizeBoundary</b> ([horizontal] [, vertical] [, anchor])	number number <a href="#">AnchorPosition</a>		Changes the size of the selection to the specified dimensions around the specified anchor.
<b>rotate</b> (angle [, anchor])	number <a href="#">AnchorPosition</a>		Rotates the selection by the specified amount around the specified anchor point.
<b>rotateBoundary</b> (angle [, anchor])	number <a href="#">AnchorPosition</a>		Rotates the boundary of the selection around the specified anchor.
<b>select</b> (region [, type] [, feather] [, antiAlias])	array of number <a href="#">SelectionType</a> number boolean		Selects the specified region.  The region parameter is an array of four coordinates, [left, top, right, bottom].
<b>selectAll</b> ( )			Selects the entire layer.

Method	Parameter type	Returns	What it does (Continued)
<b>selectBorder</b> (width)	<a href="#">UnitValue</a>		Selects the selection border only (in the specified width); subsequent actions do not affect the selected area within the borders.
<b>similar</b> (tolerance, antiAlias)	number boolean		Grows the selection to include pixels throughout the image falling within the tolerance range.
<b>smooth</b> (radius)	number		Cleans up stray pixels left inside or outside a color-based selection (within the radius specified in pixels).
<b>store</b> (into [, combination])	<a href="#">Channel</a> <a href="#">SelectionType</a>		Saves the selection as a channel.
<b>stroke</b> (strokeColor, width [, location] [, mode] [, opacity] [, preserveTransparency])	<a href="#">SolidColor</a> number <a href="#">StrokeLocation</a> <a href="#">ColorBlendMode</a> number [1..100] boolean		Strokes the selection border. <code>opacity</code> is a percentage value.
<b>translate</b> ([deltaX] [, deltaY])	<a href="#">UnitValue</a> <a href="#">UnitValue</a>		Moves the entire selection relative to its current position.
<b>translateBoundary</b> ([deltaX] [, deltaY])	<a href="#">UnitValue</a> <a href="#">UnitValue</a>		Moves the selection relative to its current position.

## Selection sample script

The following script creates a checkerboard using the following steps:

- Create an 800 x 800 pixel document.
- Divide the entire document into 100 x 100 pixel squares.
- Select every other square in the first row, then shift the selection criteria to select the alternate squares in the following row. Repeat until every other square in the document is selected.
- Fill the selected squares with the foreground color from the palette.
- Invert the selection and fill the newly selected squares with the background color from the palette.
- Deselect the squares to remove the selection outlines (the "marching ants").

### Selection.jsx

```
// Save the current preferences
var startRulerUnits = app.preferences.rulerUnits
```



```
var startTypeUnits = app.preferences.typeUnits
var startDisplayDialogs = app.displayDialogs

// Set Adobe Photoshop CC 2014 to use pixels and display no dialogs
app.preferences.rulerUnits = Units.PIXELS
app.preferences.typeUnits = TypeUnits.PIXELS
app.displayDialogs = DialogModes.NO

//Close all the open documents
while (app.documents.length) {
    app.activeDocument.close()
}

//Create variables for the 800 pixel board divided in even 100 x 100 squares
var docSize = 800
var cells = 8
var cellSize = docSize / cells

// create a new document
var checkersDoc = app.documents.add(docSize, docSize, 72, "Checkers")

// Create a variable to use for selecting the checker board
// That allows me to shift the selection one square to the right
//on every other row, and then shift back for the rows in between.
var shiftIt = true

// loop through vertically to create the first row
for (var v = 0; v < docSize; v += cellSize) {

    // Switch the shift for a new row
    shiftIt = !shiftIt

    // loop through horizontally
    for (var h = 0; h < docSize; h += (cellSize * 2)) {

        // push over the cellSize to start with only
        if (shiftIt && h == 0) {
            h += cellSize
        }

        // Select a square
        selRegion = Array(Array(h, v),
            Array(h + cellSize, v),
            Array(h + cellSize, v + cellSize),
            Array(h, v + cellSize),
            Array(h, v))

        // In the first iteration of the loop, start the selection
        //In subsequent iterations, use the EXTEND constant value
        //of the select() method to add to the selection (in the loop's else clause)
        if (h == 0 && v == 0) {
            checkersDoc.selection.select(selRegion)
        } else {
            checkersDoc.selection.select(selRegion, SelectionType.EXTEND)
        }
    }

    // turn this off for faster execution
    // turn this on for debugging
    WaitForRedraw()
}
```

```
}

// Fill the current selection with the foreground color
checkersDoc.selection.fill(app.foregroundColor)

//Invert the selection
checkersDoc.selection.invert()

// Fill the new selection with the background color
checkersDoc.selection.fill(app.backgroundColor)

// Clear the selection to get rid of the non-printing borders
checkersDoc.selection.deselect()

// Reset the application preferences
app.preferences.rulerUnits = startRulerUnits
app.preferences.typeUnits = startTypeUnits
app.displayDialogs = startDisplayDialogs

// A helper function for debugging
// It also helps the user see what is going on
// if you turn it off for this example you
// get a flashing cursor for a number time
function WaitForRedraw()
{
    var eventWait = charIDToTypeID("Wait")
    var enumRedrawComplete = charIDToTypeID("RdCm")
    var typeState = charIDToTypeID("Stte")
    var keyState = charIDToTypeID("Stte")

    var desc = new ActionDescriptor()

    desc.putEnumerated(keyState, typeState, enumRedrawComplete)

    executeAction(eventWait, desc, DialogModes.NO)
}
```

## SGIRGBSaveOptions

Options for saving a document in SGIRGB format using the [Document.saveAs\(\)](#) method.

**Note:** The SGIRGB format is not installed automatically with Adobe Photoshop CC 2014.

### Properties

Property	Value type	What it is
<code>alphaChannels</code>	boolean	Read-write. True to save the alpha channels.
<code>spotColors</code>	boolean	Read-write. True to save the spot colors.
<code>typename</code>	string	Read-only. The class name of the referenced <code>SGIRGBSaveOptions</code> object.

## SolidColor

A color definition used in the document. Maps a color to equivalents in all available color models.

- Used in [Application.backgroundColor](#) and [foregroundColor](#) properties, in [Channel.color](#), in [ColorSampler.color](#), and in [TextItem.color](#)
- Passed to [PathItem.fillPath\(\)](#), [Selection.fill\(\)](#), and [Selection.stroke\(\)](#).

### Properties

Property	Value type	What it is
<code>cmyk</code>	<a href="#">CMYKColor</a>	Read-write. The CMYK color mode.
<code>gray</code>	<a href="#">GrayColor</a>	Read-write. The Grayscale color mode.
<code>hsb</code>	<a href="#">HSBColor</a>	Read-write. The HSB color mode.
<code>lab</code>	<a href="#">LabColor</a>	Read-write. The LAB color mode.
<code>model</code>	<a href="#">ColorModel</a>	Read-write. The color model.
<code>nearestWebColor</code>	<a href="#">RGBColor</a>	Read-only. The nearest web color to the current color.
<code>rgb</code>	<a href="#">RGBColor</a>	Read-write. The RGB color mode.
<code>typename</code>	string	Read-only. The class name of the referenced <code>SolidColor</code> object.

### Methods

Method	Parameter type	Returns	What it does
<code>isEqual</code> (color)	<a href="#">SolidColor</a>	boolean	True if the <code>SolidColor</code> object is visually equal to the specified color.

## SubPathInfo

An array of [PathPoint](#) objects that describes a straight or curved segment of a path, used to create a [SubPathItem](#).

Pass an array of these objects to the [PathItems.add\(\)](#) method. This method creates a [SubPathItem](#) object for each `SubPathInfo` object, and creates and returns a new [PathItem](#) object for the path represented by all of the subpaths.

- Use `SubPathInfo` to create subpaths; the properties are writeable.
- Use the [SubPathItem](#) object to retrieve information about existing subpaths. The properties are read-only.

### Properties

Property	Value type	What it is
<code>closed</code>	boolean	Read-write. True if the path describes an enclosed area.
<code>entireSubPath</code>	array of <a href="#">PathPoint</a>	Read-write.
<code>operation</code>	<a href="#">ShapeOperation</a>	Read-write. The subpath's operation on other subpaths. Specifies how to combine the shapes if the destination path already has a selection.
<code>typename</code>	string	Read-only. The class name of the referenced <code>SubPathInfo</code> object.

## SubPathItem

Represents a subpath; a collection of subpaths make up a [PathItem](#).

Create these objects by passing [SubPathInfo](#) objects to the [PathItems.add\(\)](#) method. This method creates a `SubPathItem` object for each [SubPathInfo](#) object, and creates and returns a new [PathItem](#) object for the path represented by all of the subpaths. Access these objects in the [PathItem.subPathItems](#) collection.

- Use the [SubPathItem](#) object to retrieve information about existing subpaths. The properties are read-only.
- Use [SubPathInfo](#) to create subpaths; the properties are writeable.

### Properties

Property	Value type	What it is
<code>closed</code>	boolean	Read-only. True if the path is closed.
<code>operation</code>	<a href="#">ShapeOperation</a>	Read-only. How this object behaves when it intersects another <a href="#">SubPathItem</a> object. Specifies how to combine the shapes if the destination path already has a selection.
<code>parent</code>	<a href="#">PathItem</a>	Read-only. The object's container.
<code>pathPoints</code>	<a href="#">PathPoints</a>	Read-only. The <code>PathPoints</code> collection.
<code>typename</code>	string	Read-only. The class name of the referenced <code>SubPathItem</code> object.

## SubPathItems

A collection of [SubPathItem](#) objects that make up a [PathItem](#). Access this object in the [PathItem.subPathItems](#) collection property.

- Use [SubPathInfo](#) to create subpaths; the properties are writeable.
- Use the [SubPathItem](#) object to retrieve information about existing subpaths. The properties are read-only.

### Properties

Property	Value type	What it is
<code>length</code>	number	Read-only. The number of elements in the collection.
<code>parent</code>	<a href="#">PathItem</a>	Read-only. The containing path item.
<code>typename</code>	string	Read-only. The class name of the referenced <code>SubPathItems</code> object.

## TargaSaveOptions

Options for saving a document in TGA (Targa) format using the [Document.saveAs\(\)](#) method.

### Properties

Property	Value type	What it is
<b>alphaChannels</b>	boolean	Read-write. True to save the alpha channels.
<b>resolution</b>	<a href="#">TargaBitsPerPixels</a>	Read-write. The number of bits per pixel (default: <code>TargaBitsPerPixels.TWENTYFOUR</code> ).
<b>rleCompression</b>	boolean	Read-write. True to use RLE compression (default: <code>true</code> ).
<b>typename</b>	string	Read-only. The class name of the referenced <code>TargaSaveOptions</code> object.



## TextFont

Describes a font that is available to the application. Access this object in the [Application.fonts](#) collection. For example:

```
var myFont = app.fonts.getByName("ArialMT");
```

### Properties

Property	Value type	What it is
<b>family</b>	string	Read-only. The font family.
<b>name</b>	string	Read-only. The name of the font.
<b>parent</b>	<a href="#">Application</a>	Read-only. The containing application.
<b>postScriptName</b>	string	Read-only. The PostScript name of the font.
<b>style</b>	string	Read-only. The font style.
<b>typename</b>	string	Read-only. The class name of the referenced <code>TextFont</code> object.

## TextFonts

The collection of fonts available on your computer. Fonts are represented by [TextFont](#) objects. Access this object in the [Application.fonts](#) collection property. For example, this displays the number of available fonts:

```
alert (app.fonts.length) ;
```

### Properties

Property	Value type	What it is
<b>length</b>	number	Read-only. The number of elements in the collection.
<b>parent</b>	<a href="#">Application</a>	Read-only. The containing application.
<b>typename</b>	string	Read-only. The class name of the referenced <code>TextFonts</code> object.

### Methods

Method	Parameter type	Returns	What it does
<b>getByName</b> (name)	string	<a href="#">TextFont</a>	Gets the first element in the <code>TextFonts</code> collection with the provided name.

## TextItem

The text in an [ArtLayer](#) object whose [kind](#) property is `LayerKind.TEXT`. Access this object in the [ArtLayer.textItem](#) property. For example:

```
myLayers[i].textItem.contents = "Layer in " + textArray[i] + " Set Inside "
```

Many of the properties use the [UnitValue](#) type, which combines a measurement value with a measurement unit. For information about this type, see the *JavaScript Tools Guide*.

## Properties

Property	Value type	What it is
<code>alternateLigatures</code>	boolean	Read-write. True to use alternate ligatures.  <b>Note:</b> Alternate ligatures are the same as Discretionary Ligatures. See Adobe Photoshop CC 2014 Help for more information.
<code>antiAliasMethod</code>	<a href="#">AntiAlias</a>	Read-write. The method of anti aliasing to use.
<code>autoKerning</code>	<a href="#">AutoKernType</a>	Read-write. The auto kerning option to use.
<code>autoLeadingAmount</code>	number [0.01..5000.00]	Read-write. The percentage to use for auto (default) leading (in points).  Valid only when <a href="#">useAutoLeading</a> = <code>true</code> .
<code>baselineShift</code>	<a href="#">UnitValue</a>	Read-write. The unit value to use in the baseline offset of text.
<code>capitalization</code>	<a href="#">TextCase</a>	Read-write. The text case.
<code>color</code>	<a href="#">SolidColor</a>	Read-write. The text color.
<code>contents</code>	string	Read-write. The actual text in the layer.
<code>desiredGlyphScaling</code>	number [50..200]	Read-write. The desired amount by which to scale the horizontal size of the text letters. A percentage value; at 100, the width of characters is not scaled.  Valid only when <a href="#">justification</a> = <code>Justification.CENTERJUSTIFIED</code> , <code>FULLYJUSTIFIED</code> , <code>LEFTJUSTIFIED</code> , or <code>Justification.RIGHTJUSTIFIED</code> .  When used, the <a href="#">minimumGlyphScaling</a> and <a href="#">maximumGlyphScaling</a> values are also required.

Property	Value type	What it is (Continued)
<b>desiredLetterScaling</b>	number [100..500]	<p>Read-write. The amount of space between letters (at 0, no space is added between letters).</p> <p>Equivalent to <b>Letter Spacing</b> in the Justification dialog (Select <b>Justification</b> on the Paragraphs palette menu).</p> <p>Valid only when <a href="#">justification</a> = <code>Justification.CENTERJUSTIFIED</code>, <code>FULLYJUSTIFIED</code>, <code>LEFTJUSTIFIED</code>, or <code>Justification.RIGHTJUSTIFIED</code>.</p> <p>When used, the <a href="#">minimumLetterScaling</a> and <a href="#">maximumLetterScaling</a> values are also required.</p>
<b>desiredWordScaling</b>	number [0..1000]	<p>Read-write. The amount (percentage) of space between words (at 100, no additional space is added between words).</p> <p>Equivalent to <b>Word Spacing</b> in the Justification dialog (Select <b>Justification</b> on the Paragraphs palette menu).</p> <p>Valid only when <a href="#">justification</a> = <code>Justification.CENTERJUSTIFIED</code>, <code>FULLYJUSTIFIED</code>, <code>LEFTJUSTIFIED</code>, or <code>Justification.RIGHTJUSTIFIED</code>.</p> <p>When used, the <a href="#">minimumWordScaling</a> and <a href="#">maximumWordScaling</a> values are also required.</p>
<b>direction</b>	<a href="#">Direction</a>	Read-write. The text orientation.
<b>fauxBold</b>	boolean	<p>Read-write. True to use faux bold (default: <code>false</code>).</p> <p>Setting this to true is equivalent to selecting text and clicking Faux Bold in the Character palette.</p>
<b>fauxItalic</b>	boolean	<p>Read-write. True to use faux italic (default: <code>false</code>).</p> <p>Setting this to true is equivalent to selecting text and clicking Faux Italic in the Character palette.</p>
<b>firstLineIndent</b>	<a href="#">UnitValue</a> [-1296..1296] points	Read-write. The amount (unit value) to indent the first line of paragraphs.
<b>font</b>	string	Read-write. The text face of the character. Use the PostScript Name of the font. See <a href="#">TextFont</a> and use the <code>postScriptName</code> property.
<b>hangingPunctuation</b>	boolean	Read-write. True to use Roman hanging punctuation.
<b>height</b>	<a href="#">UnitValueX</a>	<p>Read-write. The height of the bounding box (unit value) for paragraph text.</p> <p>Valid only when <a href="#">kind</a> = <code>TextType.PARAGRAPHTEXT</code>.</p>
<b>horizontalScale</b>	number [0..1000]	Read-write. Character scaling (horizontal) in proportion to <a href="#">verticalScale</a> (a percentage value).

Property	Value type	What it is (Continued)
<b>hyphenateAfterFirst</b>	number [1..15]	Read-write. The number of letters after which hyphenation in word wrap is allowed.
<b>hyphenateBeforeLast</b>	number [1..15]	Read-write. The number of letters before which hyphenation in word wrap is allowed.
<b>hyphenateCapitalWords</b>	boolean	Read-write. True to allow hyphenation in word wrap of capitalized words.
<b>hyphenateWordsLongerThan</b>	number [2..25]	Read-write. The minimum number of letters a word must have in order for hyphenation in word wrap to be allowed.
<b>hyphenation</b>	boolean	Read-write. True to use hyphenation in word wrap.
<b>hyphenationZone</b>	<a href="#">UnitValue</a> [0..720] pica	Read-write. The distance at the end of a line that will cause a word to break in unjustified type.
<b>hyphenLimit</b>	number	Read-write. The maximum number of consecutive lines that can end with a hyphenated word.
<b>justification</b>	<a href="#">Justification</a>	Read-write. The paragraph justification.
<b>kind</b>	<a href="#">TextType</a>	Read-write. The text-wrap type.
<b>language</b>	<a href="#">Language</a>	Read-write. The language to use.
<b>leading</b>	<a href="#">UnitValue</a>	Read-write. The leading amount.
<b>leftIndent</b>	<a href="#">UnitValue</a> [-1296..1296] points	Read-write. The amount of space to indent text from the left.
<b>ligatures</b>	boolean	Read-write. True to use ligatures.
<b>maximumGlyphScaling</b>	number [50..200]	Read-write. The maximum amount to scale the horizontal size of the text letters (a percentage value; at 100, the width of characters is not scaled).  Valid only when <a href="#">justification</a> = <code>Justification.CENTERJUSTIFIED</code> , <code>FULLYJUSTIFIED</code> , <code>LEFTJUSTIFIED</code> , or <code>Justification.RIGHTJUSTIFIED</code> .  When used, the <a href="#">minimumGlyphScaling</a> and <a href="#">desiredGlyphScaling</a> values are also required.

Property	Value type	What it is (Continued)
<code>maximumLetterScaling</code>	number [100..500]	<p>Read-write. The maximum amount of space to allow between letters (at 0, no space is added between letters).</p> <p>Equivalent to <b>Letter Spacing</b> in the Justification dialog (Select <b>Justification</b> on the Paragraphs palette menu).</p> <p>Valid only when <a href="#">justification</a> = <code>Justification.CENTERJUSTIFIED</code>, <code>FULLYJUSTIFIED</code>, <code>LEFTJUSTIFIED</code>, or <code>Justification.RIGHTJUSTIFIED</code>.</p> <p>When used, the <a href="#">minimumLetterScaling</a> and <a href="#">desiredLetterScaling</a> values are also required.</p>
<code>maximumWordScaling</code>	number [0..1000]	<p>Read-write. The maximum amount of space to allow between words (a percentage value; at 100, no additional space is added between words).</p> <p>Equivalent to <b>Word Spacing</b> in the Justification dialog (Select <b>Justification</b> on the Paragraphs palette menu).</p> <p>Valid only when <a href="#">justification</a> = <code>Justification.CENTERJUSTIFIED</code>, <code>FULLYJUSTIFIED</code>, <code>LEFTJUSTIFIED</code>, or <code>Justification.RIGHTJUSTIFIED</code>.</p> <p>When used, the <a href="#">minimumWordScaling</a> and <a href="#">desiredWordScaling</a> values are also required.</p>
<code>minimumGlyphScaling</code>	number [50..200]	<p>Read-write. The minimum amount to scale the horizontal size of the text letters (a percentage value; at 100, the width of characters is not scaled).</p> <p>Valid only when <a href="#">justification</a> = <code>Justification.CENTERJUSTIFIED</code>, <code>FULLYJUSTIFIED</code>, <code>LEFTJUSTIFIED</code>, or <code>Justification.RIGHTJUSTIFIED</code>.</p> <p>When used, the <a href="#">maximumGlyphScaling</a> and <a href="#">desiredGlyphScaling</a> values are also required.</p>

Property	Value type	What it is (Continued)
<b>minimumLetterScaling</b>	number [100..500]	<p>Read-write. The minimum amount of space to allow between letters (a percentage value; at 0, no space is removed between letters).</p> <p>Equivalent to <b>Letter Spacing</b> in the Justification dialog (Select <b>Justification</b> on the Paragraphs palette menu).</p> <p>Valid only when <a href="#">justification</a> = <code>Justification.CENTERJUSTIFIED</code>, <code>FULLYJUSTIFIED</code>, <code>LEFTJUSTIFIED</code>, or <code>Justification.RIGHTJUSTIFIED</code>.</p> <p>When used, the <a href="#">maximumLetterScaling</a> and <a href="#">desiredLetterScaling</a> values are also required.</p>
<b>minimumWordScaling</b>	number [0..1000]	<p>Read-write. The minimum amount of space to allow between words (a percentage value; at 100, no additional space is removed between words).</p> <p>Equivalent to <b>Word Spacing</b> in the Justification dialog (Select <b>Justification</b> on the Paragraphs palette menu).</p> <p>Valid only when <a href="#">justification</a> = <code>Justification.CENTERJUSTIFIED</code>, <code>FULLYJUSTIFIED</code>, <code>LEFTJUSTIFIED</code>, or <code>Justification.RIGHTJUSTIFIED</code>.</p> <p>When used, the <a href="#">maximumWordScaling</a> and <a href="#">desiredWordScaling</a> values are also required.</p>
<b>noBreak</b>	boolean	<p>Read-write. True to disallow line breaks in this text.</p> <p><b>Tip:</b> When true for many consecutive characters, can prevent word wrap and thus may prevent some text from appearing on the screen.</p>
<b>oldStyle</b>	boolean	Read-write. True to use old style type.
<b>parent</b>	<a href="#">ArtLayer</a>	Read-write. The containing layer.
<b>position</b>	array of <a href="#">UnitValue</a>	<p>Read-write. The position of origin for the text. The array members specify the X and Y coordinates.</p> <p>Equivalent to clicking the text tool at a point in the document to create the point of origin for text.</p>
<b>rightIndent</b>	<a href="#">UnitValue</a> [-1296..1296] points	Read-write. The amount of space to indent text from the right.
<b>size</b>	<a href="#">UnitValue</a>	Read-write. The font size in <code>UnitValue</code> . NOTE: Type was <code>points</code> for CS3 and older..
<b>spaceAfter</b>	<a href="#">UnitValue</a> [-1296..1296] points	Read-write. The amount of space to use after each paragraph.

Property	Value type	What it is (Continued)
<b>spaceBefore</b>	<a href="#">UnitValue</a> [-1296..1296] points	Read-write. The amount of space to use before each paragraph.
<b>strikeThru</b>	<a href="#">StrikeThruType</a>	Read-write. The text strike-through option to use.
<b>textComposer</b>	<a href="#">TextComposer</a>	Read-write. The composition method to use to evaluate line breaks and optimize the specified hyphenation and justification options.  Valid only when <a href="#">kind</a> = <code>TextType.PARAGRAPHTEXT</code> .
<b>tracking</b>	number [-1000..10000]	Read-write. The amount of uniform spacing between multiple characters.  Tracking units are 1/1000 of an em space. The width of an em space is relative to the current type size. In a 1-point font, 1 em equals 1 point; in a 10-point font, 1 em equals 10 points. So, for example, 100 units in a 10-point font are equivalent to 1 point.
<b>typename</b>	string	Read-only. The class name of the referenced <code>textItem</code> object.
<b>underline</b>	<a href="#">UnderlineType</a>	Read-write. The text underlining options.
<b>useAutoLeading</b>	boolean	Read-write. True to use a font's built-in leading information.
<b>verticalScale</b>	number [0-1000]	Read-write. Vertical character scaling in proportion to <a href="#">horizontalScale</a> (a percentage value).
<b>warpBend</b>	number [-100..100]	Read-write. The warp bend percentage.
<b>warpDirection</b>	<a href="#">Direction</a>	Read-write. The warp direction.
<b>warpHorizontalDistortion</b>	number [-100..100]	Read-write. The horizontal distortion of the warp (a percentage value).
<b>warpStyle</b>	<a href="#">WarpStyle</a>	Read-write. The style of warp to use.
<b>warpVerticalDistortion</b>	number [-100..100]	Read-write. The vertical distortion of the warp (a percentage value).
<b>width</b>	<a href="#">UnitValue</a>	Read-write. The width of the bounding box for paragraph text.  Valid only when <a href="#">kind</a> = <code>TextType.PARAGRAPHTEXT</code> .



## Methods

Method	Parameter type	Returns	What it does
<b>convertToShape</b> ( )			Converts the text item and its containing layer to a fill layer with the text changed to a clipping path.
<b>createPath</b> ( )			Creates a clipping path from the outlines of the actual text items (such as letters or words).

# TiffSaveOptions

Options for saving a document in TIFF format using the [Document.saveAs\(\)](#) method.

## Properties

Property	Value type	What it is
<b>alphaChannels</b>	boolean	Read-write. True to save the alpha channels.
<b>annotations</b>	boolean	Read-write. True to save the annotations.
<b>byteOrder</b>	<a href="#">ByteOrder</a>	Read-write. The order in which the document's multibyte values are read (default: <code>ByteOrder.MACOS</code> in Mac OS, <code>ByteOrder.IBM</code> in Windows).
<b>embedColorProfile</b>	boolean	Read-write. True to embed the color profile in the document.
<b>imageCompression</b>	<a href="#">TIFFEncoding</a>	Read-write. The compression type (default: <code>TIFFEncoding.NONE</code> ).
<b>interleaveChannels</b>	boolean	Read-write. True if the channels in the image will be interleaved.
<b>jpegQuality</b>	number [0..12]	Read-write. The quality of the produced image, which is inversely proportionate to the amount of JPEG compression.  Valid only when <a href="#">imageCompression</a> = <code>TIFFEncoding.JPEG</code> .
<b>layerCompression</b>	<a href="#">LayerCompression</a>	Read-write. The method of compression to use when saving layers (as opposed to saving composite data).  Valid only when <a href="#">layers</a> = <code>true</code> .
<b>layers</b>	boolean	Read-write. True to save the layers.
<b>saveImagePyramid</b>	boolean	Read-write. True to preserve multi-resolution information (default: <code>false</code> ).
<b>spotColors</b>	boolean	Read-write. True to save the spot colors.
<b>transparency</b>	boolean	Read-write. True to save the transparency as an additional alpha channel when the file is opened in another application.
<b>typename</b>	string	Read-only. The class name of the referenced <code>TiffSaveOptions</code> object.

## UnitValue

ExtendScript defines the JavaScript class `UnitValue` to represent measurement values together with their measurement units; see ['JavaScript support in Adobe Photoshop CC 2014' on page 32](#). For references details of these classes, see the *JavaScript Tools Guide*.

## xmpMetadata

Camera RAW image XMP metadata.

For camera RAW image files, the XMP metadata is stored in a *sidecar* file, which is a file in the same folder as the RAW file with the same base name and an XMP extension.

### Properties

Property	Value type	What it is
<code>parent</code>	<a href="#">Document</a>	Read-only. The containing document.
<code>rawData</code>	string	Read-write. A string containing the XMP metadata in XML (RDF) format. See the <i>XMP Specification</i> for details of this format.
<code>typename</code>	string	Read-only. The class name of the referenced <code>xmpMetadata</code> object.

# 3

## JavaScript Resource

This section describes the JavaScript resource that enables your JavaScripts to behave like a plug-in. This includes:

- the ability to specify a menu the script appears in as a command,
- a terminology resource so the script can function with the Action Manager, which allows your script to record and be automated by scripting parameters,
- a category to enable ordering and grouping of commands within menus, and
- an enable string that indicates whether the command is enabled or disabled given a set of conditions.
- The strings must be valid XML syntax. The "&" character will not work for example. Use the `&amp; &amp;` for example to get logical '&&' in the enableinfo block.

### JavaScript resource syntax

The JavaScript Resource has an HTML-style syntax, with each `<tag>` matched by a closing `</tag>`. This resource needs to appear within comments ( `/* ... */` ) and should be defined at the top of your script file (within the first 10,240 characters of the file.)

Tag	Description
<code>&lt;javascriptresource&gt;</code>	The resource definition tag.
<code>&lt;name&gt;</code>	The command name that appears in the Photoshop menu. If this tag is not provided in the resource, the name of the command in the menu defaults to the name of the script.
<code>&lt;menu&gt;</code>	The menu the command appears in. If this tag is not provided, the command appears in the <b>File &gt; Scripts</b> menu. <b>Note:</b> Currently the only supported values for <code>&lt;menu&gt;</code> are <code>automate</code> , <code>filter</code> and <code>help</code> . <code>automate</code> puts the script in the <b>File &gt; Automate</b> menu for example.
<code>&lt;about&gt;</code>	A string that appears in an About box, which the user can select from the <b>Help &gt; About Plug-in</b> menu.
<code>&lt;enableinfo&gt;</code>	A boolean expression that indicates whether the command is enabled in the menu. See <a href="#">Enable-info grammar</a> . <b>Note:</b> If you provide this tag, the menu item is enabled if and only if there is at least one document open, and the boolean expression evaluates to true. If you always want the menu item enabled, do not use this tag.
<code>&lt;eventid&gt;</code>	A unique string that identifies the event. Using a UUID will ensure that your script won't share this identifier with another script.

Tag	Description
<category>	The category the command appears within in the menu. Used to group and order commands in the menu. Commands are placed in the menu alphabetically based on the string in <category>. If two commands use the same category, they are grouped together.
<terminology>	The terminology dictionary for the script to function with the Action Manager. See the <a href="#">Terminology dictionary</a> .

## Basic JavaScript resource example

This example shows a very basic <javascriptresource>. With this resource, the script can be executed by selecting the command **Add a Document**, which appears in the **Automate** menu. This command is enabled in the menu, provided at least one document is already open. If the user requests information about the script from the **About Plug-in** menu, the string contained in the <about> tag is displayed in a dialog box.

```

/*
  <javascriptresource>
  <name>Add a Document</name>
  <type>automate</type>
  <about>A short string providing information about the script.</about>
  <enableinfo>>true</enableinfo>
</javascriptresource>
*/

app.documents.add();

```

## Enable-info grammar

The <enableinfo> tag provides a boolean expression that, when evaluated, indicates whether the command is enabled in the menu. You can use this expression to enable or disable the menu item based on various characteristics of the document. The Enable Info grammar is as follows:

```

<booleanExpression> := <conjunction> { "|" <conjunction> }
<conjunction> := <relation> {"&&" <relation> }
<relation> := <equality> {<relationOperator><equality>}
<equality> := <simpleExpression> {<equalityOperator><simpleExpression>}
<simpleExpression> := <term> {<addOperator><term>}
<term> := <factor> {<mulOperator><factor>}
<factor> := <integer> | <intrinsic> | <ident> |
  "(" <booleanExpression ">" | "(" simpleExpression ">" |
  "+" <factor> | "-" <factor> | "!" <factor>
<integer> := digit {digit}
<intrinsic> := <limitFunction> | <dimFunction> | <inFunction>
<limitFunction> := ( "min" | "max" ) "(" <simpleExpression> "," <simpleExpression> { "," <simpleExpression> } ")"
<dimFunction> := "dim" "(" <simpleExpression> "," <simpleExpression> ")"

```

```

<ident> :=          (alpha | "_") {alpha | digit | "_" }
<mulOperator> :=    "*" | "/"
<addOperator> :=    "+" | "-"
<equalityOperator> :=  "==" | "!="
<relationOperator> := "<" | "<=" | ">=" | ">"
<inFunction> :=     "in" "(" <simpleExpression> {"," <simpleExpression> } ")"

```

Operator precedence is shown in the following table. Operators are listed with the highest order of precedence at the top of the table

Operator	Description
	Or
&&	And
+ -	Addition or subtraction
* /	Multiply or divide
< <= >= >	Less than, less than or equal, greater than or equal, greater than
== !=	Equals, or does not equal.
(..) in() max() min() unary + - !	Functions Unary operators: increment, decrement, not

The grammar provides variables and constants that you can use in the <enableinfo> expression. The following table provides a list of the constants that are available.

Constant Name	Description
true	Boolean true
false	Boolean false
BitmapMode	Bitmap mode.
GrayScaleMode	Grayscale mode, 8 bit depth.
IndexedMode	Indexed color mode.
RGBMode	RGB color mode.
CMYKMode	CMYK color mode.
HSLMode	HSL color mode.
HSBMode	HSB color mode
MultiChannelMode	Multichannel mode.
DuotoneMode	Duotone mode.
LabMode	Lab color mode.

Constant Name	Description
Gray16Mode	Grayscale mode, 16 bits per channel
RGB48Mode	RGB color mode, 16 bits per channel.
Lab48Mode	LAB mode, 16 bits per channel.
CMYK64Mode	CMYK mode, 16 bits per channel.
DeepMultichannelMode	Deep multichannel mode.
Duotone16Mode	Duotone mode, 16 bit depth.
RGB96Mode	RGB color mode, 32 bits per channel.
Gray32Mode	Grayscale mode, 32 bit depth.

The following table show the set of variables you can use in the <enableinfo> expression. The value of these variables is set based on the properties of the active document.

Variable Name	Description
PSHOP_ImageMode	Image mode of the active document.
PSHOP_ImageDepth	Depth of the active document.
PSHOP_HasLayerMask	Boolean indicating presence of layer mask.
PSHOP_HasSelectionMask	Boolean indicating presence of selection mask.
PSHOP_HasTransparencyMask	Boolean indicating presence of transparency mask.
PSHOP_NumTargetChannels	Number of target channels.
PSHOP_NumTrueChannels	Numer of image channels.
PSHOP_IsAdjustorSheet	Boolean
PSHOP_IsTargetComposite	Boolean indicating whether channels are flattened.
PSHOP_IsTargetSection	Boolean.
PSHOP_IsTargetVisible	Boolean.
PSHOP_ImageWidth	Width of the image.
PSHOP_ImageHeight	Height of the image.
PSHOP_TargetProtectFlags.	

## Undefined values in enable-info evaluation

If any arithmetic or relation operation contains an operand whose value is undefined, or a variable that is undefined, the result of that evaluation is `false`.

Boolean values are treated as in C/C++, where non-zero values are `true`, and zero is `false`, with the exception that an undefined value is also `false`.



## Using the "in" function

The `in` function (see `<inFunction>`) returns `true` if the first parameter is equal to at least one of the subsequent parameters. A typical use might be to see if the image mode of the active document is one of a set of image modes. For example:

```
in(PSHOP_ImageMode, RGBMode, CMYKMode, LabMode)
```

## Action Manager automation

For your script to be able to record scripting parameters and be automated by them, it requires the addition of two basic mechanisms:

- A *terminology dictionary* that maps your script's user interface to human readable text, providing text and type information for each parameter the script uses.
- Code to read parameter information when it comes from the Action Manager, rather than from the user-interface, and code to write parameter information to the Action Manager. This code uses the Action Manager classes [ActionDescriptor](#), [ActionList](#), and [ActionReference](#).

See `Conditional Mode Change.jsx` for an example of a script that can record and be automated by scripting parameters. This file can be found in the Presets/Scripts folder.

## Terminology dictionary

The JavaScript resource provides a `<terminology>` tag that allows you to provide the terminology dictionary for your script. The first step in creating a terminology dictionary is to review your script's user interface, and create human-readable strings for each element in your user interface.

For example, in the Conditional Mode Change command, the user interface requests a source mode and a target mode. Both source mode and target mode have several options. All of these elements of the user interface need to have entries in the terminology dictionary.

The terminology dictionary is created in a PDF dictionary format, with the following entries, and must have the following format in the `<javascriptresource>`:

```
<terminology><![CDATA[<<<  
  /Version integer  
  /Events <<event dictionary>>  
  /Classes <<class dictionary>>  
  /Enumerations <<enumeration dictionary>>  
>>> ]]></terminology>
```

**Note:** The information in the terminology tag needs to be wrapped in a `CDATA` block so the xml parser will ignore "/" and other tags that appear in the terminology.

The definitions for events, classes and enumerations dictionaries are provided below.

The `/Events` dictionary contains an entry for each event:

```

/eventName [                               // Name used in string-based API
  (String event name)                       // required
  /direct parameter type                    // optional; if omitted, no parameter
  <<                                        // optional parameter dictionary
    /parameterName [                       // Name used in string-based API
      (String name)                        // required
      /parameter type                      // required
    ]
    ...                                    // other parameters
  >>
]

```

The `/Classes` dictionary contains an entry for each class:

```

/className [                               // Name used in string-based API
  (ZString class name)                     // required
  <<                                        // property dictionary
    /propertyName [                       // Name used in string-based API
      (String name)                        // required
      /property type                      // required
    ]
    ...                                    // other properties
  >>
]

```

The `/Enumerations` dictionary contains an entry for each enumerated type:

```

/enumTypeName                             // Name used in string-based API
<<
  /enumValue (String name)                // required
  ...
>>

```

## Value type definitions

For `/parameter type` and `/property type` definitions, you can use the Class and Enumeration type declarations you make in your own terminology dictionary, you can use declarations provided by Photoshop or you can use basic value types.

### Basic Value Types

The basic value types are shown in the following table:

Name	Code	Description
<code>typeInteger</code>	<code>'long'</code>	<code>int32</code>
<code>typeFloat</code>	<code>'doub'</code>	IEEE 64 bit double
<code>typeBoolean</code>	<code>'bool'</code>	TRUE OR FALSE.
<code>typeText</code>	<code>'TEXT'</code>	Block of any number of readable characters.
<code>typeAlias</code>	<code>'alis'</code>	Macintosh file system path.

Name	Code	Description
typePaths	'Pth '	Windows file system path.
typePlatformFilePath	'alis' or 'Pth'	typeAlias for Mac OS, typePath for Windows.

### Predefined Class Types

Photoshop provides a number of predefined classes that are available for use in the terminology dictionary. A useful subset of those classes is shown in the table below. Use these classes when they are appropriate, but you can define new classes in the terminology resource, if necessary.

Name	Code	Description
classColor	'Clr '	Class for color classes.
classRGBColor	'RGBC'	keyRed, keyGreen, keyBlue
classCMYKColor	'CMYC'	keyCyan, keyMagenta, keyYellow, keyBlack.
classUnspecifiedColor	'UnsC'	Unspecified.
classGrayscale	'Grsc'	keyGray
classBookColor	'BkCl '	Book color
classLabColor	'LbCl '	keyLuminance, keyA, keyB.

## Uniqueness rules for terminology entries

Generally, the names for terminology entries must be unique within a particular category and scope. It is best to not make names unique unnecessarily; generic terms are preferable, and if a name already exists for something, go ahead and use it. Case matters in considering uniqueness of terminology entries.

The uniqueness rules for terminology entries are:

- All event names must be different from all other event names.
- All class names must be different from all other names.
- All enumeration type names must be different from all other enumeration type names.
- All keys must be different from all other keys used in the same class or event.
- All enumeration values must be different from all other enumeration values in the same enumeration type.
- A class, event, enumeration type, key, and enumeration value can all have the same name.

## Terminology definition example

This example demonstrates the terminology definition for a new event; the example uses ZStrings. The event is called `newAnnot`, and it takes three parameters:

- `annotType`, an enumeration (`annotType`)
- `at`, a class (`point`), and
- `size`, a class (`annotSizeClass`).

The `annotSizeClass` has two properties: `width`, and `height`, both of type `floatType`. The enumeration `annotType` has three values: `annotUnknown`, `annotText`, and `annotSound`.

```
<terminology><![CDATA[<<<
  /Version 1
  /Events
    /newAnnot [(New Annotation) <<
      /annotType [(Type) /annotType]
      /at [(At) /Point]
      /size [(Size) /annotSizeClass] >>]
  /Classes
    /annotSizeClass [(Size) <<
      /width [(Width) /floatType]
      /height [(Height) /floatType]
      >>]
  /Enumerations
    /annotType <<
      /annotUnknown (Unknown)
      /annotText (Text)
      /annotSound (Sound)
    >>> ]]></terminology>
```

# 4

## Scripting Constants

This section lists and describes the enumerations defined for use with Adobe Photoshop CC 2014 JavaScript properties and methods.

Constant type	Values	What it means
<b>AdjustmentReference</b>	ABSOLUTE RELATIVE	Method to use for interpreting selective color adjustment specifications:  ABSOLUTE = % of the whole.  RELATIVE = % of the existing color amount.  Pass to <a href="#">ArtLayer.selectiveColor()</a> .
<b>AnchorPosition</b>	BOTTOMCENTER BOTTOMLEFT BOTTOMRIGHT MIDDLECENTER MIDDLELEFT MIDDLERIGHT TOPCENTER TOPLEFT TOPRIGHT	The point around which to transform an object. This is the point that does not move when an object is rotated or resized using methods in <a href="#">ArtLayer</a> , <a href="#">LayerSet</a> , and <a href="#">Selection</a> , or when the entire canvas is resized with <a href="#">Document.resizeCanvas()</a> .
<b>AntiAlias</b>	CRISP NONE SHARP SMOOTH STRONG	Method to use to smooth edges by softening the color transition between edge pixels and background pixels. Used in a <a href="#">TextItem.antiAliasMethod</a> .
<b>AutoKernType</b>	MANUAL METRICS OPTICAL	The type of kerning to use for characters. Used in <a href="#">TextItem.autoKerning</a> .
<b>BatchDestinationType</b>	FOLDER NODESTINATION SAVEANDCLOSE	The destination, if any, for batch-processed files, specified in the <a href="#">BatchOptions</a> used with the <a href="#">Application.batch()</a> method:  FOLDER: Save modified versions of the files to a new location (leaving the originals unchanged).  NODESTINATIONTYPE: Leave all files open.  SAVEANDCLOSE: Save changes and close the files.

Constant type	Values	What it means
<b>BitmapConversionType</b>	CUSTOMPATTERN DIFFUSIONDITHER HALFTHRESHOLD HALFTONESCREEN PATTERNDITHER	Specifies the quality of an image you are converting to bitmap mode. Used in <a href="#">BitmapConversionOptions</a> .
<b>BitmapHalfToneType</b>	CROSS DIAMOND ELLIPSE LINE ROUND SQUARE	Specifies the shape of the dots (ink deposits) in the halftone screen. Used in <a href="#">BitmapConversionOptions</a> .
<b>BitsPerChannelType</b>	EIGHT ONE SIXTEEN THIRTYTWO	The number of bits per color channel. Value of <a href="#">Document.bitsPerChannel</a> ; pass to <a href="#">Documents.add()</a> . Also used in <a href="#">PDFOpenOptions</a> and <a href="#">CameraRAWOpenOptions</a> .
<b>BlendMode</b>	COLORBLEND COLORBURN COLORDODGE DARKEN DIFFERENCE DISSOLVE DIVIDE EXCLUSION HARDLIGHT HARDMIX HUE LIGHTEN LINEARBURN LINEARDODGE LINEARLIGHT LUMINOSITY MULTIPLY NORMAL OVERLAY PASSTHROUGH PINLIGHT SATURATION SCREEN SOFTLIGHT SUBTRACT VIVIDLIGHT	Controls how pixels in an image are blended when a filter is applied. The value of <a href="#">ArtLayer.blendMode</a> and <a href="#">LayerSet.blendMode</a> .
<b>BMPDepthType</b>	BMP_A1R5G5B5 BMP_A4R4G4B4 BMP_A8R8G8B8 BMP_R5G6B5 BMP_R8G8B8 BMP_X1R5G5B5 BMP_X4R4G4B4 BMP_X8R8G8B8 EIGHT FOUR ONE SIXTEEN THIRTYTWO TWENTYFOUR	The number of bits per channel (also called pixel depth or color depth). The number selected indicates the exponent of 2. For example, a pixel with a bit-depth of EIGHT has $2^8$ , or 256, possible color values. Used in <a href="#">BMPSaveOptions</a> .

Constant type	Values	What it means
<b>ByteOrder</b>	IBM MACOS	The platform-specific order in which multibyte values are read.
<b>CameraRAWSettingsType</b>	CAMERA CUSTOM SELECTEDIMAGE	The default CameraRaw settings to use: the camera settings, custom settings, or the settings of the selected image. Set in <a href="#">CameraRAWOpenOptions</a> .
<b>CameraRAWSize</b>	EXTRALARGE LARGE MAXIMUM MEDIUM MINIMUM SMALL	The camera RAW size type options:  EXTRALARGE=5120 x 4096 LARGE=4096 x 2731 MAXIMUM=6144 X 4096 MEDIUM=3072 x 2048 MINIMUM=1536 x 1024 SMALL=2048 x 1365  Set in <a href="#">CameraRAWOpenOptions</a> .
<b>ChangeMode</b>	BITMAP CMYK GRAYSCALE INDEXEDCOLOR LAB MULTICHANNEL RGB	The new color profile or mode for a document, specified in <a href="#">Document.changeMode()</a> .  <b>Note:</b> Color images must be changed to GRAYSCALE mode before you can change them to BITMAP mode.
<b>ChannelType</b>	COMPONENT MASKEDAREA SELECTEDAREA SPOTCOLOR	The type of a color channel:  COMPONENT: related to document color mode.  MASKEDAREA: Alpha channel where color indicates masked area.  SELECTEDAREA: Alpha channel where color indicates selected are.  SPOTCOLOR: Alpha channel to store a spot color.

Constant type	Values	What it means
<b>ColorBlendMode</b>	BEHIND CLEAR COLOR COLORBURN COLORDODGE DARKEN DARKERCOLOR DIFFERENCE DISSOLVE EXCLUSION HARDLIGHT HARDMIXBLEND HUE LIGHTEN LIGHTERCOLOR LINEARBURN LINEARDODGE LINEARLIGHT LUMINOSITY MULTIPLY NORMAL OVERLAY PINLIGHT SATURATION SCREEN SOFTLIGHT VIVIDLIGHT	The way color should be blended in a fill or stroke operation. Pass to <a href="#">PathItem.fillPath()</a> , <a href="#">Selection.fill()</a> , <a href="#">Selection.stroke()</a>
<b>ColorModel</b>	CMYK GRAYSCALE HSB LAB NONE RGB	The color model to use for a <a href="#">SolidColor</a> .
<b>ColorPicker</b>	ADOBE APPLE PLUGIN WINDOWS	The preferred color-selection tool, set in <a href="#">Preferences</a> .
<b>ColorProfileType</b>	CUSTOM NONE WORKING	The type of color profile used to manage this document, set in <a href="#">Document.colorProfileType</a> .
<b>ColorReductionType</b>	ADAPTIVE BLACKWHITE CUSTOM GRAYSCALE MACINTOSH PERCEPTUAL RESTRICTIVE SELECTIVE WINDOWS	The color reduction algorithm option for <a href="#">ExportOptionsSaveForWeb</a> .
<b>ColorSpaceType</b>	ADOBERGB COLORMATCHRGB PROPHOTORGB SRGB	The type of color space to use in <a href="#">CameraRAWOpenOptions</a> .
<b>CopyrightedType</b>	COPYRIGHTEDWORK PUBLICDOMAIN UNMARKED	The copyright status of a document. Used in <a href="#">DocumentPrintSettings.copyrighted</a> .



Constant type	Values	What it means
<b>CreateFields</b>	DUPLICATION INTERPOLATION	The method to use for creating fields. Pass to <a href="#">ArtLayer.applyDelInterlace()</a> .
<b>CropToType</b>	ARTBOX BLEEDBOX BOUNDINGBOX CROPBOX MEDIABOX TRIMBOX	The style to use when cropping a page in a PDF document. Set in <a href="#">PDFOpenOptions.cropPage</a> .
<b>DCSType</b>	COLORCOMPOSITE GRAYSCALECOMPOSITE NOCOMPOSITE	The type of composite DCS file to create with <a href="#">DCS1_SaveOptions</a> or <a href="#">DCS2_SaveOptions</a> :  COLORCOMPOSITE: Creates a color composite file in addition to DCS files.  GRAYSCALECOMPOSITE: Creates a grayscale composite file in addition to DCS files.  NOCOMPOSITE: Does not create a composite file.
<b>DepthMapSource</b>	IMAGEHIGHLIGHT LAYERMASK NONE TRANSPARENCYCHANNEL	The source to use for the depth map. Pass to <a href="#">ArtLayer.applyLensBlur()</a> .
<b>DescValueType</b>	ALIASTYPE BOOLEANATYPE CLASSTYPE DOUBLETTYPE ENUMERATEDTYPE INTEGERTYPE LARGEINTEGERTYPE LISTTYPE OBJECTTYPE RAWTYPE REFERENCETYPE STRINGTYPE UNITDOUBLE	The value type of an action key, returned by <a href="#">ActionDescriptor.getType()</a> and <a href="#">ActionList.getType()</a> .
<b>DialogModes</b>	ALL ERROR NO	Controls the type of dialogs Photoshop displays when running scripts.
<b>Direction</b>	HORIZONTAL VERTICAL	<ul style="list-style-type: none"> <li>• The direction in which to flip the document canvas, passed to <a href="#">Document.flipCanvas()</a>.</li> <li>• The orientation of text in <a href="#">TextItem.direction</a>.</li> <li>• The direction of text warping in <a href="#">TextItem.warpDirection</a>.</li> </ul>

Constant type	Values	What it means
<b>DisplacementMapType</b>	STRETCHTOFIT TILE	Describes how the displacement map fits the image if the image is not the same size as the map. Pass to <a href="#">ArtLayer.applyDisplace()</a> .
<b>Dither</b>	DIFFUSION NOISE NONE PATTERN	The type of dithering to use in <a href="#">GIFSaveOptions</a> , <a href="#">IndexedConversionOptions</a> and <a href="#">ExportOptionsSaveForWeb</a> .
<b>DocPositionStyle</b>	PRINTCENTERED USERDEFINED	The type of positioning to use in DocPosition
<b>DocumentFill</b>	BACKGROUNDCOLOR TRANSPARENT WHITE	The fill type of a new document, passed to <a href="#">Documents.add()</a> .
<b>DocumentMode</b>	BITMAP CMYK DUOTONE GRAYSCALE INDEXEDCOLOR LAB MULTICHANNEL RGB	The color mode of a open document, <a href="#">Document.mode</a> . See also <a href="#">Document.changeMode()</a> .
<b>EditLogItemsType</b>	CONCISE DETAILED SESSIONONLY	The preferred level of detail in th history log, set in <a href="#">Preferences</a> :  CONCISE: Save a concise history log.  DETAILED: Save a detailed history log.  SESSIONONLY: Save history log only for the session.
<b>ElementPlacement</b>	INSIDE PLACEATBEGINNING PLACEATEND PLACEBEFORE PLACEAFTER	The object's position in the Layers palette.  <b>Note:</b> Not all values are valid for all object types. See the specific object description to make sure you are using a valid value.
<b>EliminateFields</b>	EVENFIELDS ODDFIELDS	The type of fields to eliminate. Pass to <a href="#">ArtLayer.applyDelInterlace()</a> .
<b>ExportType</b>	ILLUSTRATORPATHS SAVEFORWEB	The type of export for <a href="#">Document.exportDocument()</a> .  This is equivalent to choosing <b>File &gt; Export &gt; Paths To Illustrator</b> , or <b>File &gt; Save For Web and Devices</b> .
<b>Extension</b>	LOWERCASE NONE UPPERCASE	The policy and format for appending an extension to the filename when saving with <a href="#">Document.saveAs()</a> .

Constant type	Values	What it means
<b>FileNamingType</b>	DDMM DDMMYY DOCUMENTNAMELOWER DOCUMENTNAMEMIXED DOCUMENTNAMEUPPER EXTENSIONLOWER EXTENSIONUPPER MMDD MDDYY SERIALLETTERLOWER SERIALLETTERUPPER SERIALNUMBER1 SERIALNUMBER2 SERIALNUMBER3 SERIALNUMBER4 YYDDMM YYMMDD YYYYMMDD	File naming options for the <a href="#">BatchOptions</a> used with the <a href="#">Application.batch()</a> method.
<b>FontPreviewType</b>	HUGE EXTRALARGE LARGE MEDIUM NONE SMALL	The preferred type size to use for font previews in the type tool font menus , set in <a href="#">Preferences</a> .
<b>FontSize</b>	LARGE MEDIUM SMALL	The preferred type size to use for panels and dialogs, set in <a href="#">Preferences</a> .
<b>ForcedColors</b>	BLACKWHITE NONE PRIMARIES WEB	The type of colors to be included the color table regardless of their usage. Used in <a href="#">GIFSaveOptions</a> and <a href="#">IndexedConversionOptions</a> .  BLACKWHITE: Pure black and pure white.  NONE: None  PRIMARIES: Red, green, blue, cyan, magenta, yellow, black, and white.  WEB: the 216 web-safe colors.
<b>FormatOptions</b>	OPTIMIZEDBASELINE PROGRESSIVE STANDARDBASELINE	The option with which to save a JPEG file, in <a href="#">JPEGSaveOptions</a> .  OPTIMIZEDBASELINE: Optimized color and a slightly reduced file size.  PROGRESSIVE: Displays a series of increasingly detailed scans as the image downloads.  STANDARDBASELINE: Format recognized by most web browsers.
<b>GalleryConstrainType</b>	CONSTRAINBOTH CONSTRAINHEIGHT CONSTRAINWIDTH	The type of proportions to constrain for images. Used in <a href="#">GalleryImagesOptions</a> .

Constant type	Values	What it means
<b>GalleryFontType</b>	ARIAL COURIERNEW HELVETICA TIMESNEWROMAN	The fonts to use for the Web photo gallery captions and other text. Used in <a href="#">GalleryBannerOptions</a> , <a href="#">GalleryImagesOptions</a> , and <a href="#">GalleryThumbnailOptions</a> .  Also used in <a href="#">PicturePackageOptions</a> .
<b>GallerySecurityTextColorType</b>	BLACK CUSTOM WHITE	The color to use for text displayed over gallery images as an antitheft deterrent. Used in <a href="#">GallerySecurityOptions</a> .
<b>GallerySecurityTextPositionType</b>	CENTERED LOWERLEFT LOWERRIGHT UPPERLEFT UPPERRIGHT	The position of the text displayed over gallery images as an antitheft deterrent. Used in <a href="#">GallerySecurityOptions</a> .  Also used in <a href="#">PicturePackageOptions</a> .
<b>GallerySecurityTextRotateType</b>	CLOCKWISE45 CLOCKWISE90 COUNTERCLOCKWISE45 COUNTERCLOCKWISE90 ZERO	The orientation of the text displayed over gallery images as an antitheft deterrent. Used in <a href="#">GallerySecurityOptions</a> .  Also used in <a href="#">PicturePackageOptions</a> .
<b>GallerySecurityType</b>	CAPTION COPYRIGHT CREDIT CUSTOMTEXT FILENAME NONE TITLE	The content to use for text displayed over gallery images as an antitheft deterrent. Used in <a href="#">GallerySecurityOptions</a> .  <b>Note:</b> All types draw from the image's file information except CUSTOMTEXT.
<b>GalleryThumbSizeType</b>	CUSTOM LARGE MEDIUM SMALL	The size of thumbnail images in the web photo gallery. Used in <a href="#">GalleryThumbnailOptions</a> .
<b>Geometry</b>	HEPTAGON HEXAGON OCTAGON PENTAGON SQUARE TRIANGLE	Geometric options for shapes, such as the iris shape in the Lens Blur Filter.  Pass to <a href="#">ArtLayer.applyLensBlur()</a> .
<b>GridLineStyle</b>	DASHED DOTTED SOLID	The preferred line style for the nonprinting grid displayed over images, set in <a href="#">Preferences</a> .
<b>GridSize</b>	LARGE MEDIUM NONE SMALL	The preferred size of grid line spacing, set in <a href="#">Preferences</a> .

Constant type	Values	What it means
<b>GuideLineStyle</b>	DASHED SOLID	The preferred line style for nonprinting guides displayed over images, set in <a href="#">Preferences</a> .
<b>IllustratorPathType</b>	ALLPATHS DOCUMENTBOUNDS NAMEDPATH	The paths to export to an Illustrator file using <a href="#">Document.exportDocument()</a> .
<b>Intent</b>	ABSOLUTECOLORIMETRIC PERCEPTUAL RELATIVECOLORIMETRIC SATURATION	The rendering intent to use when converting from one color space to another with <a href="#">Document.convertProfile()</a> or <a href="#">Document.print()</a>
<b>Justification</b>	CENTER CENTERJUSTIFIED FULLYJUSTIFIED LEFT LEFTJUSTIFIED RIGHT RIGHTJUSTIFIED	The placement of paragraph text within the bounding box. Used in <a href="#">TextItem.justification</a> .
<b>Language</b>	BRAZILLIANPORTUGUESE CANADIANFRENCH DANISH DUTCH ENGLISHUK ENGLISHUSA FINNISH FRENCH GERMAN ITALIAN NORWEGIAN NYNORSKNORWEGIAN OLDGERMAN PORTUGUESE SPANISH SWEDISH SWISSGERMAN	The language to use for text. Used in <a href="#">TextItem.language</a> .
<b>LayerCompression</b>	RLE ZIP	Compression methods for data for pixels in layers, when saving to TIFF format. Used in <a href="#">TiffSaveOptions</a> .

Constant type	Values	What it means
<b>LayerKind</b>	BLACKANDWHITE BRIGHTNESSCONTRAST CHANNELMIXER COLORBALANCE CURVES EXPOSURE GRADIENTFILL GRADIENTMAP HUESATURATION INVERSION LEVELS NORMAL PATTERNFILL PHOTOFILTER POSTERIZE SELECTIVECOLOR SMARTOBJECT SOLIDFILL TEXT THRESHOLD LAYER3D VIBRANCE VIDEO	The type of a layer object, in <a href="#">ArtLayer.kind</a> .  <b>Note:</b> You can create a text layer only from an empty art layer.
<b>LensType</b>	MOVIEPRIME PRIME105 PRIME35 ZOOMLENS	The type of lens to use. Pass to <a href="#">ArtLayer.applyLensFlare()</a> .
<b>MagnificationType</b>	ACTUALSIZE FITPAGE	The type of magnification to use when viewing an image. Used in <a href="#">PresentationOptions</a> .
<b>MatteType</b>	BACKGROUND BLACK FOREGROUND NETSCAPE NONE SEMIGRAY WHITE	The color to use to fill anti-aliased edges adjacent to transparent areas of the image. When transparency is turned off for an image, the matte color is applied to transparent areas.  Used in <a href="#">GIFSaveOptions</a> , <a href="#">IndexedConversionOptions</a> , and <a href="#">JPEGSaveOptions</a> .
<b>MeasurementRange</b>	ALLMEASUREMENTS ACTIVEMEASUREMENTS	The measurement to act upon. Pass to <a href="#">MeasurementLog</a> methods.
<b>MeasurementSource</b>	MEASURESELECTION MEASURECOUNTOOL MEASURERULERTOOL	The source for recording measurements. Pass to <a href="#">Document.recordMeasurements()</a> .
<b>NewDocumentMode</b>	BITMAP CMYK GRAYSCALE LAB RGB	The color profile to use for a new document.  Pass to <a href="#">Documents.add()</a> .  Also used in <a href="#">ContactSheetOptions</a> and <a href="#">PicturePackageOptions</a> .

Constant type	Values	What it means
<b>NoiseDistribution</b>	GAUSSIAN UNIFORM	Distribution method to use when applying an Add Noise filter. Pass to <a href="#">ArtLayer.applyAddNoise()</a> .
<b>OffsetUndefinedAreas</b>	REPEATEDEDGEPIXELS SETTOBACKGROUND WRAPAROUND	Method to use to fill the empty space left by offsetting a an image or selection. Pass to <a href="#">ArtLayer.applyOffset()</a> .
<b>OpenDocumentMode</b>	CMYK GRAYSCALE LAB RGB	The color profile to use when opening an EPS or PDF document. Pass to <code>app.open()</code> in <a href="#">EPSOpenOptions</a> or <a href="#">PDFOpenOptions</a> .
<b>OpenDocumentType</b>	ALIASPIX BMP CAMERARAW COMPUSERVEGIF DICOM ELECTRICIMAGE EPS EPSPICTPREVIEW EPSTIFFPREVIEW FILMSTRIP JPEG PCX PDF PHOTOCD PHOTOSHOP PHOTOSHOPDCS_1 PHOTOSHOPDCS_2 PHOTOSHOPEPS PHOTOSHOPPDF PICTFILEFORMAT PICTRESOURCEFORMAT PIXAR PNG PORTABLEBITMAP RAW SCITEXCT SGIRGB SOFTIMAGE TARGA TIFF WAVEFRONTRLA WIRELESSBITMAP	<p>The format in which to open the document, using <code>app.open()</code>.</p> <p><b>Note:</b> PHOTOCD is deprecated. Kodak PhotoCD is now found in the Goodies folder on the Adobe Photoshop CC 2014 Install DVD.</p> <p><b>Note:</b> The DICOM option is for the Extended version only.</p>
<b>OperatingSystem</b>	OS2 WINDOWS	The target operating system in <a href="#">BMPSaveOptions</a> .
<b>Orientation</b>	LANDSCAPE PORTRAIT	<p>Page orientation for <a href="#">PhotoCDOpenOptions</a>, deprecated in Photoshop CS3.</p> <p><b>Note:</b> Kodak PhotoCD is now found in the Goodies folder on the Adobe Photoshop CC 2014 Install DVD.</p>

Constant type	Values	What it means
<b>OtherPaintingCursors</b>	PRECISEOTHER STANDARDOTHER	The preferred pointer for the following tools: Eraser, Pencil, Paintbrush, Healing Brush, Rubber Stamp, Pattern Stamp, Smudge, Blur, Sharpen, Dodge, Burn, Sponge. Set in <a href="#">Preferences</a> .
<b>PaintingCursors</b>	BRUSHSIZE PRECISE STANDARD	The preferred pointer for the following tools: Marquee, Lasso, Polygonal Lasso, Magic Wand, Crop, Slice, Patch Eyedropper, Pen, Gradient, Line, Paint Bucket, Magnetic Lasso, Magnetic Pen, Freeform Pen, Measure, Color Sampler. Set in <a href="#">Preferences</a> .
<b>PaletteType</b>	EXACT LOCALADAPTIVE LOCALPERCEPTUAL LOCALSELECTIVE MACOSPALETTE MASTERADAPTIVE MASTERPERCEPTUAL MASTERSELECTIVE PREVIOUSPALETTE UNIFORM WEBPALETTE WINDOWSPALETTE	The palette type to use in <a href="#">GIFSaveOptions</a> and <a href="#">IndexedConversionOptions</a> .
<b>PathKind</b>	CLIPPINGPATH NORMALPATH TEXTMASK VECTORMASK WORKPATH	The type of a <a href="#">PathItem</a> .
<b>PDFCompatibility</b>	PDF13 PDF14 PDF15 PDF16 PDF17	The PDF version to make the document compatible with. Used in <a href="#">PDFSaveOptions</a> .
<b>PDFEncoding</b>	JPEG JPEG2000HIGH JPEG2000LOSSLESS JPEG2000LOW JPEG2000MED JPEG2000MEDHIGH JPEG2000MEDLOW JPEGHIGH JPEGLow JPEGMED JPEGMEDHIGH JPEGMEDLOW NONE PDFZIP PDFZIP4BIT	The type of compression to use when saving a document in PDF format. Used in <a href="#">PDFSaveOptions</a> .



Constant type	Values	What it means
<b>PDFResample</b>	NONE PDFAVERAGE PDFBICUBIC PDFSUBSAMPLE	The down sample method to use. Used in <a href="#">PDFSaveOptions</a> .
<b>PDFStandard</b>	NONE PDFX1A2001 PDFX1A2003 PDFX32002 PDFX32003 PDFX42008	The PDF standard to make the document compatible with. Used in <a href="#">PDFSaveOptions</a> .
<b>PhotoCDColorSpace</b>	LAB16 LAB8 RGB16 RGB8	The color space for <a href="#">PhotoCDOpenOptions</a> , deprecated in Photoshop CS3.  <b>Note:</b> Kodak PhotoCD is now found in the Goodies folder on the Adobe Photoshop CC 2014 Install DVD.
<b>PhotoCDSize</b>	EXTRALARGE LARGE MAXIMUM MEDIUM MINIMUM SMALL	The pixel dimensions of the image in <a href="#">PhotoCDOpenOptions</a> , deprecated in Photoshop CS3.  EXTRALARGE = 1024x1536 LARGE = 512x768 MAXIMUM = 2048x3072 MEDIUM = 256x384 MINIMUM = 64x96 SMALL = 128x192  <b>Note:</b> Kodak PhotoCD is now found in the Goodies folder on the Adobe Photoshop CC 2014 Install DVD.
<b>PICTBitsPerPixels</b>	EIGHT FOUR SIXTEEN THIRTYTWO TWO	The number of bits per pixel to use when compression a PICT file. Used in <a href="#">PICTFileSaveOptions</a> and <a href="#">PICTResourceSaveOptions</a> .  <b>Note:</b> Use 16 or 32 for RGB images; use 2, 4, or 8 for bitmap and grayscale images.
<b>PICTCompression</b>	JPEGHIGHPICT JPEGLOWPICT JPEGMAXIMUMPICT JPEGMEDIUMPICT NONE	The type of compression to use when saving an image as a PICT file. Used in <a href="#">PICTFileSaveOptions</a> and <a href="#">PICTResourceSaveOptions</a> .
<b>PicturePackageTextType</b>	CAPTION COPYRIGHT CREDIT FILENAME NONE ORIGIN USER	The function or meaning of text in a Picture Package. Used in <a href="#">PicturePackageOptions</a> .

Constant type	Values	What it means
<b>PointKind</b>	CORNERPOINT SMOOTHPOINT	The role a <a href="#">PathPoint</a> plays in a <a href="#">PathItem</a> .
<b>PointType</b>	POSTSCRIPT TRADITIONAL	The preferred measurement to use for type points, set in <a href="#">Preferences.pointSize</a> :  POSTSCRIPT = 72 points/inch. TRADITIONAL = 72.27 points/inch.
<b>PolarConversionType</b>	POLARTORECTANGULAR RECTANGULARTOPOLAR	The method of polar distortion to use. Pass to <a href="#">ArtLayer.applyPolarCoordinates()</a> .
<b>Preview</b>	EIGHTBITTIFF MACOSEIGHTBIT MACOSJPEG MACOSMONOCHROME MONOCHROMETIFF NONE	The type of image to use as a low-resolution preview in the destination application.  Used in <a href="#">DCS1_SaveOptions</a> , <a href="#">DCS2_SaveOptions</a> , and <a href="#">EPSSaveOptions</a> .
<b>PrintColorHandling</b>	PRINTERMANAGED PHOTOSHOPMANAGED SEPARATIONS	The type of color handling to use for ColorHandling
<b>PurgeTarget</b>	ALLCACHES CLIPBOARDCACHE HISTORYCACHES UNDOCACHES	Cache to be targeted in an <a href="#">Application.purge()</a> operation.
<b>QueryStateType</b>	ALWAYS ASK NEVER	The preferred policy for checking whether to maximize compatibility when opening PSD files, set in <a href="#">Preferences.maximizeCompatibility</a> .
<b>RadialBlurMethod</b>	SPIN ZOOM	The blur method to use. Pass to <a href="#">ArtLayer.applyRadialBlur()</a> .
<b>RadialBlurQuality</b>	BEST DRAFT GOOD	The smoothness or graininess of the blurred image. Pass to <a href="#">ArtLayer.applyRadialBlur()</a> .
<b>RasterizeType</b>	ENTIRELAYER FILLCONTENT LAYERCLIPPINGPATH LINKEDLAYERS SHAPE TEXTCONTENTS	The layer element to rasterize, using <a href="#">ArtLayer.rasterize()</a> .
<b>ReferenceFormType</b>	CLASSTYPE ENUMERATED IDENTIFIER INDEX NAME OFFSET PROPERTY	The type of an <a href="#">ActionReference</a> object, returned by <a href="#">getForm()</a> .

Constant type	Values	What it means
<b>ResampleMethod</b>	AUTOMATIC BICUBIC BICUBICAUTOMATIC BICUBICSHARPER BICUBICSMOOTHER BILINEAR NEARESTNEIGHBOR NONE PRESERVEDETAILS	The method to use for image interpolation. Passed to <a href="#">Document.resizeImage()</a> , and used as the value of <a href="#">Preferences.interpolation</a> .
<b>RippleSize</b>	LARGE MEDIUM SMALL	The size of undulations to use. Pass to <a href="#">ArtLayer.applyRipple()</a> .
<b>SaveBehavior</b>	ALWAYS SAVE ASKWHENSAVING NEVERSAVE	The application's preferred behavior when saving a document. See <a href="#">Preferences.appendExtension</a> and <a href="#">imagePreviews</a>
<b>SaveDocumentType</b>	ALIASPIX BMP COMPUSEVEGIF ELECTRICIMAGE JPEG PCX PHOTOSHOP PHOTOSHOPDCS_1 PHOTOSHOPDCS_2 PHOTOSHOPEPS PHOTOSHOPPDF PICTfileFORMAT PICTRESOURCEFORMAT PIXAR PNG PORTABLEBITMAP RAW SCITEXCT SGIRGB SOFTIMAGE TARGA TIFF WAVEFRONTFLA WIRELESSBITMAP	The format in which to save a document when exporting with <a href="#">Document.exportDocument()</a> . Pass in <a href="#">ExportOptionsSaveForWeb.format</a> , to specify the type of file to write. Only the following are supported for export: COMPUSEVEGIF, JPEG, PNG-8, PNG-24, and BMP.
<b>SaveEncoding</b>	ASCII BINARY JPEGHIGH JPEGLOW JPEGMAXIMUM JPEGMEDIUM	The type of encoding to use when saving a file to DCS or EPS with <a href="#">Document.saveAs()</a> .
<b>SaveLogItemsType</b>	LOGFILE LOGFILEANDMETADATA METADATA	The preferred location of history log data, set in <a href="#">Preferences.saveLogItems</a> .
<b>SaveOptions</b>	DONOTSAVECHANGES PROMPTTOSAVECHANGES SAVECHANGES	The policy for closing a document with <a href="#">Document.close()</a> .

Constant type	Values	What it means
<b>SelectionType</b>	DIMINISH EXTEND INTERSECT REPLACE	The selection behavior when a selection already exists:  DIMINISH: Remove the selection from the already selected area.  EXTEND: Add the selection to an already selected area.  INTERSECT: Make the selection only the area where the new selection intersects the already selected area.  REPLACE: Replace the selected area.  Used in <a href="#">PathItem.makeSelection()</a> , <a href="#">Selection.load()</a> , <a href="#">Selection.select()</a> , and <a href="#">Selection.store()</a> .
<b>ShapeOperation</b>	SHAPEADD SHAPEINTERSECT SHAPESUBTRACT SHAPEXOR	How to combine the shapes if the destination path already has a selection.  Set for <a href="#">SubPathInfo.operation</a> , stored in the resulting <a href="#">SubPathItem</a> .
<b>SmartBlurMode</b>	EDGEONLY NORMAL OVERLAYEDGE	The method to use for smart blurring:  EDGEONLY, OVERLAYEDGES: Apply blur only to edges of color transitions.  NORMAL: Apply blur to entire image.  Pass to <a href="#">ArtLayer.applySmartBlur()</a> .
<b>SmartBlurQuality</b>	HIGH LOW MEDIUM	The blur quality to use. Pass to <a href="#">ArtLayer.applySmartBlur()</a> .
<b>SourceSpaceType</b>	DOCUMENT PROOF	The color space for source when printing with <a href="#">Document.print()</a> .
<b>SpherizeMode</b>	HORIZONTAL NORMAL VERTICAL	The curve (or stretch shape) to use for the distortion. Pass to <a href="#">ArtLayer.applySpherize()</a> .
<b>StrikeThruType</b>	STRIKEBOX STRIKEHEIGHT STRIKEOFF	The style of strikethrough to use in text. Used in <a href="#">TextItem.strikeThru</a> .
<b>StrokeLocation</b>	CENTER INSIDE OUTSIDE	The placement of path or selection boundary strokes. Pass to <a href="#">Selection.stroke()</a> .
<b>TargaBitsPerPixels</b>	SIXTEEN THIRTYTWO TWENTYFOUR	The resolution to use when saving an image in Targa format. Used in <a href="#">TargaSaveOptions</a> .

Constant type	Values	What it means
<b>TextCase</b>	ALLCAPS NORMAL SMALLCAPS	The capitalization style to use in text. Used in <a href="#">TextItem.capitalization</a> .
<b>TextComposer</b>	ADOBEEVERYLINE ADOBESINGLELINE	The composition method to use to optimize the specified hyphenation and justification options. Used in <a href="#">TextItem.textComposer</a> .
<b>TextType</b>	PARAGRAPHTEXT POINTTEXT	The type of text, used in <a href="#">TextItem.kind</a> .  PARAGRAPHTEXT: Text that wraps within a bounding box.  POINTTEXT: Text that does not wrap.
<b>TextureType</b>	BLOCKS CANVAS FILE FROSTED TINYLENS	The type of texture or glass surface image to load for a texturizer or glass filter. Pass to <a href="#">ArtLayer.applyGlassEffect()</a> .
<b>TIFFEncoding</b>	JPEG NONE TIFFLZW TIFFZIP	The type of compression to use for TIFF files. Used in <a href="#">TiffSaveOptions</a> .
<b>ToolType</b>	ARTHISTORYBRUSH BACKGROUNDERASER BLUR BRUSH BURN CLONESTAMP COLORREPLACEMENTTOOL DODGE ERASER HEALINGBRUSH HISTORYBRUSH PATTERNSTAMP PENCIL SHARPEN SMUDGE SPONGE	The tool to use with <a href="#">PathItem.strokePath()</a> .
<b>TransitionType</b>	BLINDSHORIZONTAL BLINDVERTICAL BOXIN BOXOUT DISSOLVE GLITTERDOWN GLITTERRIGHT GLITTERRIGHTDOWN NONE RANDOM SPLITHORIZONTALIN SPLITHORIZONTALOUT SPLITVERTICALIN SPLITVERTICALOUT WIPEDOWN WIPELEFT WIPERIGHT WIPEUP	The method to use for transition from one image to the next in a PDF presentation. Used in <a href="#">PresentationOptions</a> .

Constant type	Values	What it means
<b>TrimType</b>	BOTTOMRIGHT TOPLEFT TRANSPARENT	Type of pixels to trim around an image, passed to <a href="#">Document.trim()</a> :  BOTTOMRIGHT = bottom right pixel color.  TOPLEFT = top left pixel color.
<b>TypeUnits</b>	MM PIXELS POINTS	The preferred unit for text character measurements, set in <a href="#">Preferences</a> .
<b>UndefinedAreas</b>	REPEATEDGEPIXELS WRAPAROUND	The method to use to treat undistorted areas or areas left blank in an image to which the a filter in the Distort category has been applied. Pass to <a href="#">ArtLayer.applyDisplace()</a> , <a href="#">applyShear()</a> , <a href="#">applyWave()</a> .
<b>UnderlineType</b>	UNDERLINELEFT UNDERLINEOFF UNDERLINERIGHT	The placement of text underlining. Used in <a href="#">TextItem.underline</a> .  <b>Note:</b> UNDERLINELEFT and UNDELINERIGHT are valid only when <code>direction = Direction.VERTICAL</code> .
<b>Units</b>	CM INCHES MM PERCENT PICAS PIXELS POINTS	The preferred measurement unit for type and ruler increments, set in <a href="#">Preferences.rulerUnits</a> .
<b>Urgency</b>	FOUR HIGH LOW NONE NORMAL SEVEN SIX THREE TWO	The editorial urgency status of a document, set in <a href="#">DocumentPrintSettings.urgency</a> .
<b>WarpStyle</b>	ARC ARCH ARCLOWER ARCUPPER BULGE FISH FISHEYE FLAG INFLATE NONE RISE SHELLLOWER SHELLUPPER SQUEEZE TWIST WAVE	The warp style to use for text. Used in <a href="#">TextItem.warpStyle</a> .

Constant type	Values	What it means
<b>WaveType</b>	SINE SQUARE TRIANGULAR	The type of wave to use. Pass to <a href="#">ArtLayer.applyWave()</a> .
<b>WhiteBalanceType</b>	ASSHOT AUTO CLOUDY CUSTOM DAYLIGHT FLASH FLUORESCENT SHADE TUNGSTEN	Lighting conditions that affect color balance. Set in <a href="#">CameraRAWOpenOptions</a> .
<b>ZigZagType</b>	AROUNDCENTER OUTFROMCENTER PONDRI PPLES	The method of zigzagging to use. Pass to <a href="#">ArtLayer.applyZigZag()</a> .

## Appendix A: Event ID Codes

The following table lists events and their four-character ID codes or string identifiers for use with the `notifier` object.

**Note:** Do not include single quotes ( ' ) with four-character IDs in your code. The single quotes are used in this table to illustrate the placement of required spaces in codes that do not contain four letters. However, string identifiers, which are longer than four characters, require double quotes in the code.

**Tip:** If you can't find the event you want to use for notification in this table, you can use `ScriptListener` to determine the event ID code. See the `ScriptListener` documentation in the Action Manager chapter of the *Photoshop CC 2014 Scripting Guide*.

Event	4-char ID or String
3DTransform	'TdT '
Average	'Avrg'
ApplyStyle	'ASty'
Assert	'Asrt'
AccentedEdges	'AccE'
Add	'Add '
AddNoise	'AdNs'
AddTo	'AddT'
Align	'Algn'
All	'All '
AngledStrokes	'AngS'
ApplyImage	'AppI'
BasRelief	'BsRl'
Batch	'Btch'
BatchFromDroplet	'BtcF'
Blur	'Blr '
BlurMore	'BlrM'
Border	'Brdr'
Brightness	'BrgC'
CanvasSize	'CnvS'
ChalkCharcoal	'ChlC'
ChannelMixer	'ChnM'



<b>Event</b>	<b>4-char ID or String</b>
Charcoal	'Chrc'
Chrome	'Chrm'
Clear	'Cler'
Close	'Cls '
Clouds	'Clds'
ColorBalance	'ClrB'
ColorHalftone	'ClrH'
ColorRange	'ClrR'
ColoredPencil	'ClrP'
ContactSheet	"0B71D221-F8CE-11d2-B21B-0008C75B322C"
ConteCrayon	'CntC'
Contract	'Cntc'
ConvertMode	'CnvM'
Copy	'copy'
CopyEffects	'CpFX'
CopyMerged	'CpyM'
CopyToLayer	'CpTL'
Craquelure	'Crql'
CreateDroplet	'CrtD'
Crop	'Crop'
Crosshatch	'Crsh'
Crystallize	'Crst'
Curves	'Crvs'
Custom	'Cstm'
Cut	'cut '
CutToLayer	'CtTL'
Cutout	'Ct '
DarkStrokes	'DrkS'
DeInterlace	'Dntr'
DefinePattern	'DfnP'
Defringe	'Dfrg'
Delete	'Dlt '
Desaturate	'Dstt'

<b>Event</b>	<b>4-char ID or String</b>
Deselect	'Dslc'
Despeckle	'Dspc'
DifferenceClouds	'DrfC'
Diffuse	'Dfs '
DiffuseGlow	'DfsG'
DisableLayerFX	'dlfx'
Displace	'Dspl'
Distribute	'Dstr'
Draw	'Draw'
DryBrush	'DryB'
Duplicate	'Dplc'
DustAndScratches	'DstS'
Emboss	'Embs'
Equalize	'Eqlz'
Exchange	'Exch'
Expand	'Expn'
Export	'Expr'
JumpTo	'Jpto'
ExportTransparentImage	"02879e00-cb66-11d1-bc43-0060b0a13dc4"
Extrude	'Extr'
Facet	'Fct '
Fade	'Fade'
Feather	'Fthr'
Fibers	'Fbrs'
Fill	'Fl '
FilmGrain	'FlmG'
Filter	'Fltr'
FindEdges	'FndE'
FitImage	"3caa3434-cb67-11d1-bc43-0060b0a13dc4"
FlattenImage	'FltI'
Flip	'Flip'
Fragment	'Frgm'
Fresco	'Frsc'

<b>Event</b>	<b>4-char ID or String</b>
GaussianBlur	'GsnB'
Get	'getd'
Glass	'Gls '
GlowingEdges	'GlwE'
Gradient	'Grdn'
GradientMap	'GrMp'
Grain	'Grn '
GraphicPen	'GraP'
Group	'GrpL'
Grow	'Grow'
HalftoneScreen	'Hlfs'
Hide	'Hd '
HighPass	'HghP'
HSBHSL	'HsbP'
HueSaturation	'HStr'
ImageSize	'ImgS'
Import	'Impr'
InkOutlines	'InkO'
Intersect	'Intr'
IntersectWith	'IntW'
Inverse	'Invs'
Invert	'Invr'
LensFlare	'LnsF'
Levels	'Lvls'
LightingEffects	'LghE'
Link	'Lnk '
Make	'Mk '
Maximum	'Mxm '
Median	'Mdn '
MergeLayers	'Mrg2'
MergeLayersOld	'MrgL'
MergeSpotChannel	'MSpt'
MergeVisible	'MrgV'

<b>Event</b>	<b>4-char ID or String</b>
Mezzotint	'Mztn'
Minimum	'Mnm '
ModeChange	"8cba8cd6-cb66-11d1-bc43-0060b0a13dc4"
Mosaic	'Msc '
Mosaic_PLUGIN	'MscT'
MotionBlur	'MtnB'
Move	'move'
NTSCColors	'NTSC'
NeonGlow	'NGLw'
Next	'Nxt '
NotePaper	'NtPr'
Notify	'Ntfy'
Null	typeNull
OceanRipple	'OcnR'
Offset	'Ofst'
Open	'Opn '
Paint	'Pnt '
PaintDaubs	'PntD'
PaletteKnife	'PltK'
Paste	'past'
PasteEffects	'PaFX'
PasteInto	'PstI'
PasteOutside	'PstO'
Patchwork	'Ptch'
Photocopy	'Phtc'
PicturePackage	"4C1ABF40-DD82-11d2-B20F-0008C75B322C"
Pinch	'Pnch'
Place	'Plc '
Plaster	'Plst'
PlasticWrap	'PlsW'
Play	'Ply '
Pointillize	'Pntl'
Polar	'Plr '

<b>Event</b>	<b>4-char ID or String</b>
PosterEdges	'PstE'
Posterize	'Pstr'
Previous	'Prvs'
Print	'Prnt'
ProfileToProfile	'PrfT'
Purge	'Prge'
Quit	'quit'
RadialBlur	'RdlB'
Rasterize	'Rstr'
RasterizeTypeSheet	'RstT'
RemoveBlackMatte	'RmvB'
RemoveLayerMask	'RmvL'
RemoveWhiteMatte	'RmvW'
Rename	'Rnm '
ReplaceColor	'RplC'
Reset	'Rset'
ResizeImage	"1333cf0c-cb67-11d1-bc43-0060b0a13dc4"
Reticulation	'Rtcl'
Revert	'Rvrt'
Ripple	'Rple'
Rotate	'Rtte'
RoughPastels	'RghP'
Save	'save'
Select	'slct'
SelectiveColor	'SlcC'
Set	'setd'
SharpenEdges	'ShrE'
Sharpen	'Shrp'
SharpenMore	'ShrM'
Shear	'Shr '
Show	'Shw '
Similar	'Smlr'
SmartBlur	'SmrB'

<b>Event</b>	<b>4-char ID or String</b>
Smooth	'Smth'
SmudgeStick	'SmdS'
Solarize	'Slrz'
Spatter	'Spt '
Spherize	'Sphr'
SplitChannels	'SplC'
Sponge	'Spng'
SprayedStrokes	'SprS'
StainedGlass	'StnG'
Stamp	'Stmp'
Stop	'Stop'
Stroke	'Strk'
Subtract	'Sbtr'
SubtractFrom	'SbtF'
Sumie	'Smie'
TakeMergedSnapshot	'TkMr'
TakeSnapshot	'TkSn'
TextureFill	'TxtF'
Texturizer	'Txtz'
Threshold	'Thrs'
Tiles	'Tls '
TornEdges	'TrnE'
TraceContour	'TrcC'
Transform	'Trnf'
Trap	'Trap'
Twirl	'Twrl'
Underpainting	'Undr'
Undo	'undo'
Ungroup	'Ungr'
Unlink	'Unlk'
UnsharpMask	'UnsM'
Variations	'Vrtn'
Wait	'Wait'

<b>Event</b>	<b>4-char ID or String</b>
WaterPaper	'WtrP'
Watercolor	'Wtrc'
Wave	'Wave'
Wind	'Wnd '
ZigZag	'ZgZg'
BackLight	'BacL'
FillFlash	'File'
ColorCast	'ColE'

# Index

## A

Action Manager 193  
actions  
    command lists 40  
    descriptions 43  
    descriptors 37  
    playing 47  
active document 45  
activePrinter 96  
Add Noise filter  
adjustments  
    brightness 55  
    color 197  
    color balance 55, 61  
    contrast 55, 59  
    curves 55  
    highlights 62  
    levels 55, 59  
    shadows 62  
    temperature 61  
Adobe Illustrator, exporting paths to 105  
alpha channels  
    defined 72  
    from transparency (TIFF documents) 186  
    opacity 72  
    saving  
        in BMP documents 69  
        in PDF documents 148  
        in PICT documents 153  
        in PICT resources 154  
        in Pixar documents 156  
        in PSD documents 152  
        in RAW documents 164  
        in SGIRGB documents 171  
        in Targa documents 176  
        in TIFF documents 186  
anchor points  
    adding 143  
annotations, importing 92  
anti aliasing  
    text 179  
application  
    activating 47  
    checking if feature enabled 47  
    defaults 158  
    location 46  
    preferences 158  
artLayers, *See* layers  
Asian text 160  
authors 99  
auto kerning 179, 197  
auto leading 184  
auto spacing, contact sheets 82

available memory 45  
Average filter 55

## B

background color  
    application 45  
    galleries 110  
background layers 53  
backgroundColor 96  
baseline shift 179  
batch command 47  
batches  
    destination folder 66, 197  
    specifying options 66  
beeping 158  
bitmap documents  
    converting to 198  
    depth type 198  
    halftone type 198  
    opening 207  
    saving 69  
bitmap images  
    *See* bitmap documents  
black and white images 62  
bleedWidth 96  
blending modes  
    layer sets 129  
    layers 53  
Blur filter 55  
blur filters  
    Average 55  
    Blur More 55  
    Gaussian Blur 56  
    Lens Blur 57  
    Motion Blur 58  
    Radial Blur 58  
    Smart Blur 59  
Blur More filter 55  
BMP documents  
    *See* bitmap documents  
brightness 55  
    adjusting 55  
    equalizing 60  
build 45

## C

caches  
    images 159  
    purging 49  
camera raw documents  
    opening 70  
    settings 199  
    size options 199



- canvas
    - flipping 92
    - resizing 92
  - canvas, defined 88
  - caption 96
  - captions
    - contact sheets 82
    - documents 99
    - gallery images 111
    - gallery thumbnails 115
    - images 99
  - centerCropMarks 96
  - channels
    - activating 88
    - adding 74
    - adjusting 55
    - alpha *See* alpha channels
    - creating 74
    - deleting 72
    - displaying in color 158
    - duplicating 72
    - making visible 72
    - merging 72
    - mixing 61
    - splitting 93
    - spot *See* spot channels
    - types of 72
  - clipping paths
    - from paths 139
    - from text 185
  - Clouds filter 55
  - CMYKColor 79
  - color balance, adjusting 61
  - color picker 158
  - color profiles
    - changing 91
    - determining type of 89
    - naming 88
  - color profiles, *see* individual document formats
  - color samplers
    - adding 81
    - creating 81
    - moving 80
    - removing 80
  - colorBars 96
  - colorHandling 96
  - colors
    - active links 110
    - adjusting 197
    - balancing 55
    - channels 72
    - CMYK 79
    - custom settings 113
    - in galleries 110
    - inverting 60
    - modifying 62
    - none 135
    - preserving (GIF only) 116
    - reduction 106
    - settings 45
    - solid color objects 172
    - testing if equal 172
    - visited links 110
  - comments, layer comps 126
  - compatibility, maximizing 159
  - component channels
    - color balance 55
    - defined 72
    - listing 88
    - See* composite channels
  - composite channels 72
    - See* component channels
  - Compuserve GIF documents
    - opening 207
    - saving 116
  - contact sheets
    - captions 82
    - columns 82
    - dimensions 82
    - making 48
    - rows 82
  - contrast
    - adjusting 55
    - adjusting automatically 59
    - camera raw settings 70
    - midtones 62
  - copies 96
  - copyrights 99
  - cornerCropMarks 96
  - count items
    - adding 84
    - creating 84
    - removing 83
  - cropping 91
  - cursors 160
  - curves, adjusting 55
  - Custom filters 55
- D**
- DCS 1 documents, saving 85
  - De-Interlace filter 56
  - desaturate 60
  - Despeckle filter 56
  - dialogs
    - displaying 45
  - Difference Clouds filter 56
  - Diffuse Glow filter 56
  - Displace filter 56
  - distort filters
    - Diffuse Glow 56
    - Displace 56
    - Glass Effect 56
    - Ocean Ripple 58
    - Pinch 58
    - Polar Coordinates 58
    - Ripple 58
    - Shear 58
    - Spherize 59
    - Twirl 59

- Wave 59
- Zigzag 59
- document formats, *see* individual document formats
- DocumentPrintSettings 96
- documents 88
  - activating 45
  - adding 102
  - closing 90
  - code sample 94
  - color profiles 88
  - color samplers 88
  - counting items 89
  - counting objects 91
  - cropping 36, 91
  - dimensions 88
  - duplicating 36, 91
  - exporting 92
  - info 99
  - loading 48
  - managed 89
  - measurement scale 89
  - metadata 89, 99
  - open with Photoshop dialog 49
  - opening 49
  - optimizing for web 106
  - printing 92
  - resizing 92
  - resolution 90
  - saving 92, 93
  - suspending history 93
  - trapping (CMYK) 93
  - trimming 94
- Dust and Scratches filter 56

**E**

- Enable Info
  - constants 191
  - grammar 190
  - operator precedence 191
  - variables 192
- EPSSaveOptions 104
- equalize 60
- event IDs
  - using ScriptListener to find 216
- Events Manager 46
- executing scripts 33
- exif 99
- exporting
  - documents 92
  - paths 105
  - to Illustrator 105
  - to Web 106
- ExportOptionsIllustrator 105
- ExportOptionsSaveForWeb 106

**F**

- file extensions
  - format 161
  - including 158

- script files 32
- file metadata 99
- files
  - merging 48
- filetypes
  - macOS 46
  - Windows 47
- filling
  - paths 138
  - selections 167
- filter, *see* individual filter names
- flip 96
- Folder object 32
- fonts
  - detecting 45
  - determining family of 177
  - determining style of 177
- formats, *see* individual document formats

**G**

- galleries 113
  - background color 110
  - banners 109
  - captions 111
  - color options 110
  - credits 111
  - dimensions 111
  - filenames 111
  - link colors 110
  - making 47, 48
  - metadata 113
  - photographer 109
  - security text 114
  - thumbnail images 115
- GalleryBannerOptions 109
- GalleryCustomColorOptions 110
- GalleryImagesOptions 111, 112
- GalleryOptions 113
- GallerySecurityOptions 114
- GalleryThumbnailOptions 115
- Gaussian Blur filter 56
- GIF documents
  - See* Compuserve GIF documents
- GIFSaveOptions 116
- Glass Effect filter 56
- glyph scaling 179–182
- GrayColor 117
- grids 159
- grouped layers 53
- guides 159

**H**

- halftone screen 68
- hanging punctuation 180
- hardProof 96
- High Pass filter 56
- highlights
  - adjusting 62
  - color balance 55

- histograms
    - channels 72
  - history log 161
  - history states
    - activating 88
    - allowing nonlinear 159
    - default number of 160
    - snapshot 120
    - suspending 93
  - HSBColor 122
  - hyphenation 181
- I**
- IDs
    - getting 37
    - PICT Resource 154
    - property 43
    - runtime 47
    - runtime to string 50
    - string to runtime 50
    - string to type 50
    - type to char 50
  - Illustrator
    - See Adobe Illustrator
  - image
    - resizing 93
  - image pyramids 186
  - images
    - bitmap 68
    - black and white 62
    - caches 159
    - captions 111
    - definition of 88
    - desaturating 60
    - equalizing 60
    - filetypes 46
    - from split channels 93
    - inverting colors 60
    - previewing 159
    - pyramids 186
    - resizing 92
    - resizing in galleries 112
    - thumbnails 115
  - indexed color model 123
  - IndexedConversionOptions 123
  - individual document formats, examples 93
  - installing scripts 33
  - Intent 96
  - interpolate 96
  - interpolation 159
- J**
- JavaScript
    - supported features 32
  - JavaScript Resource
    - Enable Info grammar 190
    - javascriptresource syntax 189
  - javascriptresource tag 189
  - JPEG
    - quality 124
  - JPEG documents
    - quality 124
    - saving 124
  - JPEG options
    - scans 124
  - JPEGSaveOptions 124
  - justification 181
- K**
- kerning 179
    - text
      - auto kerning 197
  - keyboard behavior 159
- L**
- LabColor 125
  - labels 96
  - languages 181
  - layer comps 126
    - adding 127
    - applying 126
    - in documents 89
  - layer sets
    - adding 131
    - art layers in 129
    - duplicating 130
    - in documents 89
    - linked layers in 129
    - linking 130
    - locking contents 129
    - moving 130
    - nesting 129
    - opacity 129
    - unlinking 130
  - layer styles, applying 59
  - LayerComps 127
  - layered TIFFdocuments, saving 158
  - Layers 128
  - layers
    - adding 65
    - applying styles 59
    - background 53
    - blending mode 53
    - bounds 53
    - clipboard commands 59
    - comps 126
    - copying 59
    - duplicating 60
    - flattening 92
    - grouping 53
    - in documents 89
    - inverting 60
    - kind 53
    - linking 60
    - locking contents 53–54
    - making visible 54
    - merging 60
    - merging visible 92

- moving 61
- rasterizing 92
- rasterizing contents 61
- removing 65
- resizing 62
- rotating 62
- saving in PDF documents 148
- unlinking 62

LayerSet 129

LayerSets 131

layersets

- merging 130

leading 181, 184

Lens Blur filter

- applying 57

Lens Flare filter 57

letter spacing 180–183

levels

- adjusting 55

- adjusting automatically 55

ligatures 179–181

linked layers 60

- unlinking 62

links

- colors 110

## M

MacOS

- filetypes 46

managed documents 89

mapBlack 96

maximizing compatibility 159

Maximum filter 57

Median Noise filter 57

memory 45

merging

- layers 60

- visible layers 92

metadata

- document 89

- document object 99

- galleries 113

- xmp 90, 188

methods

- batch 47

midtones

- color balance 55

Minimum filter 58

Motion Blur filter 58

## N

negative 96

noise filters

- Add Noise

- Despeckle 56

- Dust and Scratches 56

- Median Noise 57

nonlinear history 159

notifications

- events within scripts 136

notifiers

- adding 137

- event IDs 216

- removing 136

NTSC filter 58

## O

Ocean Ripple filter 58

Offset filter 58

old style type 183

opacity

- channels 72

- gallery security text 114

- layer fill 53

- layer sets 129

- layers 54

- picture packages 155

open options

- DICOM format 87

- EPS format 103

- PDF format 147

- Photo CD format 151

- RAW format 70, 163

optimizing 106

other filters

- Custom 55

- High Pass 56

- Maximum 57

- Minimum 58

- Offset 58

## P

palettes 160

pasting 92

path 46

path items

- adding 142

- deselecting 138

- filling 138

- from text 185

- making selection 139

- path points 174

- selecting 139

- specifying path kind 138

- stroking 139

- sub items 138

- sub path info 173

- sub path items 174

- work path from selection 167

path point info

- anchor points 144

- left direction 144

- right direction 144

path points

- anchor points 143

- left direction 143

- right direction 143

PathItems 142

- paths
    - See *path items*
  - PDF documents
    - opening 147
    - saving 148
  - PDF presentations
    - auto advance 162
    - making 48
    - output format 162
    - transition type 162
  - Photo CD discs, opening 151
  - photo filtering 61
  - photo galleries
    - See *galleries*
  - photomerge 48
  - Photoshop documents
    - opening 207
    - saving 152
  - Photoshop files, maximizing compatibility 159
  - PICT documents
    - opening 207
    - saving 153
  - PICT resources
    - opening 207
    - saving 154
  - picture packages
    - contents 155
    - flattening 155
    - making 48
    - opacity 155
    - options 155
    - text properties 155
  - Pinch filter 58
  - Pixar documents
    - opening 207
    - saving 156
  - PixarSaveOptions 156
  - pixels
    - aspect ratio 89
    - doubling 160
    - equalizing 60
    - interpolation 159
    - locking 54
    - unit measures 214
  - playback options 46
  - playbackDisplayDialogs 46
  - plug-in folder
    - additional plug-in folder 161
  - PNG 8 documents, saving 106
  - PNG documents
    - saving 157
  - PNGSaveOptions 157
  - Polar Coordinates filter 58
  - posterrize 61
  - postscript encoding 92
  - PostScript names 177
  - posX 96
  - posY 96
  - Preferences 158
  - PresentationOptions 162
  - presentations
    - making 48
    - PDF presentations
  - printBorder 96
  - printing, documents 92
  - printOneCopy 92
  - printSelected 96
  - printSettings 89
  - printSpace 96
  - property
    - measurementLog 46
  - PSD documents
    - opening 207
    - saving 152
  - purging 49
- Q**
- quickMaskMode 90
  - quote style 160
- R**
- Radial Blur filter 58
  - rasterize 61
  - rasterizing
    - document layers 92
  - RAW documents
    - opening 163
  - RawSaveOptions 164
  - recentFiles 46
  - registrationMarks 96
  - render filters
    - Clouds 55
    - Difference Clouds 56
    - Lens Flare 57
  - renderIntent 96
  - resolution
    - bitmap conversions 68
    - documents 90
  - RGBColor 165
  - Ripple filter 58
  - rotation 62
  - ruler units 160
  - runMenultem 49
- S**
- save as 93
  - saved 90
  - saving 92
  - saving, *see individual document formats.*
  - scale 97
  - scripting interface
    - build date 46
    - version 46
  - scriptingVersion 46
  - scripts
    - automation 189, 193
    - enabling/disabling in menu 189
    - executing 33

- grouping in menu 189
- installing 33
- startup 33
- terminology dictionary 193
- valid file extensions 32
- Scripts Events Manager 46
- selected areas 90
- selections 166
  - boundaries 166
  - clearing 166
  - copying 166
  - cutting 166
  - deselecting 166
  - feathering 166
  - filling 167
  - from paths 139
  - making work path from 167
  - resizing 166, 167
  - rotating 167
  - smoothing 168
  - stroking 168
- selective color 62
- SGIRGB documents
  - saving 171, 211
- SGIRGBSaveOptions 171, 197
- shadows
  - adjusting 62
  - color balance 55
- Sharpen Edges filter 58
- Sharpen filter 58
- sharpen filters
  - Sharpen 58
  - Sharpen Edges 58
  - Sharpen More 58
  - Unsharp Mask 59
- Sharpen More filter 58
- Shear filter 58
- Smart Blur filter 59
- smart quotes 160
- Spherize filter 59
- spot channels
  - defined 72
  - merging into component channels 73
  - opacity 72
  - saving
    - in DCS 2 documents 86
    - in PDF documents 149
    - in PSD documents 152
    - in RAW documents 164
    - in SGIRGB documents 171
    - in TIFF documents 186
- spotColors 171
- startup scripts 33
- strike thru 184
- stroking
  - default stroke color 45
  - path items 139
  - selections 168
- styles, applying 59
- sub path items 138

- systemInformation 46

## T

- temperature 61
- terminology dictionary
  - defined 193
  - syntax 193
- text
  - Asian 160
  - auto kerning 179
  - auto leading 184
  - captions 111
  - color
  - composer 184
  - content 179
  - creating paths from 185
  - formatting 184
  - gallery security 114, 204
  - hyphenation 181
  - in picture packages 155
  - justification 181
  - languages 181
  - offset 179
  - orientation 180
  - spacing 180–183
  - tracking 184
  - wrapping 181
- text composer 184
- text fonts
  - See fonts
- text items
  - See text
- text layers
  - adding contents 179
  - creating 53
- Texture Fill filter 59
- texture filters, Texture Fill 59
- threshold 62
- thumbnails 115
  - Mac OS 159
  - Windows 161
- TIFF documents
  - layered 158
  - saving 186
- togglePalettes 50
- tool tips 160
- tracking, text 184
- transmission info 99
- trapping 93
- Twirl filter 59
- type units 161

## U

- underlining 184
- units
  - ruler 160
  - type 161
- UnitValue object 32, 187
- Unsharp Mask filter 59

URLs, document 99  
UTF8 Encoding 113

## V

vectorData 97  
version  
    application 47  
    scripting interface 46  
video alpha 161  
video filters  
    De-Interlace 56  
    NTSC 58  
visibility  
    channels 72  
    layer comps 126  
    layers 54

## W

warp 184  
Wave filter 59

Web photo galleries  
    See galleries.  
webSnap 107  
width 90  
Windows  
    filetypes 47  
word spacing 180–183  
work paths  
    designating 208  
    from selected area 167  
wrapping, text 181

## X

XML 188  
xmp metadata 90, 188

## Z

Zigzag filter 59  
zoom 159